2-Port USB/VGA Cable KVM Switch with Audio, Cables and USB Peripheral Sharing

MODEL NUMBER: **B032-VUA2**

Highlights

- Built-in 4-ft. (1.22 m) VGA, USB and audio cables and 3.5 mm speaker jack
- Supports video resolutions up to 2048 x 1536
- Hotkey and mouse port switching
- Compatible with Windows®, Mac®, Sun and Linux®
- Plug and play—no software, drivers or external power required

System Requirements

- VGA, SVGA or multisync monitor
- USB keyboard
- USB mouse
- Speakers with 3.5 mm audio jack
- Computers with VGA and USB ports

Package Includes

- B032-VUA2 2-Port USB/VGA Cable KVM Switch
- Owner's manual

Control 2 computers using one VGA monitor, USB keyboard and USB mouse. Connect a USB hub (sold separately) to share USB peripherals, such as printers and hard drives, between computers.

Features

Access and Control 2 Computers with One Keyboard/Mouse/Monitor
- Recommended for home, office, gaming and multimedia applications

- Switch between computers using hotkeys or mouse wheel

- Supports video resolutions up to 2048 x 1536

- Compliant with EDID

- Built-in 4-ft. (1.22 m) VGA, USB and audio cables and 3.5 mm speaker jack

Independent USB Peripheral Sharing
- Adding an optional USB hub (sold separately) to the USB console mouse port allows connection of peripherals, such as printers, hard drives, scanners, webcams and thumb drives

Flexible Keyboard/Mouse Applications
- Console mouse port emulation/bypass supports most mouse drivers and multifunction mice

- Works with gaming keyboards and wireless keyboards and mice

- Supports Mac and Sun keyboard emulation

Easy Plug-and-Play Setup and Use
- Compatible with Windows, Mac, Sun and Linux

- Plug and play—no software, drivers or external power required

Specifications

OVERVIEW	
UPC Code	037332200372
Technology	Stereo Audio; VGA/SVGA

VIDEO	
Max Supported Video Resolution	2048 x 1536

INPUT	
Built-In Cable Length (ft.)	4
Built-In Cable Length (m)	1.2
Built-In Cable Length (in.)	48
Built-In Cable Length (cm)	121.9
Redundancy - Dual Power Inputs	No
Bus Powered	Yes

POWER	
Power Consumption (Watts)	0.33

USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	(x2) Port Selected (Green)

PHYSICAL	
Material of Construction	Plastic
Color	Black
Rackmountable	No
Shipping Dimensions (hwd / cm)	5.89 x 23.90 x 17.50
Shipping Dimensions (hwd / in.)	2.32 x 9.41 x 6.89
Shipping Weight (kg)	0.31
Shipping Weight (lbs.)	0.68
Unit Dimensions (hwd / in.)	1 x 2.6 x 3.1
Unit Dimensions (hwd / cm)	2.6 x 6.6 x 7.9
Unit Weight (lbs.)	0.7
Unit Weight (kg)	0.32

ENVIRONMENTAL	
Operating Temperature Range	32 to 122 F (0 to 50 C)
Storage Temperature Range	-4 to 140 F (-20 to 60 C)

Relative Humidity	0 to 80% RH, Non-Condensing

COMMUNICATIONS

IP Remote Access	No

CONNECTIONS

Number of Ports	2
PC/Server Connections	USB; VGA
Side A - Connector 1	HD15 (FEMALE)
Side A - Connector 2	(2) USB A (FEMALE)
Side A - Connector 3	3.5MM (FEMALE)
Side B - Connector 1	(2) HD15 (MALE)
Side B - Connector 2	(2) USB A (MALE)
Side B - Connector 3	(2) 3.5MM (MALE)
Computer Keyboard and Mouse Interface	USB
Computer Monitor Interface	VGA
Console Keyboard and Mouse Interface	USB
Console Monitor Interface	VGA

FEATURES & SPECIFICATIONS

Number of Users	1
NIAP-Certified Secure	No
On-Screen Display (OSD)	No
Port Selection	Hotkey; Mouse
USB Hub Ports	Yes
Number of USB Hub Ports	1
USB Specification	USB 1.1 (up to 12 Mbps)
Driver Required	No
Cat5 KVM Switch	No

REMOTE ACCESS

Modem Port	No

WARRANTY

Product Warranty Period (Worldwide)	3-year limited warranty