

Tripp Lite

1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

## Power-on-Cable (PoC)

MODEL NUMBER: 0SU60020







### Description

Completing the OOB Remote Support package

Maximizing power efficiency

Unique "power cord" design

### **Features**

- Seamless integration with KVM and IP devices
- · Modular design allows expandability
- 90-260 VAC / 44-66 Hz international coverage
- Current consumption up to 10A
- Flexible power redundancy
- Unique design & 0U footprint
- Easy 3rd party integration with open standard protocol
- Galvanic Separation no physical connection between management and power device
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

# **Specifications**

**OVERVIEW** 

### **Highlights**

- Seamless integration with PX and IP Control remote access units
- Modular design allows expandability
- 90-260 VAC / 44-66 Hz international coverage
- Current consumption up to 10A
- Flexible power redundancy
- Unique design & 0U footprint
- Easy 3rd party integration with open standard protocol
- Galvanic Separation no physical connection between management and power device
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### **System Requirements**

KVM

### **Package Includes**

 For use with PX (Model #0SU70028) and IP Control (Model #0SU70017) remote access units





| UPC Code                            | 037332185501             |
|-------------------------------------|--------------------------|
| Accessory Type                      | Server Interface Unit    |
| PHYSICAL                            |                          |
| Color                               | Black                    |
|                                     |                          |
| Shipping Dimensions (hwd / cm)      | 6.60 x 16.76 x 22.35     |
| Shipping Dimensions (hwd / in.)     | 2.60 x 6.60 x 8.80       |
| Shipping Weight (kg)                | 0.45                     |
| Shipping Weight (lbs.)              | 1.00                     |
|                                     |                          |
| ENVIRONMENTAL                       |                          |
| Storage Temperature Range           | -15 to 50 C / 5 to 122 F |
| Relative Humidity                   | 0 to 95%                 |
| Operating Temperature               | 0 to 50 C / 32 to 122 F  |
|                                     |                          |
| WARRANTY                            |                          |
| Product Warranty Period (Worldwide) | 3-year limited warranty  |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>