

## VGA with Audio over Cat5/Cat6 Transmitter and Receiver with Repeater Kit, Box-Style, 1920x1440 60 Hz, Up to 1000 ft. TAA

MODEL NUMBER: B130-111A



### Features

- Kit comes with both local transmitter and remote/repeater units.
- Locate multiple sets of monitors and speakers at different points in a chain of up to 2,000 ft. by connecting additional receiver (B132-100A or B132-100A-WP-1) or repeater (B132-110A) units.
- Up to 4 remote units (3 repeaters and 1 receiver) can be connected together, providing audio/video to up to 4 sets of monitors and speakers
- 24Awg, Solid Wire Cat5e/6 cable, such as Tripp Lite's N022-01K-GY (Cat5) and N222-01K-GY (Cat6), is required to achieve maximum distance and resolution
- For optimal image quality between 500 and 1,000 ft., use Zero-Skew cable, such as Tripp Lite P524-01K
- Extend a 1920 x 1440 (60Hz) video and audio signal up to 500 ft., or a 1024 x 768 (60Hz) video and audio signal up to 1,000 ft., between the local transmitter and the first remote/repeater unit in the installation.
- Extend a 1920 x 1440 (60Hz) video and audio signal up to an additional 500 ft., or a 1024 x 768 (60Hz) video and audio signal up to an additional 1,000 ft., from the first remote/repeater unit to the last set of display and speakers in the installation.
- Features built-in Equalization and Gain controls for video image adjustment.
- Includes mounting hardware that allows wall mounting, rackmounting or pole mounting.
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

### Highlights

- Kit comes with both local transmitter and remote/repeater units
- Locate multiple sets of monitors and speakers at different points in a chain of up to 2,000 ft. by connecting additional receiver (B132-100A or B132-100A-WP-1) or repeater (B132-110A) units
- Up to 4 remote units (3 repeaters and 1 receiver) can be connected together, providing audio/video to up to 4 sets of monitors and speakers
- 24Awg, Solid Wire Cat5e/6 cable, such as Tripp Lite's N022-01K-GY (Cat5) and N222-01K-GY (Cat6), is required to achieve maximum distance and resolution
- For optimal image quality between 500 and 1,000 ft., use Zero-Skew cable, such as Tripp Lite P524-01K
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### System Requirements

- Computer with VGA video and 3.5mm Audio outputs
- Monitor / TV / Speakers with VGA and 3.5mm Audio inputs

### Package Includes

- B130-111A local transmitter unit
- B130-111A remote/repeater unit
- (2) External Power Supplies with NEMA 1-15P Plug (Input: 100-240V, 50/60Hz, 0.5A; 5V, 2A, 5 ft.)
- Screwdriver for video adjustment
- Mounting hardware
- Owner's manual

## Specifications



|                                 |   |
|---------------------------------|---|
| UPC Code                        | 037332161628                                  |
| Product Type                    | Extender Kit                                  |
| Technology                      | VGA/SVGA; Stereo Audio; Cat5/5e; Cat6         |
| <b>VIDEO</b>                    |   |
| Max 720P Range (ft)             | 500   |
| Max 1080P Range (ft)            | 500   |
| HDR Support                     | No  |
| 3D Video Supported              | No  |
| Maximum Signal Range (ft)       | 1000  |
| Maximum Signal Range (m)        | 305   |
| <b>INPUT</b>                    |   |
| Bus Powered                     | No  |
| <b>POWER</b>                    |   |
| Power Over Cable (PoC) Support  | No  |
| AC Adapter                      | Input: 100-240V, 50/60Hz, 0.5A; 5V, 2A, 5 ft. |
| <b>PHYSICAL</b>                 |   |
| Color                           | Black   |
| Number of Displays              | 1   |
| Form Factor/Mounting Options    | Box   |
| Shipping Dimensions (hwd / cm)  | 5.08 x 16.00 x 21.34                          |
| Shipping Dimensions (hwd / in.) | 2.00 x 6.30 x 8.40                            |
| Shipping Weight (kg)            | 0.91  |
| Shipping Weight (lbs.)          | 2.00  |
| <b>COMMUNICATIONS</b>           |   |
| Max 1024 x 768 Range (ft)       | 1000  |
| Max 480P Range (ft)             | 1000  |
| Max 1440 x 900 Range (ft)       | 500   |
| Max 1080i Range (ft)            | 500   |
| Max 1920 x 1440 Range (ft)      | 500   |
| Max 480i Range (ft)             | 1000  |
| Max 640 x 480 Range (ft)        | 1000  |
| Max 800 x 600 Range (ft)        | 1000  |



|  |                         |
|--|-------------------------|
| Max 1600 x 1200 Range (ft)                   | 500                     |
| EDID Compatible                              | No                      |
| IR Remote Extension Support                  | No                      |
| RS-232 Serial Extension Support              | No                      |
| Consumer Electronics Control (CEC) Supported | No                      |
| USB Extension Support                        | No                      |
| <b>CONNECTIONS</b>                           |                         |
| Number of Ports                              | 1                       |
| Side A - Connector 1                         | (2) HD15 (FEMALE)       |
| Side A - Connector 2                         | RJ45 (FEMALE)           |
| Side B - Connector 1                         | HD15 (FEMALE)           |
| Side B - Connector 2                         | (2) RJ45 (FEMALE)       |
| Side B - Connector 3                         | 3.5MM (FEMALE)          |
| <b>FEATURES &amp; SPECIFICATIONS</b>         |                         |
| Driver Required                              | No                      |
| 10/100 Ethernet Extension Support            | No                      |
| Built-In Equalizer                           | No                      |
| <b>WARRANTY</b>                              |                         |
| Product Warranty Period (Worldwide)          | 1-year limited warranty |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>