

Han B Base SM HC plastic cover Pg29



-	
Part number	09 30 016 0296
Specification	Han B Base SM HC plastic cover Pg29
HARTING eCatalogue	https://b2b.harting.com/09300160296

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Hoods/Housings
Series of hoods/housings	Han [®] B
Type of hood/housing	Surface mounted housing
Description of hood/housing	With thermo-plastic cover
Туре	High construction

Version

Size	16 B
Version	Side entry
Cable entry	2x Pg 29
Locking type	Single locking lever
Han-Easy Lock [®]	Yes
Field of application	Standard hoods/housings for industrial connectors

Technical characteristics

Limiting temperature	-40 +125 °C
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4 4X 12

Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated

Page 1 / 2 | Creation date 2022-02-07 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



Material properties

Colour (hood/housing)RAL 7037 (dust grey)Material (seal)NBRMaterial (locking)Polycarbonate (PC) stainless steelColour (locking)RAL 7037 (dust grey)Material flammability class acc. to UL 94 (locking levers)v-0RoHScompliantELV statuscompliantChina RoHSeRACH ANNEX XIVI substancesNot containedREACH ANNEX XIVI substancesYesREACH SVHC substancesYesCalifornia Proposition 65 substancesYickel NaphthaleneReach and approvalsNickel NaphthaleneSpecifications and approvalsNickel Naphthalene		
Material (locking)Polycarbonate (PC) Stainless steelColour (locking)RAL 7037 (dust grey)Material flammability class acc. to UL 94 (locking levers)V-0RoHScompliantELV statuscompliantChina RoHSeREACH Annex XVII substancesNot containedREACH ANNEX XIV substancesNot containedREACH SVHC substancesYesREACH SVHC substancesYesREACH SVHC substancesYesCalifornia Proposition 65 substancesNickel Naphthalene	Colour (hood/housing)	RAL 7037 (dust grey)
Material (locking)Stainless steelColour (locking)RAL 7037 (dust grey)Material flammability class acc. to UL 94 (locking levers)V-0RoHScompliantELV statuscompliantChina RoHSeREACH Annex XVII substancesNot containedREACH ANNEX XIV substancesNot containedREACH SVHC substancesYesREACH SVHC substancesYesREACH SVHC substancesYesCalifornia Proposition 65 substancesNickel Naphthalene	Material (seal)	NBR
Material flammability class acc. to UL 94 (locking levers)V-0RoHScompliantELV statuscompliantChina RoHSeREACH Annex XVII substancesNot containedREACH ANNEX XIV substancesNot containedREACH SVHC substancesYesREACH SVHC substancesYesCalifornia Proposition 65 substancesYesCalifornia Proposition 65 substancesNickel Naphthalene	Material (locking)	• • • •
(locking levers)u-uRoHScompliantELV statuscompliantChina RoHSeREACH Annex XVII substancesNot containedREACH ANNEX XIV substancesNot containedREACH SVHC substancesYesREACH SVHC substancesPotassium 1,1,2,2,3,3,4,4,-nonafluorobutane-1-sulphonateCalifornia Proposition 65 substancesNickel Naphthalene	Colour (locking)	RAL 7037 (dust grey)
ELV statuscompliantChina RoHSeREACH Annex XVII substancesNot containedREACH ANNEX XIV substancesNot containedREACH SVHC substancesYesREACH SVHC substancesPotassium 1,1,2,2,3,3,4,4-nonafluorobutane-1-sulphonateCalifornia Proposition 65 substancesYesCalifornia Proposition 65 substancesNickel Naphthalene		V-0
China RoHSeREACH Annex XVII substancesNot containedREACH ANNEX XIV substancesNot containedREACH SVHC substancesYesREACH SVHC substancesPotassium 1,1,2,2,3,3,4,4,+nonafluorobutane-1-sulphonateCalifornia Proposition 65 substancesYesCalifornia Proposition 65 substancesNickel Naphthalene	RoHS	compliant
REACH Annex XVII substancesNot containedREACH ANNEX XIV substancesNot containedREACH SVHC substancesYesREACH SVHC substancesPotassium 1,1,2,2,3,3,4,4-nonafluorobutane-1-sulphonateCalifornia Proposition 65 substancesYesCalifornia Proposition 65 substancesNickel Naphthalene	ELV status	compliant
REACH ANNEX XIV substancesNot containedREACH SVHC substancesYesREACH SVHC substancesPotassium 1,1,2,2,3,3,4,4-nonafluorobutane-1-sulphonateCalifornia Proposition 65 substancesYesCalifornia Proposition 65 substancesNickel Naphthalene	China RoHS	e
REACH SVHC substances Yes REACH SVHC substances Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate California Proposition 65 substances Yes California Proposition 65 substances Nickel Naphthalene	REACH Annex XVII substances	Not contained
REACH SVHC substances Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate California Proposition 65 substances Yes California Proposition 65 substances Nickel Naphthalene	REACH ANNEX XIV substances	Not contained
California Proposition 65 substances Yes California Proposition 65 substances Nickel Naphthalene Naphthalene	REACH SVHC substances	Yes
California Proposition 65 substances Nickel Naphthalene	REACH SVHC substances	Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate
California Proposition 65 substances Naphthalene	California Proposition 65 substances	Yes
Specifications and approvals	California Proposition 65 substances	
	Specifications and approvals	

Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
CE	Yes
Commercial data	
Packaging size	1
Net weight	391.2 g
Country of origin	Germany
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors

Page 2 / 2 | Creation date 2022-02-07 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com