

Han 24B-HTE-NPTF 1"

		Part number	09 30 524 0421	
		Specification	Han 24B-HTE-NPTF 1"	
Identification				
Category	Hoods/Hous	ings		
Series of hoods/housings	Han [®] B			
Type of hood/housing	Hood	Hood		
Туре	High constru	High construction		
Version				
Size		24 B		
Version		Top entry		
Locking type		Double locking lever		
Field of application	Standard ho	ods/housings for industri	al connectors	
Technical characteristics				
Limiting temperature	-40 +125 °	-40 +125 °C		
	IP65			
Degree of protection acc. to IEC 60529	IP66 IP67			
Material properties				
Material (hood/housing)	Aluminium d	Aluminium die-cast		
Surface (hood/housing)	Powder-coat	Powder-coated		
Colour (hood/housing)	RAL 7037 (d	RAL 7037 (dust grey)		
RoHS	compliant			
ELV status	compliant			
China RoHS	е	e		
REACH Annex XVII substances	Not containe	d		

Page 1 / 2 | Creation date 2022-02-07 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



Material properties			
REACH ANNEX XIV substances	Not contained		
REACH SVHC substances	Not contained		
California Proposition 65 substances	Yes		
Specifications and approvals			
Approvals	DNV GL		
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076		
CE	Yes		
Commercial data			
Packaging size	1		
Net weight	238 g		
Country of origin	China		
European customs tariff number	85389099		
eCl@ss	27440202 Shell for industrial connectors		