

# Han PushPull SCRJ POF Plastic



Part number	09 35 241 0421
Specification	Han PushPull SCRJ POF Plastic
HARTING eCatalogue	https://b2b.harting.com/09352410421

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Connectors
Series	Han <sup>®</sup> PushPull (V14)
Identification	SCRJ
Element	Connector sets
Specification	PROFINET-Identification: PROFINET O-Plug SCRJ 1 mm POF
Features	Intuitive locking mechanism
Version	
Shielding	Unshielded
Number of contacts	2
Locking type	PushPull
Details	When installing a PROFINET system, observe the PROFINET installation guideline.
Pack contents	inkl. housing, SCRJ insert und POF contacts
Technical characteristics	
Wire outer diameter	≤2.2 mm
Ferrule diameter	2.5 mm
Limiting temperature	-40 +70 °C
Mating cycles	≥750

Page 1 / 3 | Creation date 2022-01-19 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

IP65

HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany

Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com

Degree of protection acc. to IEC 60529



#### Technical characteristics

Cable diameter	6.5 9.5 mm
Material properties	
Material (hood/housing)	Thermoplastic
Colour (hood/housing)	Black
Material (O-ring)	NBR
Material (cable seal)	TPE
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel Lead Antimony trioxide

## Specifications and approvals

Specifications	IEC 61076-3-117 Variant 14 (V14) IEC 61754-24 Mating face
Approvals	DNV GL
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
PROFINET	Yes

### Commercial data

Packaging size	1
Net weight	27.4 g
Country of origin	Germany
European customs tariff number	85389099

Page 2 / 3 | Creation date 2022-01-19 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com Product data sheet 09 35 241 0421 Han PushPull SCRJ POF Plastic



Commercial data

eCl@ss

27440101 Rectangular connectors (set)

Page 3 / 3 | Creation date 2022-01-19 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com