99 mn

WEATHERPROOF

- Meets IEC 60529 IPX4
 requirements
- Survives rough weather on the job

FLOATS

 Floats for easy recovery from water

BRIGHT

- Provides 25 lumens
- Large reflector for broader beam

DURABLE

- Shatterproof lens
- Rugged polyethylene body
- Survives 1 meter drop

5109L

A great choice for wet areas and outdoor work, the 5109L is weatherproof and floats for easy recovery from water. It stays where you put it and provides a broad beam, making it a terrific area light. In addition, the light operates for 65 continuous hours using a 6V Carbon Zinc battery.

A shatterproof lens and a rugged polyethylene case help it stand up to rough job site conditions. Assembled in the USA using US and imported parts.

Product Detail:

117 mm

 Designation:
 Eveready LED Floating Lantern

 Model:
 5109L

 Color:
 Yellow

 Power Source:
 One 6V Spring Terminal Lantern Battery

 ANSI/NEDA:
 Series 908D or 908A

 Lamp:
 Three White Nichia[®] LEDs

 Lamp Life (hr):
 Lifetime

 Lamp Output (lumens):
 25

 Beam Distance (m):
 82

 Peak Beam Intensity (cd):
 1,680


 Run Time (h:mm):
 65

 Typical Weight:
 230 grams (without battery)

 Dimensions (mm):
 112 x 185 x 99

Performance:

Run Time Continuous Drain to End of Useable Light (21 C)



Battery Type


Tested according to ANSI/NEMA FL 1 Standards.

Important Notice

This datasheet contains information specific to products manufactured at the time of its publication Contents herein do not constitu00te a warranty ©Energizer / All Rights Reserved



Please read all instructions and cautionary markings on the package and light







FL1 STANDARD

m

NDA

STANDARD



LED Floating Lantern