

Han 24B Ex-HSE-M32 4 pegs



Image is for illustration purposes only. Please refer to product description.

Part number	19 36 024 1522
Specification	Han 24B Ex-HSE-M32 4 pegs
HARTING eCatalogue	https://b2b.harting.com/19360241522

Identification

Category	Hoods/Housings
Series of hoods/housings	Han [®] Ex
Type of hood/housing	Hood

Version

Size	24 B
Version	Side entry
Cable entry	1x M32
Locking type	Double locking lever
Field of application	Connectors for explosion hazardous environments
Details	ATTENTION! Only to be used with Han [®] Ex inserts!

Technical characteristics

Limiting temperature	-20 ... +40 °C
Degree of protection acc. to IEC 60529	IP65 With cable gland

Material properties

Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 5015 (sky blue)
RoHS	compliant
ELV status	compliant
China RoHS	e



Pushing Performance

Material properties

REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel
	Lead

Commercial data

Packaging size	1
Net weight	535 g
Country of origin	China
European customs tariff number	85389099
eCl@ss	27440202 Shell for industrial connectors