

## Han 3M Hood Top Entry M20 glued seal



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 19 37 003 1443                                                                        |
| Specification      | Han 3M Hood Top Entry M20 glued seal                                                  |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19370031443">https://b2b.harting.com/19370031443</a> |

### Identification

|                             |                                              |
|-----------------------------|----------------------------------------------|
| Category                    | Hoods/Housings                               |
| Series of hoods/housings    | Han <sup>®</sup> M                           |
| Type of hood/housing        | Hood                                         |
| Description of hood/housing | for Han-Brid <sup>®</sup><br>With glued seal |

### Version

|                      |                                       |
|----------------------|---------------------------------------|
| Size                 | 3 A                                   |
| Version              | Top entry                             |
| Cable entry          | 1x M20                                |
| Locking type         | Single locking lever                  |
| Field of application | Hoods/housings for rough environments |
| Pack contents        | With seal screw                       |

### Technical characteristics

|                                        |                 |
|----------------------------------------|-----------------|
| Limiting temperature                   | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP65<br>IP67    |

### Material properties

|                         |                      |
|-------------------------|----------------------|
| Material (hood/housing) | Zinc die-cast        |
| Surface (hood/housing)  | Powder-coated        |
| Colour (hood/housing)   | RAL 9005 (jet black) |



Pushing Performance

## Material properties

|                                      |               |
|--------------------------------------|---------------|
| Material (seal)                      | FPM           |
| RoHS                                 | compliant     |
| ELV status                           | compliant     |
| China RoHS                           | e             |
| REACH Annex XVII substances          | Not contained |
| REACH ANNEX XIV substances           | Not contained |
| REACH SVHC substances                | Not contained |
| California Proposition 65 substances | Yes           |
| California Proposition 65 substances | Nickel        |
|                                      | Lead          |

## Specifications and approvals

|           |        |
|-----------|--------|
| Approvals | DNV GL |
| CE        | Yes    |

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 10                                       |
| Net weight                     | 0.01 g                                   |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |