

## Han-Eco Mod.24 Outd.-HCC-M40



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 19 41 224 0723                                                                        |
| Specification      | Han-Eco Mod.24 Outd.-HCC-M40                                                          |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19412240723">https://b2b.harting.com/19412240723</a> |

### Identification

|                          |                        |
|--------------------------|------------------------|
| Category                 | Hoods/Housings         |
| Series of hoods/housings | Han-Eco® Modular       |
| Type of hood/housing     | Cable to cable housing |

### Version

|              |                      |
|--------------|----------------------|
| Size         | 24 B                 |
| Module slots | 7                    |
| Version      | Top entry            |
| Cable entry  | 1x M40               |
| Locking type | Double locking lever |

### Technical characteristics

|                                        |                 |
|----------------------------------------|-----------------|
| Limiting temperature                   | -40 ... +125 °C |
| Number of relockings                   | ≥500            |
| Degree of protection acc. to IEC 60529 | IP65            |

### Material properties

|                         |                                          |
|-------------------------|------------------------------------------|
| Material (hood/housing) | Polyamide (PA)<br>Fibre-glass reinforced |
| Colour (hood/housing)   | RAL 9005 (jet black)                     |
| Material (seal)         | FPM                                      |
| Colour (seal)           | RAL 7001 (silver-grey)                   |
| Material (locking)      | Polyamide (PA)<br>Fibre-glass reinforced |



Pushing Performance

## Material properties

|                                                            |                      |
|------------------------------------------------------------|----------------------|
| Colour (locking)                                           | RAL 9005 (jet black) |
| Material flammability class acc. to UL 94                  | V-0                  |
| Material flammability class acc. to UL 94 (locking levers) | V-0                  |
| RoHS                                                       | compliant            |
| ELV status                                                 | compliant            |
| China RoHS                                                 | e                    |
| REACH Annex XVII substances                                | No                   |
| REACH ANNEX XIV substances                                 | No                   |
| REACH SVHC substances                                      | No                   |

## Specifications and approvals

|                |                                   |
|----------------|-----------------------------------|
| Specifications | IEC 61984                         |
|                | EN 45545-2 R22: HL1, HL2, HL3     |
|                | EN 45545-2 R23: HL1, HL2, HL3     |
|                | EN 45545-2 R24: HL1, HL2, HL3     |
| UL / CSA       | UL 1977 ECBT2.E235076             |
|                | CSA-C22.2 No. 182.3 ECBT8.E235076 |
| CE             | Yes                               |

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 1                                        |
| Net weight                     | 232 g                                    |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |