




Pushing Performance

## Han-Eco 10A-HTE-M25



|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 19 46 010 0446                                                                        |
| Specification      | Han-Eco 10A-HTE-M25                                                                   |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19460100446">https://b2b.harting.com/19460100446</a> |

### Identification

|                          |                |
|--------------------------|----------------|
| Category                 | Hoods/Housings |
| Series of hoods/housings | Han-Eco® A     |
| Type of hood/housing     | Hood           |

### Version

|              |                      |
|--------------|----------------------|
| Size         | 10 A                 |
| Version      | Top entry            |
| Cable entry  | 1x M25               |
| Locking type | Single locking lever |

### Technical characteristics

|                                        |                 |
|----------------------------------------|-----------------|
| Limiting temperature                   | -40 ... +125 °C |
| Number of relockings                   | ≥500            |
| Degree of protection acc. to IEC 60529 | IP65            |

### Material properties

|                                           |                                                        |
|-------------------------------------------|--------------------------------------------------------|
| Material (hood/housing)                   | Polyamide (PA)<br>Fibre-glass reinforced               |
| Colour (hood/housing)                     | RAL 9005 (jet black)                                   |
| Material (seal)                           | NBR                                                    |
| Colour (seal)                             | RAL 9005 (jet black)                                   |
| Material flammability class acc. to UL 94 | V-0                                                    |
| RoHS                                      | compliant with exemption                               |
| RoHS exemptions                           | 6(c): Copper alloy containing up to 4 % lead by weight |



Pushing Performance

## Material properties

| ELV status                           | compliant with exemption |
|--------------------------------------|--------------------------|
| China RoHS                           | 50                       |
| REACH Annex XVII substances          | No                       |
| REACH ANNEX XIV substances           | No                       |
| REACH SVHC substances                | Yes                      |
| REACH SVHC substances                | Lead                     |
| California Proposition 65 substances | Yes                      |
| California Proposition 65 substances | Nickel<br>Lead           |

## Specifications and approvals

|                |                               |
|----------------|-------------------------------|
| Specifications | IEC 61984                     |
|                | EN 45545-2 R22: HL1, HL2, HL3 |
|                | EN 45545-2 R23: HL1, HL2, HL3 |
|                | EN 45545-2 R24: HL1, HL2, HL3 |
| CE             | Yes                           |

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 1                                        |
| Net weight                     | 59.8 g                                   |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |