

Specification Sheet

Part Number: MP2M3.NN3P



Mounting plates allow multiple bundles to run parallel. The mounts are secured using two screws, while the bundles are attached using cable ties in any of the available slots.

Cable Tie Mounting Plate, .50" x 3.00", T18-T50 Cable Ties, #6 (M3) Screw, PA66, Natural, 100/pkg

Article Number 151-24219

Type MP2M3

Color Natural (NA)

Quantity Per bag

Product Description HellermannTyton mounting plates allow multiple cable to be run in parallel. The mount is secured with two screws and the cables are attached to the plate by using a cable tie through any of the available slots.

Short Description Cable Tie Mounting Plate, .50" x 3.00", T18-T50 Cable Ties, #6 (M3) Screw, PA66, Natural, 100/pkg

Global Part Name MP2M3-PA66-NA

| | |
|--|--------------------------|
| Length L (Imperial) | 3.0 |
| Length L (Metric) | 76.2 |
| Fixation Method | Screw Mounting and Rivet |
| Width W (Imperial) | 0.5 |
| Width W (Metric) | 12.7 |
| Cable Ties | T18 - T50 |
| Height H (Imperial) | 0.125 |
| Height H (Metric) | 3.2 |
| Cable Tie Width Max (Imperial) | 0.2 |
| Cable Tie Width Max (Metric) | 5.2 |
| Mounting Hole Diameter D (Imperial) | 0.14 |
| Mounting Hole Diameter D (Metric) | 3.7 mm |
| Mounting Hole Diameter D Max (Metric) | 3.7 |
| Mounting Hole Centers (Imperial) | 1.25 |

| | |
|-------------------------------------|----------------------------------|
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL 94 V-2 |
| Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 100 |
| Package Quantity (Metric) | 100 |
| Customs Number | 3926909988 |