


# BUK7C10-75AITE

## N-channel TrenchPLUS standard level FET

**Rev. 03 — 17 February 2009** **Product data sheet**

## 1. Product profile

### 1.1 General description

Standard level N-channel enhancement mode Field-Effect Transistor (FET) in a plastic package using TrenchMOS technology. The devices include TrenchPLUS current sensing and diodes for ElectroStatic Discharge (ESD) protection and temperature sensing. This product has been designed and qualified to the appropriate AEC standard for use in automotive critical applications.

### 1.2 Features and benefits

- Allows responsive temperature monitoring due to integrated temperature sensor
- Electrostatically robust due to integrated protection diodes
- Low conduction losses due to low on-state resistance
- Q101 compliant
- Reduced component count due to integrated current sensor

### 1.3 Applications

- Automotive and general purpose power switching
- Fan control
- Electrical Power Assisted Steering (EPAS)
- Variable Valve Timing for engines

### 1.4 Quick reference data

**Table 1. Quick reference**



| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|---|---|---|---|---|---|---|
| $V_{DS}$ | drain-source voltage | $T_j \geq 25$ °C; $T_j \leq 175$ °C | - | - | 75 | V |
| $I_D$ | drain current | $V_{GS}$ = 10 V; $T_{mb}$ = 25 °C; see Figure 2; see Figure 3 [1] | - | - | 114 | A |
| **Static characteristics** | | | | | | |
| $R_{DSon}$ | drain-source on-state resistance | $V_{GS}$ = 10 V; $I_D$ = 50 A; $T_j$ = 25 °C; see Figure 7; see Figure 8 | - | 8.8 | 10 | mΩ |
| $I_D/I_{sense}$ | ratio of drain current to sense current | $T_j$ > -55 °C; $T_j$ < 175 °C; $V_{GS}$ > 10 V | 450 | 500 | 550 | |
| $S_{F(TSD)}$ | temperature sense diode temperature coefficient | $I_F$ = 250 µA; $T_j$ > -55 °C; $T_j$ < 175 °C | -1.4 | -1.54 | -1.68 | mV/K |
| $V_{F(TSD)}$ | temperature sense diode forward voltage | $I_F$ = 250 µA; $T_j$ = 25 °C | 648 | 658 | 668 | mV |

[1] Current is limited by power dissipation chip rating.

nexperia

## 2. Pinning information

**Table 2. Pinning information**

| Pin | Symbol | Description | Simplified outline | Graphic symbol |
|---|---|---|---|---|
| 1 | G | gate |  |  |
| 2 | ISENSE | sense current | | |
| 3 | A | anode | | |
| 4 | D | drain | | |
| 5 | K | cathode | | |
| 6 | KS | Kelvin source | | |
| 7 | S | source | | |
| mb | D | mounting base; connected to drain | | |



**SOT427 (D2PAK)**



## 3. Ordering information

**Table 3. Ordering information**

| Type number | Package | | |
|---|---|---|---|
| | Name | Description | Version |
| BUK7C10-75AITE | D2PAK | plastic single-ended surface-mounted package (D2PAK); 7 leads (one lead cropped) | SOT427 |



© Nexperia B.V. 2017. All rights reserved

# 4. Limiting values

**Table 4. Limiting values**

*In accordance with the Absolute Maximum Rating System (IEC 60134).*


| Symbol | Parameter | Conditions | | Min | Max | Unit |
|---|---|---|---|---|---|---|
| $V_{DS}$ | drain-source voltage | $T_j \geq 25$ °C; $T_j \leq 175$ °C | | - | 75 | V |
| $V_{DGS}$ | drain-gate voltage | | | - | 75 | V |
| $V_{GS}$ | gate-source voltage | | | -20 | 20 | V |
| $I_D$ | drain current | $T_{mb}$ = 25 °C; $V_{GS}$ = 10 V; see Figure 2; see Figure 3 | [1] | - | 114 | A |
| | | | [2] | - | 75 | A |
| | | $T_{mb}$ = 100 °C; $V_{GS}$ = 10 V; see Figure 2 | [2] | - | 75 | A |
| $I_{DM}$ | peak drain current | $T_{mb}$ = 25 °C; $t_p \leq 10$ µs; pulsed; see Figure 3 | | - | 456 | A |
| $P_{tot}$ | total power dissipation | $T_{mb}$ = 25 °C; see Figure 1 | | - | 272 | W |
| $I_{GS(CL)}$ | gate-source clamping current | continuous | | - | 10 | mA |
| | | pulsed; $t_p$ = 5 ms; δ = 0.01 | | - | 50 | mA |
| $V_{isol(FET-TSD)}$ | FET to temperature sense diode isolation voltage | | | -100 | 100 | V |
| $T_{stg}$ | storage temperature | | | -55 | 175 | °C |
| $T_j$ | junction temperature | | | -55 | 175 | °C |
| **Source-drain diode** | | | | | | |
| $I_S$ | source current | $T_{mb}$ = 25 °C | [1] | - | 114 | A |
| | | | [2] | - | 75 | A |
| $I_{SM}$ | peak source current | $t_p \leq 10$ µs; pulsed; $T_{mb}$ = 25 °C | | - | 456 | A |
| **Avalanche ruggedness** | | | | | | |
| $E_{DS(AL)S}$ | non-repetitive drain-source avalanche energy | $I_D$ = 75 A; $V_{sup} \leq 75$ V; $R_{GS}$ = 50 Ω; $V_{GS}$ = 10 V; $T_{j(init)}$ = 25 °C; unclamped | | - | 739 | mJ |
| **Electrostatic discharge** | | | | | | |
| $V_{esd}$ | electrostatic discharge voltage | HBM; C = 100 pF; R = 1.5 kΩ | | - | 6 | kV |

[1] Current is limited by power dissipation chip rating.

[2] Continuous current is limited by package.




© Nexperia B.V. 2017. All rights reserved





$$P_{der} = \frac{P_{tot}}{P_{tot(25°C)}} \times 100\,\%$$

**Fig 1. Normalized total power dissipation as a function of mounting base temperature**




$$V_{GS} \geq 10V$$

**Fig 2. Normalized continuous drain current as a function of mounting base temperature**




$$T_{mb} = 25°C; I_{DM} \text{ is single pulse}$$

**Fig 3. Safe operating area; continuous and peak drain currents as a function of drain-source voltage**



© Nexperia B.V. 2017. All rights reserved

## 5. Thermal characteristics

**Table 5. Thermal characteristics**

| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|---|---|---|---|---|---|---|
| $R_{th(j-a)}$ | thermal resistance from junction to ambient | mounted on printed-circuit board; minimum footprint | - | - | 50 | K/W |
| $R_{th(j-mb)}$ | thermal resistance from junction to mounting base | see Figure 4 | - | - | 0.55 | K/W |





**Fig 4. Transient thermal impedance from junction to mounting base as a function of pulse duration**


© Nexperia B.V. 2017. All rights reserved

# 6. Characteristics

**Table 6. Characteristics**


| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|---|---|---|---|---|---|---|
| **Static characteristics** | | | | | | |
| $V_{(BR)DSS}$ | drain-source breakdown voltage | $I_D$ = 0.25 mA; $V_{GS}$ = 0 V; $T_j$ = 25 °C | 75 | - | - | V |
| | | $I_D$ = 0.25 mA; $V_{GS}$ = 0 V; $T_j$ = -55 °C | 70 | - | - | V |
| $V_{GS(th)}$ | gate-source threshold voltage | $I_D$ = 1 mA; $V_{DS}$ = $V_{GS}$; $T_j$ = 25 °C; see Figure 9 | 2 | 3 | 4 | V |
| | | $I_D$ = 1 mA; $V_{DS}$ = $V_{GS}$; $T_j$ = 175 °C; see Figure 9 | 1 | - | - | V |
| | | $I_D$ = 1 mA; $V_{DS}$ = $V_{GS}$; $T_j$ = -55 °C; see Figure 9 | - | - | 4.4 | V |
| $I_{DSS}$ | drain leakage current | $V_{DS}$ = 75 V; $V_{GS}$ = 0 V; $T_j$ = 25 °C | - | 0.1 | 10 | µA |
| | | $V_{DS}$ = 75 V; $V_{GS}$ = 0 V; $T_j$ = 175 °C | - | - | 250 | µA |
| $V_{(BR)GSS}$ | gate-source breakdown voltage | $I_G$ = 1 mA; $V_{DS}$ = 0 V; $T_j$ > -55 °C; $T_j$ < 175 °C | 20 | 22 | - | V |
| | | $I_G$ = -1 mA; $V_{DS}$ = 0 V; $T_j$ > -55 °C; $T_j$ < 175 °C | 20 | 22 | - | V |
| $I_{GSS}$ | gate leakage current | $V_{DS}$ = 0 V; $V_{GS}$ = 10 V; $T_j$ = 25 °C | - | 22 | 1000 | nA |
| | | $V_{DS}$ = 0 V; $V_{GS}$ = -10 V; $T_j$ = 25 °C | - | 22 | 1000 | nA |
| | | $V_{DS}$ = 0 V; $V_{GS}$ = 10 V; $T_j$ = 175 °C | - | - | 10 | µA |
| | | $V_{DS}$ = 0 V; $V_{GS}$ = -10 V; $T_j$ = 175 °C | - | - | 10 | µA |
| $R_{DSon}$ | drain-source on-state resistance | $V_{GS}$ = 10 V; $I_D$ = 50 A; $T_j$ = 25 °C; see Figure 7; see Figure 8 | - | 8.8 | 10 | mΩ |
| | | $V_{GS}$ = 10 V; $I_D$ = 50 A; $T_j$ = 175 °C; see Figure 7; see Figure 8 | - | - | 21 | mΩ |
| $V_{F(TSD)}$ | temperature sense diode forward voltage | $I_F$ = 250 µA; $T_j$ = 25 °C | 648 | 658 | 668 | mV |
| $S_{F(TSD)}$ | temperature sense diode temperature coefficient | $I_F$ = 250 µA; $T_j$ > -55 °C; $T_j$ < 175 °C | -1.4 | -1.54 | -1.68 | mV/K |
| $V_{F(TSD)hys}$ | temperature sense diode forward voltage hysteresis | $I_F$ > 125 µA; $I_F$ < 250 µA; $T_j$ = 25 °C | 25 | 32 | 50 | mV |
| $I_D/I_{sense}$ | ratio of drain current to sense current | $V_{GS}$ > 10 V; $T_j$ > -55 °C; $T_j$ < 175 °C | 450 | 500 | 550 | |
| **Dynamic characteristics** | | | | | | |
| $Q_{G(tot)}$ | total gate charge | $I_D$ = 25 A; $V_{DS}$ = 60 V; $V_{GS}$ = 10 V; $T_j$ = 25 °C; see Figure 14 | - | 121 | - | nC |
| $Q_{GS}$ | gate-source charge | | - | 20 | - | nC |
| $Q_{GD}$ | gate-drain charge | | - | 44 | - | nC |
| $C_{iss}$ | input capacitance | $V_{GS}$ = 0 V; $V_{DS}$ = 25 V; f = 1 MHz; $T_j$ = 25 °C; see Figure 12 | - | 4700 | - | pF |
| $C_{oss}$ | output capacitance | | - | 800 | - | pF |
| $C_{rss}$ | reverse transfer capacitance | | - | 455 | - | pF |


© Nexperia B.V. 2017. All rights reserved

**Table 6. Characteristics** *…continued*


| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|---|---|---|---|---|---|---|
| $t_{d(on)}$ | turn-on delay time | $V_{DS}$ = 30 V; $R_L$ = 1.2 Ω; $V_{GS}$ = 10 V; $R_{G(ext)}$ = 10 Ω; $T_j$ = 25 °C | - | 35 | - | ns |
| $t_r$ | rise time | | - | 108 | - | ns |
| $t_{d(off)}$ | turn-off delay time | | - | 185 | - | ns |
| $t_f$ | fall time | | - | 100 | - | ns |
| $L_D$ | internal drain inductance | from upper edge of drain mounting base to center of die; $T_j$ = 25 °C | - | 2.5 | - | nH |
| $L_S$ | internal source inductance | from source lead to source bond pad; $T_j$ = 25 °C | - | 7.5 | - | nH |
| **Source-drain diode** | | | | | | |
| $V_{SD}$ | source-drain voltage | $I_S$ = 25 A; $V_{GS}$ = 0 V; $T_j$ = 25 °C; see Figure 18 | - | 0.85 | 1.2 | V |
| $t_{rr}$ | reverse recovery time | $I_S$ = 20 A; $dI_S/dt$ = -100 A/µs; $V_{GS}$ = -10 V; $V_{DS}$ = 30 V; $T_j$ = 25 °C | - | 75 | - | ns |
| $Q_r$ | recovered charge | | - | 270 | - | nC |


© Nexperia B.V. 2017. All rights reserved





$T_j = 25°C; t_p = 300\mu s$

**Fig 5. Output characteristics: drain current as a function of drain-source voltage; typical values**





$T_j = 25°C; I_D = 50A$

**Fig 6. Drain-source on-state resistance as a function of gate-source voltage; typical values**




$T_j = 25°C; t_p = 300\mu s$


**Fig 7. Drain-source on-state resistance as a function of drain current; typical values**




$$a = \frac{R_{DSon}}{R_{DSon(25°C)}}$$


**Fig 8. Normalized drain-source on-state resistance factor as a function of junction temperature**


© Nexperia B.V. 2017. All rights reserved





$I_D = 1mA; V_{DS} = V_{GS}$

**Fig 9. Gate-source threshold voltage as a function of junction temperature**





$T_j = 25\,°C; V_{DS} = 5V$

**Fig 10. Sub-threshold drain current as a function of gate-source voltage**




$T_j = 25°C; V_{DS} = 25V$


**Fig 11. Forward transconductance as a function of drain current; typical values**




$V_{GS} = 0V; f = 1MHz$


**Fig 12. Input, output and reverse transfer capacitances as a function of drain-source voltage; typical values**


© Nexperia B.V. 2017. All rights reserved





$V_{DS} = 25V$

**Fig 13. Transfer characteristics: drain current as a function of gate-source voltage; typical values**





$T_j = 25°C; I_D = 25A$

**Fig 14. Gate-source voltage as a function of turn-on gate charge; typical values**




$I_F = 250\mu A$


**Fig 15. Forward voltage of temperature sense diode as a function of junction temperature; typical values**




$V_F$ at $T_j = 25°C; I_F = 250\mu A$


**Fig 16. Temperature coefficient of temperature sense diode as a function of forward voltage; typical values**


© Nexperia B.V. 2017. All rights reserved




$I_D = 25A$

**Fig 17. Drain-sense current ratio as a function of gate-source voltage; typical values**




$V_{GS} = 0V$


**Fig 18. Reverse diode current as a function of reverse diode voltage; typical values**



© Nexperia B.V. 2017. All rights reserved

## 7. Package outline

**Plastic single-ended surface-mounted package (D2PAK); 7 leads (one lead cropped)** **SOT427**




**DIMENSIONS (mm are the original dimensions)**

| UNIT | A | $A_1$ | b | c | D max. | $D_1$ | E | e | $L_p$ | $H_D$ | Q |
|---|---|---|---|---|---|---|---|---|---|---|---|
| mm | 4.50<br>4.10 | 1.40<br>1.27 | 0.85<br>0.60 | 0.64<br>0.46 | 11 | 1.60<br>1.20 | 10.30<br>9.70 | 1.27 | 2.90<br>2.10 | 15.80<br>14.80 | 2.60<br>2.20 |

| OUTLINE VERSION | REFERENCES | | | | EUROPEAN PROJECTION | ISSUE DATE |
|---|---|---|---|---|---|---|
| | IEC | JEDEC | JEITA | | | |
| SOT427 | | | | | | ~~05-03-09~~<br>06-03-16 |

**Fig 19. Package outline SOT427 (D2PAK)**


© Nexperia B.V. 2017. All rights reserved

# 8. Revision history

**Table 7. Revision history**

| Document ID | Release date | Data sheet status | Change notice | Supersedes |
|---|---|---|---|---|
| BUK7C10-75AITE_3 | 20090217 | Product data sheet | - | BUK7C10_75AITE-02 |
| Modifications: | • The format of this data sheet has been redesigned to comply with the new identity guidelines of NXP Semiconductors.<br>• Legal texts have been adapted to the new company name where appropriate. | | | |
| BUK7C10_75AITE-02 (9397 750 11048) | 20030318 | Product data sheet | - | BUK7C10_75AITE-01 |
| BUK7C10_75AITE-01 (9397 750 09881) | 20020725 | Product data sheet | - | - |


© Nexperia B.V. 2017. All rights reserved

# 9. Legal information

## 9.1 Data sheet status

| Document status [1][2] | Product status[3] | Definition |
|---|---|---|
| Objective [short] data sheet | Development | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet | Qualification | This document contains data from the preliminary specification. |
| Product [short] data sheet | Production | This document contains the product specification. |

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL http://www.nexperia.com.

## 9.2 Definitions

**Draft** — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

**Short data sheet** — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Nexperia sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

## 9.3 Disclaimers

**General** — Information in this document is believed to be accurate and reliable. However, Nexperia does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

**Right to make changes** — Nexperia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

**Suitability for use** — Nexperia products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of a Nexperia product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Nexperia accepts no liability for inclusion and/or use of Nexperia products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

**Applications** — Applications that are described herein for any of these products are for illustrative purposes only. Nexperia makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

**Quick reference data** — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

**Limiting values** — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

**Terms and conditions of sale** — Nexperia products are sold subject to the general terms and conditions of commercial sale, as published at http://www.nexperia.com/profile/terms, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by Nexperia. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

**No offer to sell or license** — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

## 9.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

# 10. Contact information

For more information, please visit: http://www.nexperia.com

For sales office addresses, please send an email to: salesaddresses@nexperia.com



© Nexperia B.V. 2017. All rights reserved

## 11. Contents

**1 Product profile . . . . . 1**
1.1 General description . . . . . 1
1.2 Features and benefits . . . . . 1
1.3 Applications . . . . . 1
1.4 Quick reference data . . . . . 1
**2 Pinning information . . . . . 2**
**3 Ordering information . . . . . 2**
**4 Limiting values . . . . . 3**
**5 Thermal characteristics . . . . . 5**
**6 Characteristics . . . . . 6**
**7 Package outline . . . . . 12**
**8 Revision history . . . . . 13**
**9 Legal information . . . . . 14**
9.1 Data sheet status . . . . . 14
9.2 Definitions . . . . . 14
9.3 Disclaimers . . . . . 14
9.4 Trademarks . . . . . 14
**10 Contact information . . . . . 14**

© Nexperia B.V. 2017. All rights reserved

For more information, please visit: http://www.nexperia.com
For sales office addresses, please send an email to: salesaddresses@nexperia.com
**Date of release: 17 February 2009**