 	нт. 	m	t		0		₽	► ►	
						LAYOUT SHOWN AS E	XAMPLE		
	Keying Shown a	is example							
CHARACTERISTICS	F	Connector dimension Dim Nominal]						
 -Standard : Based on MIL-DTL-38999 Series III -Shell Material : Composite -Shell Plating : Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum 		ØS 29.4 Max Z' 31.5 Max VV THREAD M18x1-6g			due to a u the Specificatio	all not be liable for an use of the Products wh ons issued by either o essional recommendat Countr FR	ich does not comply f the Parties or by a th ion, technical notice. y Jurisdictior	with hird party	_
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories					PN: 8D513M03BN				
-Temperature Range : -65°C to +200°C				A 18	-10-2016 First Release				
-Salt Spray : 2000 hours			-	ISS Designed B	DATE Latest modifica y: Dat		CU	STOMER DRAWING	MOD N°
			TITLE		Composite Plug 8D series		eries		
BASIC SERIES: 8D 5 - 13 M SHELL TYPE : Plug with RFI Shielding	03 B N			SCALE		General linear Tolerances: ±	1	NPRDS / PROJECT 859	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13		ORIE CONTACT TYPE : SOCKET(5	NTATION : N 600 Matings)	SOU	RIAU WW	N.SOURIAU.C		This document is the pro SOURIAU it must not be reprodu communicated without p	ced or
PLATING : M = Nickel		CONTACT LAY	/OUT : 13-03	FORMAT		SOURIAU 8D513M	DRG N°		SHEET
						ΙΛΙζΤζηο			-/-

r	Т	۵		П	m	D	0	
		Contact Layout						
		03						
4								
		3#16						
	Ctc A B	0 -	Y 1.47 2.79					
w	С	-2.39	1.47					
	L							
							due to the Specifica	shall not be liable for a a use of the Products w ations issued by either ofessional recommend
S								Coun
								PN: 8D513
						A 18-10	-2016 First Release	
							TE Latest modi	fication - by
						Designed By:		Date:
						TITLE		Comp
<u> </u>						SCALE NA	$\bigcirc \bigcirc$	General linear Tolerances: ±
						SOURI	AU WV	VW.SOURIAU.
						FORMAT		SOURIAL

G

Н

F

Е

A3

D

С

