

Specification Sheet

Part Number: 596-00242



Made with UV stable inks and materials for durability and weather resistance.

The labels are supplied with aggressive adhesive to ensure long life.

Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Solar Label, Clear Laminate, UV Stable, 4.2" x 2.25", VL, Clear, 50/roll

Article Number 596-00242

Type LAM1

Color Clear (CL)

Quantity Per roll

Product Description HellermannTyton printable Solar Installation labels are designed to meet the requirements of the 2014 and 2017 National Electrical Code (NEC) and the International Fire Code (IFC) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description	Solar Label, Clear Laminate, UV Stable, 4.2" x 2.25", VL, Clear, 50/roll
Global Part Name	LAM1-443/281-CL
Technical Description	Clear Laminate Label, UV stable, 4.2" X 2.25", Clear
Local Order Number 2	Cross Reference = 10 per pack: 596-00670
Width W (Imperial)	4.2
Width W (Metric)	106.6
Thickness T (Metric)	64.0
Height H (Imperial)	2.25
Height H (Metric)	57.10
Material	Type 443/281, UV-stabilized flexible white vinyl with clear polyester laminate (443/281)
Material Shortcut	443/281
Adhesive	Acrylic
Halogen Free	No
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)

Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	UL 969 NEC2011 IFC 2012
Warranty (US)	Yes
UL Recognized (US)	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50
Customs Number	3919102055
Labels per Column	1
Labels per Row	1