

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

HDBaseT Class B (HDBaseT-Lite) HDMI over Cat5e/6/6a Extender Receiver, Serial and IR, 4K x 2K 30 Hz UHD / 1080p 60 Hz, Up to 230 ft. (70 m), TAA

MODEL NUMBER: BHDBT-R-SI











Works with a Tripp Lite HDBaseT matrix transmitter to extend uncompressed HDMI video and audio, RS-232 serial and IR remote control signals over a Cat5e/6/6a cable up to 230 ft. to a projector, monitor or television.

Description

The BHDBT-R-SI HDBaseT Class B (HDBaseT-Lite) HDMI over Cat5e/6/6a Extender Receiver works in tandem with the Tripp Lite BHDBT-Series matrix transmitter in your HDBaseT Class B installation to extend uncompressed HDMI video and audio, RS-232 serial and IR remote control signals.

Using a single Cat5e/6/6a cable, the BHDBT-R-SI can extend an HD 1920 x 1080 (1080p) @ 60Hz signal up to 230-ft. (70.1 m) or an Ultra High Definition (UHD) 4096 x 2160 or $3840 \times 2160 \times 2160$

You can control RS-232 serial devices, such as touchscreen displays or scanners, at baud rates up to 115 Kbps. The 2-way IR Remote Control feature (@ 39 KHz) lets you control your Blu-ray player using its remote when at the remote monitor and vice versa. The monitor connects to the rear locking HDMI port (ideal for use with Tripp Lite's P569-006-LOCK High-Speed HDMI cables with locking connectors) that prevents the cable from coming loose or undone, ensuring an intact signal.

The BHDBT-R-SI supports 7.1-channel surround sound, DTS-HD and Dolby TrueHD audio, as well as 3D video, EDID and HDCP. Included mounting hardware lets you attach the receiver to a wall, rack or pole. Sets up quickly with no software to download or install.

Highlights

- Extends both a 4096 x 2160 and 3840 x 2160 (4K x 2K) @ 30 Hz signal up to 130-ft. (39.62 m)
- Extends a 1080p @ 60 Hz signal up to 230-ft. (70.1 m)
- Supports 7.1-channel surround sound, DTS-HD and Dolby TrueHD
- Mounts easily to wall, rack or pole
- Plug and play—no software or drivers to install

Package Includes

- BHDBT-R-SI HDBaseT Class B HDMI over Cat5e/6/6a Extender Receiver
- IR-IN cable
- IR-OUT cable
- 3.5 mm Male to DB9 Female adapter cable
- 3.5 mm Male to DB9 Male adapter cable
- External Power Supply with NEMA 1-15P Plug (Input: 100–240V, 50/60 Hz, 0.5A; Output: 5V, 3A)
- Mounting hardware
- Owner's Manual



Features

Supports the Latest Video and Audio Applications

- Connects to Tripp Lite BHDBT-Series matrix transmitter with a single Cat5e/6/6a cable
- Extends an Ultra High Definition (UHD) 4096 x 2160 or 3840 x 2160 (4K x 2K) @ 30Hz signal up to 130-ft. (39.62 m) (40 m)
- Extends a High Definition 1920 x 1080 (1080p) @ 60Hz signal up to 230-ft. (70.1 m) (70 m)
- Supports 7.1-channel surround sound, DTS-HD and Dolby TrueHD audio
- Supports 36-bit Deep Color (12 bits per channel), CEC passthrough, 3D video, EDID and HDCP
- Add up to 5 BHDBT-TR-SI Extender Transceivers to further expand the range of your installation up to 780-ft. (237.74 m) (4K x 2K @ 30Hz) or 1,380-ft. (420.62 m) (1080p @ 60Hz) with a monitor attached to each transceiver

Allows You to Control Other Devices

- 2-way 39 KHz IR Remote Control functionality lets you control your Blu-ray player with its remote while standing at the remote monitor (and vice versa)
- RS-232 serial port supports 115 Kbps full-duplex baud rates for devices such as scanners and touchscreen monitors

Easy to Set Up and Use

- Plug-and-play engineering—no software or drivers to download and install
- Included mounting hardware lets you install unit on a wall, rack or pole
- Locking HDMI port (ideal for use with Tripp Lite's P569-006-LOCK HDMI cables) prevents cable from coming loose or disconnected, ensuring an intact signal

TAA-Compliant

• Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW		
UPC Code	037332187017	
Product Type	Receiver	
Technology	HDBaseT; HDMI; IR; Cat5/5e; Cat6	
VIDEO		
Max 720P Range (ft)	230	
Max 1080P Range (ft)	230	
HDR Support	No	
3D Video Supported	No	
Maximum Signal Range (ft)	230	
Maximum Signal Range (m)	70	



Bus Powered	No	
POWER		
Power Over Cable (PoC) Support	No	
AC Adapter	Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 3A	
PHYSICAL		
Color	Black	
Number of Displays	1	
Shipping Dimensions (hwd / cm)	5.59 x 21.34 x 16.51	
Shipping Dimensions (hwd / in.)	2.20 x 8.40 x 6.50	
Shipping Weight (kg)	0.61	
Shipping Weight (lbs.)	1.34	
Unit Dimensions (hwd / in.)	1.1 x 4.5 x 2.5	
Unit Weight Details	0.55lbs	
ENVIRONMENTAL		
Operating Temperature Range	0 to 40 C (32 to 104 F)	
Storage Temperature Range	-20 to 60 C (-4 to 140 F)	
Relative Humidity	20 to 90%	
COMMUNICATIONS		
Max 1024 x 768 Range (ft)	230	
Max 480P Range (ft)	230	
Max 1440 x 900 Range (ft)	230	
Max 1080i Range (ft)	230	
Max 1920 x 1440 Range (ft)	130	
Max 4K UHD Range (ft)	130	
Max 480i Range (ft)	230	
Max 640 x 480 Range (ft)	230	
Max 800 x 600 Range (ft)	230	
Max 1600 x 1200 Range (ft)	230	
Max 2048 x 1536 Range (ft)	130	
EDID Compatible	No	
IR Remote Extension Support	Yes	
RS-232 Serial Extension Support	Yes	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Consumer Electronics Control (CEC) Supported	No	
USB Extension Support	No	
CONNECTIONS		
Number of Ports	1	
Side A - Connector 1	HDMI (FEMALE)	
Side B - Connector 1	RJ45 (FEMALE)	
FEATURES & SPECIFICATIONS		
Driver Required	No	
10/100 Ethernet Extension Support	No	
Built-In Equalizer	No	
STANDARDS & COMPLIANCE		
Certifications	CE, FCC, RoHS, REACH	
Approvals	CE, FCC, RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	1-year limited warranty	

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies