

## Low Noise 150 mA LDO Regulator

No. EA-173-181227

### OUTLINE

The RP130x is a voltage regulator IC with high ripple rejection, low dropout voltage, high output voltage accuracy and extremely low supply current. The IC consists of a voltage reference unit, an error amplifier, a resistor-net for voltage setting, a short current limit circuit and a chip enable circuit.

This IC has an excellent low supply current performed by CMOS process, moreover they perform with low dropout voltage due to built-in low on-resistance. A chip enable function prolongs the battery life.

The input transient response, the load transient response and the ripple rejection have been improved in the RP130x compared with the conventional products. Besides achieving low supply current (Typ. 38  $\mu$ A).

The range of the operation voltage is capable from 1.7 V to 6.5 V and the range of the output voltage is capable from 1.2 V to 5.3 V for this product, which is wider range as our conventional product R1114x.

The output voltage of this IC is fixed with high accuracy. Since the packages for this IC are DFN(PLP)1010-4, SOT-23-5 and SC-82AB, therefore high density mounting of the IC on board is possible.

### FEATURES

- Supply Current ..... Typ. 38  $\mu$ A
- Standby Current..... Typ. 0.1  $\mu$ A
- Ripple Rejection..... Typ. 80 dB (f = 1 kHz)
- Input Voltage Range (Maximum Rating)..... 1.7 V to 6.5 V (7.0 V)
- Output Voltage Range..... 1.2 V to 5.3 V (0.1 V step<sup>(1)</sup>)
- Output Voltage Accuracy.....  $\pm 1.0\%$  ( $V_{OUT} > 2.0$  V,  $T_a = 25^\circ\text{C}$ )
- Temperature-Drift Coefficient of Output Voltage ..... Typ.  $\pm 20$  ppm/ $^\circ\text{C}$
- Dropout Voltage ..... Typ. 0.32 V ( $I_{OUT} = 150$  mA,  $V_{OUT} = 2.8$  V)
- Line Regulation ..... Typ. 0.02%/V
- Packages ..... DFN(PLP)1010-4, SC-82AB, SOT-23-5
- Built-in Fold Back Protection Circuit ..... Typ. 40 mA
- Ceramic capacitors are recommended to be used with this IC ..... 0.47  $\mu$ F or more

### APPLICATIONS

- Power source for battery-powered equipment.
- Power source for portable communication equipment.
- Power source for electrical appliances such as cameras, VCRs and camcorders.
- Power source for high stable reference voltage.

<sup>(1)</sup> For other voltages, please refer to *SELECTION GUIDE*.

---

## RP130x

---

No. EA-173-181227

### SELECTION GUIDE

The set output voltage, chip enable polarity, auto-discharge function<sup>(1)</sup>, and packages for the IC can be selected at the user's request.

#### Selection Guide

| Product Name     | Package        | Quantity per Reel | Pb Free | Halogen Free |
|------------------|----------------|-------------------|---------|--------------|
| RP130Kxx1*-TR    | DFN(PLP)1010-4 | 10,000 pcs        | Yes     | Yes          |
| RP130Qxx1*-TR-FE | SC-82AB        | 3,000 pcs         | Yes     | Yes          |
| RP130Nxx1*-TR-FE | SOT-23-5       | 3,000 pcs         | Yes     | Yes          |

xx : Set Output Voltage ( $V_{SET}$ )

Fixed Type: 12 to 53 Stepwise setting with 0.1 V increment in the range from 1.2 V to 5.3 V

Exception: 1.25 V = RP130x121\*5

1.85 V = RP130x181\*5

2.85 V = RP130x281\*5

3.45 V = RP130x341\*5

4.25 V = RP130x421\*5

\* : CE pin polarity and auto-discharge function at off state are options as follows.

A: active low, without auto-discharge function at off state.

B: active high, without auto-discharge function at off state.


D: active high, with auto-discharge function at off state.

---


<sup>(1)</sup> Auto-discharge function quickly lowers the output voltage to 0 V by releasing the electrical charge in the external capacitor when the chip enable signal is switched from the active mode to the standby mode.

---


## BLOCK DIAGRAMS







**RP130xxx1A Block Diagram**



**RP130xxx1B Block Diagram**



**RP130xxx1D Block Diagram**

**PIN DESCRIPTIONS****Top View****Bottom View****DFN(PLP)1010-4 Pin Configuration****SC-82AB Pin Configuration****SOT-23-5 Pin Configuration****DFN(PLP)1010-4 Pin Description**

| Pin No | Symbol                      | Pin Description                           |
|--------|-----------------------------|-------------------------------------------|
| 1      | VOUT                        | Output Pin                                |
| 2      | GND                         | Ground Pin                                |
| 3      | $\overline{\text{CE}}$ / CE | Chip Enable Pin ("L" Active / "H" Active) |
| 4      | VDD                         | Input Pin                                 |

**SC-82AB Pin Description**

| Pin No | Symbol                      | Pin Description                           |
|--------|-----------------------------|-------------------------------------------|
| 1      | $\overline{\text{CE}}$ / CE | Chip Enable Pin ("L" Active / "H" Active) |
| 2      | GND                         | Ground Pin                                |
| 3      | VOUT                        | Output Pin                                |
| 4      | VDD                         | Input Pin                                 |

**SOT-23-5 Pin Description**

| Pin No | Symbol                      | Pin Description                           |
|--------|-----------------------------|-------------------------------------------|
| 1      | VDD                         | Input Pin                                 |
| 2      | GND                         | Ground Pin                                |
| 3      | $\overline{\text{CE}}$ / CE | Chip Enable Pin ("L" Active / "H" Active) |
| 4      | NC                          | No Connection                             |
| 5      | VOUT                        | Output Pin                                |

<sup>(1)</sup> Tab is GND level (they are connected to the reverse side of this IC). The tab is better to be connected to the GND, but leaving it open is also acceptable.

## ABSOLUTE MAXIMUM RATINGS

### Absolute Maximum Ratings

| Symbol    | Item                             |                |                                   | Rating                 | Unit |
|-----------|----------------------------------|----------------|-----------------------------------|------------------------|------|
| $V_{IN}$  | Input Voltage                    |                |                                   | 7.0                    | V    |
| $V_{CE}$  | Input Voltage (CE Pin)           |                |                                   | −0.3 to 7.0            | V    |
| $V_{OUT}$ | Output Voltage                   |                |                                   | −0.3 to $V_{IN} + 0.3$ | V    |
| $I_{OUT}$ | Output Current                   |                |                                   | 200                    | mA   |
| $P_D$     | Power Dissipation <sup>(1)</sup> | DFN(PLP)1010-4 | JEDEC STD. 51-7 Test Land Pattern | 800                    | mW   |
|           |                                  | SC-82AB        | Standard Test Land Pattern        | 380                    |      |
|           |                                  | SOT-23-5       | JEDEC STD. 51-7 Test Land Pattern | 660                    |      |
| $T_j$     | Junction Temperature Range       |                |                                   | −40 to 125             | °C   |
| $T_{stg}$ | Storage Temperature Range        |                |                                   | −55 to 125             | °C   |

### ABSOLUTE MAXIMUM RATINGS

Electronic and mechanical stress momentarily exceeded absolute maximum ratings may cause the permanent damages and may degrade the lifetime and safety for both device and system using the device in the field. The functional operation at or over these absolute maximum ratings are not assured.

## RECOMMENDED OPERATING CONDITIONS

### Recommended Operating Conditions

| Symbol   | Item                        | Rating     | Unit |
|----------|-----------------------------|------------|------|
| $V_{IN}$ | Input Voltage               | 1.7 to 6.5 | V    |
| $T_a$    | Operating Temperature Range | −40 to 85  | °C   |

### RECOMMENDED OPERATING CONDITIONS

All of electronic equipment should be designed that the mounted semiconductor devices operate within the recommended operating conditions. The semiconductor devices cannot operate normally over the recommended operating conditions, even if when they are used over such conditions by momentary electronic noise or surge. And the semiconductor devices may receive serious damage when they continue to operate over the recommended operating conditions.

<sup>(1)</sup> Refer to *POWER DISSIPATION* for detailed information.

## ELECTRICAL CHARACTERISTICS

$V_{IN} = V_{SET} + 1\text{ V}$  ( $V_{OUT} > 1.5\text{ V}$ ),  $V_{IN} = 2.5\text{ V}$  ( $V_{OUT} \leq 1.5\text{ V}$ ),  $I_{OUT} = 1\text{ mA}$ ,  $C_{IN} = C_{OUT} = 0.47\text{ }\mu\text{F}$ , unless otherwise noted.

The specifications surrounded by   are guaranteed by design engineering at  $-40^{\circ}\text{C} \leq T_a \leq 85^{\circ}\text{C}$ .

### RP130xxx1A Electrical Characteristics

(Ta = 25°C)

| Symbol                                  | Item                                   | Conditions                                                                                                                                                      |                                            | Min.                                                                 | Typ.              | Max.                                                                 | Unit                    |
|-----------------------------------------|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|----------------------------------------------------------------------|-------------------|----------------------------------------------------------------------|-------------------------|
| $V_{OUT}$                               | Output Voltage                         | $T_a = 25^{\circ}\text{C}$                                                                                                                                      | $V_{SET} > 2.0\text{ V}$                   | x 0.99                                                               |                   | x 1.01                                                               | V                       |
|                                         |                                        |                                                                                                                                                                 | $V_{SET} \leq 2.0\text{ V}$                | -20                                                                  |                   | 20                                                                   | mV                      |
|                                         |                                        | $-40^{\circ}\text{C} \leq T_a \leq 85^{\circ}\text{C}$                                                                                                          | $V_{SET} > 2.0\text{ V}$                   | <span style="border: 1px solid black; padding: 0 2px;">x0.985</span> |                   | <span style="border: 1px solid black; padding: 0 2px;">x1.015</span> | V                       |
|                                         |                                        |                                                                                                                                                                 | $V_{SET} \leq 2.0\text{ V}$                | <span style="border: 1px solid black; padding: 0 2px;">-30</span>    |                   | <span style="border: 1px solid black; padding: 0 2px;">30</span>     | mV                      |
| $I_{LIM}$                               | Output Current Limit                   |                                                                                                                                                                 |                                            | <span style="border: 1px solid black; padding: 0 2px;">150</span>    |                   |                                                                      | mA                      |
| $\frac{\Delta V_{OUT}}{\Delta I_{OUT}}$ | Load Regulation                        | $1\text{ mA} \leq I_{OUT} \leq 150\text{ mA}$                                                                                                                   |                                            |                                                                      | 10                | <span style="border: 1px solid black; padding: 0 2px;">30</span>     | mV                      |
| $V_{DIF}$                               | Dropout Voltage                        | $I_{OUT} = 150\text{ mA}$                                                                                                                                       | $1.2\text{ V} \leq V_{SET} < 1.5\text{ V}$ |                                                                      | 0.67              | <span style="border: 1px solid black; padding: 0 2px;">1.00</span>   | V                       |
|                                         |                                        |                                                                                                                                                                 | $1.5\text{ V} \leq V_{SET} < 1.7\text{ V}$ |                                                                      | 0.54              | <span style="border: 1px solid black; padding: 0 2px;">0.81</span>   |                         |
|                                         |                                        |                                                                                                                                                                 | $1.7\text{ V} \leq V_{SET} < 2.0\text{ V}$ |                                                                      | 0.46              | <span style="border: 1px solid black; padding: 0 2px;">0.68</span>   |                         |
|                                         |                                        |                                                                                                                                                                 | $2.0\text{ V} \leq V_{SET} < 2.5\text{ V}$ |                                                                      | 0.41              | <span style="border: 1px solid black; padding: 0 2px;">0.60</span>   |                         |
|                                         |                                        |                                                                                                                                                                 | $2.5\text{ V} \leq V_{SET} < 4.0\text{ V}$ |                                                                      | 0.32              | <span style="border: 1px solid black; padding: 0 2px;">0.51</span>   |                         |
|                                         |                                        |                                                                                                                                                                 | $4.0\text{ V} \leq V_{SET}$                |                                                                      | 0.24              | <span style="border: 1px solid black; padding: 0 2px;">0.37</span>   |                         |
| $I_{SS}$                                | Supply Current                         | $I_{OUT} = 0\text{ mA}$                                                                                                                                         |                                            |                                                                      | 38                | <span style="border: 1px solid black; padding: 0 2px;">58</span>     | $\mu\text{A}$           |
| $I_{standby}$                           | Supply Current (Standby)               | $V_{CE} = V_{IN}$                                                                                                                                               |                                            |                                                                      | 0.1               | 1.0                                                                  | $\mu\text{A}$           |
| $\frac{\Delta V_{OUT}}{\Delta V_{IN}}$  | Line Regulation                        | $V_{SET} + 0.5\text{ V} \leq V_{IN} \leq 6.5\text{ V}$                                                                                                          |                                            |                                                                      | 0.02              | <span style="border: 1px solid black; padding: 0 2px;">0.10</span>   | %/V                     |
| RR                                      | Ripple Rejection                       | f = 1 kHz, Ripple 0.2 Vp-p<br>$V_{IN} = V_{SET} + 1\text{ V}$<br>$I_{OUT} = 30\text{ mA}$ (In case that $V_{OUT} \leq 2.0\text{ V}$ , $V_{IN} = 3.0\text{ V}$ ) |                                            |                                                                      | 80                |                                                                      | dB                      |
| $V_{IN}$                                | Input Voltage                          |                                                                                                                                                                 |                                            | <span style="border: 1px solid black; padding: 0 2px;">1.7</span>    |                   | <span style="border: 1px solid black; padding: 0 2px;">6.5</span>    | V                       |
| $\frac{\Delta V_{OUT}}{\Delta T_a}$     | Output Voltage Temperature Coefficient | $-40^{\circ}\text{C} \leq T_a \leq 85^{\circ}\text{C}$                                                                                                          |                                            |                                                                      | $\pm 20$          |                                                                      | ppm/ $^{\circ}\text{C}$ |
| $I_{SC}$                                | Short Current Limit                    | $V_{OUT} = 0\text{ V}$                                                                                                                                          |                                            |                                                                      | 40                |                                                                      | mA                      |
| $V_{CEH}$                               | $\overline{CE}$ Input Voltage "H"      |                                                                                                                                                                 |                                            | <span style="border: 1px solid black; padding: 0 2px;">1.0</span>    |                   |                                                                      | $\mu\text{A}$           |
| $V_{CEL}$                               | $\overline{CE}$ Input Voltage "L"      |                                                                                                                                                                 |                                            |                                                                      |                   | <span style="border: 1px solid black; padding: 0 2px;">0.4</span>    |                         |
| en                                      | Output Noise                           | BW = 10 Hz to 100 kHz<br>$I_{OUT} = 30\text{ mA}$                                                                                                               |                                            |                                                                      | 20<br>x $V_{SET}$ |                                                                      | $\mu\text{Vrms}$        |

All test items listed under *Electrical Characteristics* are done under the pulse load condition ( $T_j \approx T_a = 25^{\circ}\text{C}$ ) except for Output Noise, Ripple Rejection, and Output Voltage Temperature Coefficient.

## ELECTRICAL CHARACTERISTICS (continued)

$V_{IN} = V_{SET} + 1\text{ V}$  ( $V_{OUT} > 1.5\text{ V}$ ),  $V_{IN} = 2.5\text{ V}$  ( $V_{OUT} \leq 1.5\text{ V}$ ),  $I_{OUT} = 1\text{ mA}$ ,  $C_{IN} = C_{OUT} = 0.47\text{ }\mu\text{F}$ , unless otherwise noted.

The specifications surrounded by   are guaranteed by design engineering at  $-40^{\circ}\text{C} \leq T_a \leq 85^{\circ}\text{C}$ .

### RP130xxx1B/D Electrical Characteristics

( $T_a = 25^{\circ}\text{C}$ )

| Symbol                            | Item                                              | Conditions                                                                                                                                                                           | Min.                                                              | Typ.                                                                  | Max.                                                                  | Unit                    |
|-----------------------------------|---------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|-----------------------------------------------------------------------|-----------------------------------------------------------------------|-------------------------|
| $V_{OUT}$                         | Output Voltage                                    | $T_a = 25^{\circ}\text{C}$                                                                                                                                                           | $V_{SET} > 2.0\text{ V}$                                          | x 0.99                                                                | x 1.01                                                                | V                       |
|                                   |                                                   |                                                                                                                                                                                      | $V_{SET} \leq 2.0\text{ V}$                                       | -20                                                                   | 20                                                                    | mV                      |
|                                   |                                                   | $-40^{\circ}\text{C} \leq T_a \leq 85^{\circ}\text{C}$                                                                                                                               | $V_{SET} > 2.0\text{ V}$                                          | <span style="border: 1px solid black; padding: 0 2px;">x 0.985</span> | <span style="border: 1px solid black; padding: 0 2px;">x 1.015</span> | V                       |
|                                   |                                                   |                                                                                                                                                                                      | $V_{SET} \leq 2.0\text{ V}$                                       | <span style="border: 1px solid black; padding: 0 2px;">-30</span>     | <span style="border: 1px solid black; padding: 0 2px;">30</span>      | mV                      |
| $I_{LIM}$                         | Output Current Limit                              |                                                                                                                                                                                      | <span style="border: 1px solid black; padding: 0 2px;">150</span> |                                                                       |                                                                       | mA                      |
| $\Delta V_{OUT} / \Delta I_{OUT}$ | Load Regulation                                   | $1\text{ mA} \leq I_{OUT} \leq 150\text{ mA}$                                                                                                                                        |                                                                   | 10                                                                    | <span style="border: 1px solid black; padding: 0 2px;">30</span>      | mV                      |
| $V_{DIF}$                         | Dropout Voltage                                   | $I_{OUT} = 150\text{ mA}$                                                                                                                                                            | $1.2\text{ V} \leq V_{SET} < 1.5\text{ V}$                        | 0.67                                                                  | <span style="border: 1px solid black; padding: 0 2px;">1.00</span>    |                         |
|                                   |                                                   |                                                                                                                                                                                      | $1.5\text{ V} \leq V_{SET} < 1.7\text{ V}$                        | 0.54                                                                  | <span style="border: 1px solid black; padding: 0 2px;">0.81</span>    |                         |
|                                   |                                                   |                                                                                                                                                                                      | $1.7\text{ V} \leq V_{SET} < 2.0\text{ V}$                        | 0.46                                                                  | <span style="border: 1px solid black; padding: 0 2px;">0.68</span>    |                         |
|                                   |                                                   |                                                                                                                                                                                      | $2.0\text{ V} \leq V_{SET} < 2.5\text{ V}$                        | 0.41                                                                  | <span style="border: 1px solid black; padding: 0 2px;">0.60</span>    |                         |
|                                   |                                                   |                                                                                                                                                                                      | $2.5\text{ V} \leq V_{SET} < 4.0\text{ V}$                        | 0.32                                                                  | <span style="border: 1px solid black; padding: 0 2px;">0.51</span>    |                         |
|                                   |                                                   |                                                                                                                                                                                      | $4.0\text{ V} \leq V_{SET}$                                       | 0.24                                                                  | <span style="border: 1px solid black; padding: 0 2px;">0.37</span>    |                         |
| $I_{SS}$                          | Supply Current                                    | $I_{OUT} = 0\text{ mA}$                                                                                                                                                              |                                                                   | 38                                                                    | <span style="border: 1px solid black; padding: 0 2px;">58</span>      | $\mu\text{A}$           |
| $I_{standby}$                     | Standby Current                                   | $V_{CE} = 0\text{ V}$                                                                                                                                                                |                                                                   | 0.1                                                                   | 1.0                                                                   | $\mu\text{A}$           |
| $\Delta V_{OUT} / \Delta V_{IN}$  | Line Regulation                                   | $V_{SET} + 0.5\text{ V} \leq V_{IN} \leq 6.5\text{ V}$                                                                                                                               |                                                                   | 0.02                                                                  | <span style="border: 1px solid black; padding: 0 2px;">0.10</span>    | %/V                     |
| RR                                | Ripple Rejection                                  | $f = 1\text{ kHz}$ , Ripple $0.2\text{ V}_{p-p}$<br>$V_{IN} = V_{SET} + 1\text{ V}$ , $I_{OUT} = 30\text{ mA}$ (In case that $V_{OUT} \leq 2.0\text{ V}$ , $V_{IN} = 3.0\text{ V}$ ) |                                                                   | 80                                                                    |                                                                       | dB                      |
| $V_{IN}$                          | Input Voltage                                     |                                                                                                                                                                                      | <span style="border: 1px solid black; padding: 0 2px;">1.7</span> |                                                                       | <span style="border: 1px solid black; padding: 0 2px;">6.5</span>     | V                       |
| $\Delta V_{OUT} / \Delta T_a$     | Output Voltage Temperature Coefficient            | $-40^{\circ}\text{C} \leq T_a \leq 85^{\circ}\text{C}$                                                                                                                               |                                                                   | $\pm 20$                                                              |                                                                       | ppm/ $^{\circ}\text{C}$ |
| $I_{SC}$                          | Short Current Limit                               | $V_{OUT} = 0\text{ V}$                                                                                                                                                               |                                                                   | 40                                                                    |                                                                       | mA                      |
| $I_{PD}$                          | CE Pull-down Current                              |                                                                                                                                                                                      |                                                                   | 0.4                                                                   |                                                                       | $\mu\text{A}$           |
| $V_{CEH}$                         | $\overline{\text{CE}}$ Input Voltage "H"          |                                                                                                                                                                                      | <span style="border: 1px solid black; padding: 0 2px;">1.0</span> |                                                                       |                                                                       | $\mu\text{A}$           |
| $V_{CEL}$                         | $\overline{\text{CE}}$ Input Voltage "L"          |                                                                                                                                                                                      |                                                                   |                                                                       | <span style="border: 1px solid black; padding: 0 2px;">0.4</span>     |                         |
| en                                | Output Noise                                      | BW = 10 Hz to 100 kHz<br>$I_{OUT} = 30\text{ mA}$                                                                                                                                    |                                                                   | 20<br>x $V_{SET}$                                                     |                                                                       | $\mu\text{V}_{rms}$     |
| $R_{LOW}$                         | Nch ON Resistance for Auto Discharge (RP130xxx1D) | $V_{IN} = 4.0\text{ V}$<br>$V_{CE} = 0\text{ V}$                                                                                                                                     |                                                                   | 30                                                                    |                                                                       | $\Omega$                |

All test items listed under *Electrical Characteristics* are done under the pulse load condition ( $T_j \approx T_a = 25^{\circ}\text{C}$ ) except for Output Noise, Ripple Rejection, and Output Voltage Temperature Coefficient.

## RP130x

No. EA-173-181227

The specifications surrounded by   are guaranteed by design engineering at  $-40^{\circ}\text{C} \leq T_a \leq 85^{\circ}\text{C}$ .


### Product-specific Electrical Characteristics

( $T_a = 25^{\circ}\text{C}$ )

| Product Name | $V_{\text{OUT}} [\text{V}]$<br>( $T_a = 25^{\circ}\text{C}$ ) |      |       | $V_{\text{OUT}} [\text{V}]$<br>( $T_a = -40^{\circ}\text{C}$ to $85^{\circ}\text{C}$ ) |      |                                                                     | $V_{\text{DIF}} [\text{V}]$ |                                                                    |
|--------------|---------------------------------------------------------------|------|-------|----------------------------------------------------------------------------------------|------|---------------------------------------------------------------------|-----------------------------|--------------------------------------------------------------------|
|              | Min.                                                          | Typ. | Max.  | Min.                                                                                   | Typ. | Max.                                                                | Typ.                        | Max.                                                               |
| RP130x121x   | 1.180                                                         | 1.2  | 1.220 | <span style="border: 1px solid black; padding: 0 2px;">1.170</span>                    | 1.2  | <span style="border: 1px solid black; padding: 0 2px;">1.230</span> | 0.67                        | <span style="border: 1px solid black; padding: 0 2px;">1.00</span> |
| RP130x121x5  | 1.230                                                         | 1.25 | 1.270 | <span style="border: 1px solid black; padding: 0 2px;">1.220</span>                    | 1.25 | <span style="border: 1px solid black; padding: 0 2px;">1.280</span> |                             |                                                                    |
| RP130x131x   | 1.280                                                         | 1.3  | 1.320 | <span style="border: 1px solid black; padding: 0 2px;">1.270</span>                    | 1.3  | <span style="border: 1px solid black; padding: 0 2px;">1.330</span> |                             |                                                                    |
| RP130x141x   | 1.380                                                         | 1.4  | 1.420 | <span style="border: 1px solid black; padding: 0 2px;">1.370</span>                    | 1.4  | <span style="border: 1px solid black; padding: 0 2px;">1.430</span> | 0.54                        | <span style="border: 1px solid black; padding: 0 2px;">0.81</span> |
| RP130x151x   | 1.480                                                         | 1.5  | 1.520 | <span style="border: 1px solid black; padding: 0 2px;">1.470</span>                    | 1.5  | <span style="border: 1px solid black; padding: 0 2px;">1.530</span> |                             |                                                                    |
| RP130x161x   | 1.580                                                         | 1.6  | 1.620 | <span style="border: 1px solid black; padding: 0 2px;">1.570</span>                    | 1.6  | <span style="border: 1px solid black; padding: 0 2px;">1.630</span> |                             |                                                                    |
| RP130x171x   | 1.680                                                         | 1.7  | 1.720 | <span style="border: 1px solid black; padding: 0 2px;">1.670</span>                    | 1.7  | <span style="border: 1px solid black; padding: 0 2px;">1.730</span> | 0.46                        | <span style="border: 1px solid black; padding: 0 2px;">0.68</span> |
| RP130x181x   | 1.780                                                         | 1.8  | 1.820 | <span style="border: 1px solid black; padding: 0 2px;">1.770</span>                    | 1.8  | <span style="border: 1px solid black; padding: 0 2px;">1.830</span> |                             |                                                                    |
| RP130x181x5  | 1.830                                                         | 1.85 | 1.870 | <span style="border: 1px solid black; padding: 0 2px;">1.820</span>                    | 1.85 | <span style="border: 1px solid black; padding: 0 2px;">1.880</span> |                             |                                                                    |
| RP130x191x   | 1.880                                                         | 1.9  | 1.920 | <span style="border: 1px solid black; padding: 0 2px;">1.870</span>                    | 1.9  | <span style="border: 1px solid black; padding: 0 2px;">1.930</span> | 0.41                        | <span style="border: 1px solid black; padding: 0 2px;">0.60</span> |
| RP130x201x   | 1.980                                                         | 2.0  | 2.020 | <span style="border: 1px solid black; padding: 0 2px;">1.970</span>                    | 2.0  | <span style="border: 1px solid black; padding: 0 2px;">2.030</span> |                             |                                                                    |
| RP130x211x   | 2.079                                                         | 2.1  | 2.121 | <span style="border: 1px solid black; padding: 0 2px;">2.069</span>                    | 2.1  | <span style="border: 1px solid black; padding: 0 2px;">2.132</span> |                             |                                                                    |
| RP130x221x   | 2.178                                                         | 2.2  | 2.222 | <span style="border: 1px solid black; padding: 0 2px;">2.167</span>                    | 2.2  | <span style="border: 1px solid black; padding: 0 2px;">2.233</span> | 0.32                        | <span style="border: 1px solid black; padding: 0 2px;">0.51</span> |
| RP130x231x   | 2.277                                                         | 2.3  | 2.323 | <span style="border: 1px solid black; padding: 0 2px;">2.266</span>                    | 2.3  | <span style="border: 1px solid black; padding: 0 2px;">2.335</span> |                             |                                                                    |
| RP130x241x   | 2.376                                                         | 2.4  | 2.424 | <span style="border: 1px solid black; padding: 0 2px;">2.364</span>                    | 2.4  | <span style="border: 1px solid black; padding: 0 2px;">2.436</span> |                             |                                                                    |
| RP130x251x   | 2.475                                                         | 2.5  | 2.525 | <span style="border: 1px solid black; padding: 0 2px;">2.463</span>                    | 2.5  | <span style="border: 1px solid black; padding: 0 2px;">2.538</span> | 0.24                        | <span style="border: 1px solid black; padding: 0 2px;">0.37</span> |
| RP130x261x   | 2.574                                                         | 2.6  | 2.626 | <span style="border: 1px solid black; padding: 0 2px;">2.561</span>                    | 2.6  | <span style="border: 1px solid black; padding: 0 2px;">2.639</span> |                             |                                                                    |
| RP130x271x   | 2.673                                                         | 2.7  | 2.727 | <span style="border: 1px solid black; padding: 0 2px;">2.660</span>                    | 2.7  | <span style="border: 1px solid black; padding: 0 2px;">2.741</span> |                             |                                                                    |
| RP130x281x   | 2.772                                                         | 2.8  | 2.828 | <span style="border: 1px solid black; padding: 0 2px;">2.758</span>                    | 2.8  | <span style="border: 1px solid black; padding: 0 2px;">2.842</span> | 0.24                        | <span style="border: 1px solid black; padding: 0 2px;">0.37</span> |
| RP130x281x5  | 2.822                                                         | 2.85 | 2.879 | <span style="border: 1px solid black; padding: 0 2px;">2.807</span>                    | 2.85 | <span style="border: 1px solid black; padding: 0 2px;">2.893</span> |                             |                                                                    |
| RP130x291x   | 2.871                                                         | 2.9  | 2.929 | <span style="border: 1px solid black; padding: 0 2px;">2.857</span>                    | 2.9  | <span style="border: 1px solid black; padding: 0 2px;">2.944</span> |                             |                                                                    |
| RP130x301x   | 2.970                                                         | 3.0  | 3.030 | <span style="border: 1px solid black; padding: 0 2px;">2.955</span>                    | 3.0  | <span style="border: 1px solid black; padding: 0 2px;">3.045</span> | 0.24                        | <span style="border: 1px solid black; padding: 0 2px;">0.37</span> |
| RP130x311x   | 3.069                                                         | 3.1  | 3.131 | <span style="border: 1px solid black; padding: 0 2px;">3.054</span>                    | 3.1  | <span style="border: 1px solid black; padding: 0 2px;">3.147</span> |                             |                                                                    |
| RP130x321x   | 3.168                                                         | 3.2  | 3.232 | <span style="border: 1px solid black; padding: 0 2px;">3.152</span>                    | 3.2  | <span style="border: 1px solid black; padding: 0 2px;">3.248</span> |                             |                                                                    |
| RP130x331x   | 3.267                                                         | 3.3  | 3.333 | <span style="border: 1px solid black; padding: 0 2px;">3.251</span>                    | 3.3  | <span style="border: 1px solid black; padding: 0 2px;">3.350</span> | 0.24                        | <span style="border: 1px solid black; padding: 0 2px;">0.37</span> |
| RP130x341x   | 3.366                                                         | 3.4  | 3.434 | <span style="border: 1px solid black; padding: 0 2px;">3.349</span>                    | 3.4  | <span style="border: 1px solid black; padding: 0 2px;">3.451</span> |                             |                                                                    |
| RP130x341x5  | 3.416                                                         | 3.45 | 3.485 | <span style="border: 1px solid black; padding: 0 2px;">3.398</span>                    | 3.45 | <span style="border: 1px solid black; padding: 0 2px;">3.502</span> |                             |                                                                    |
| RP130x351x   | 3.465                                                         | 3.5  | 3.535 | <span style="border: 1px solid black; padding: 0 2px;">3.448</span>                    | 3.5  | <span style="border: 1px solid black; padding: 0 2px;">3.553</span> | 0.24                        | <span style="border: 1px solid black; padding: 0 2px;">0.37</span> |
| RP130x361x   | 3.564                                                         | 3.6  | 3.636 | <span style="border: 1px solid black; padding: 0 2px;">3.546</span>                    | 3.6  | <span style="border: 1px solid black; padding: 0 2px;">3.654</span> |                             |                                                                    |
| RP130x371x   | 3.663                                                         | 3.7  | 3.737 | <span style="border: 1px solid black; padding: 0 2px;">3.645</span>                    | 3.7  | <span style="border: 1px solid black; padding: 0 2px;">3.756</span> |                             |                                                                    |
| RP130x381x   | 3.762                                                         | 3.8  | 3.838 | <span style="border: 1px solid black; padding: 0 2px;">3.743</span>                    | 3.8  | <span style="border: 1px solid black; padding: 0 2px;">3.857</span> | 0.24                        | <span style="border: 1px solid black; padding: 0 2px;">0.37</span> |
| RP130x391x   | 3.861                                                         | 3.9  | 3.939 | <span style="border: 1px solid black; padding: 0 2px;">3.842</span>                    | 3.9  | <span style="border: 1px solid black; padding: 0 2px;">3.959</span> |                             |                                                                    |
| RP130x401x   | 3.960                                                         | 4.0  | 4.040 | <span style="border: 1px solid black; padding: 0 2px;">3.940</span>                    | 4.0  | <span style="border: 1px solid black; padding: 0 2px;">4.060</span> |                             |                                                                    |
| RP130x411x   | 4.059                                                         | 4.1  | 4.141 | <span style="border: 1px solid black; padding: 0 2px;">4.039</span>                    | 4.1  | <span style="border: 1px solid black; padding: 0 2px;">4.162</span> | 0.24                        | <span style="border: 1px solid black; padding: 0 2px;">0.37</span> |
| RP130x421x   | 4.158                                                         | 4.2  | 4.242 | <span style="border: 1px solid black; padding: 0 2px;">4.137</span>                    | 4.2  | <span style="border: 1px solid black; padding: 0 2px;">4.263</span> |                             |                                                                    |
| RP130x421x5  | 4.208                                                         | 4.25 | 4.293 | <span style="border: 1px solid black; padding: 0 2px;">4.186</span>                    | 4.25 | <span style="border: 1px solid black; padding: 0 2px;">4.314</span> |                             |                                                                    |
| RP130x431x   | 4.257                                                         | 4.3  | 4.343 | <span style="border: 1px solid black; padding: 0 2px;">4.236</span>                    | 4.3  | <span style="border: 1px solid black; padding: 0 2px;">4.365</span> | 0.24                        | <span style="border: 1px solid black; padding: 0 2px;">0.37</span> |
| RP130x441x   | 4.356                                                         | 4.4  | 4.444 | <span style="border: 1px solid black; padding: 0 2px;">4.334</span>                    | 4.4  | <span style="border: 1px solid black; padding: 0 2px;">4.466</span> |                             |                                                                    |
| RP130x451x   | 4.455                                                         | 4.5  | 4.545 | <span style="border: 1px solid black; padding: 0 2px;">4.433</span>                    | 4.5  | <span style="border: 1px solid black; padding: 0 2px;">4.568</span> |                             |                                                                    |
| RP130x461x   | 4.554                                                         | 4.6  | 4.646 | <span style="border: 1px solid black; padding: 0 2px;">4.531</span>                    | 4.6  | <span style="border: 1px solid black; padding: 0 2px;">4.669</span> | 0.24                        | <span style="border: 1px solid black; padding: 0 2px;">0.37</span> |
| RP130x471x   | 4.653                                                         | 4.7  | 4.747 | <span style="border: 1px solid black; padding: 0 2px;">4.630</span>                    | 4.7  | <span style="border: 1px solid black; padding: 0 2px;">4.771</span> |                             |                                                                    |
| RP130x481x   | 4.752                                                         | 4.8  | 4.848 | <span style="border: 1px solid black; padding: 0 2px;">4.728</span>                    | 4.8  | <span style="border: 1px solid black; padding: 0 2px;">4.872</span> |                             |                                                                    |
| RP130x491x   | 4.851                                                         | 4.9  | 4.949 | <span style="border: 1px solid black; padding: 0 2px;">4.827</span>                    | 4.9  | <span style="border: 1px solid black; padding: 0 2px;">4.974</span> | 0.24                        | <span style="border: 1px solid black; padding: 0 2px;">0.37</span> |
| RP130x501x   | 4.950                                                         | 5.0  | 5.050 | <span style="border: 1px solid black; padding: 0 2px;">4.925</span>                    | 5.0  | <span style="border: 1px solid black; padding: 0 2px;">5.075</span> |                             |                                                                    |
| RP130x511x   | 5.049                                                         | 5.1  | 5.151 | <span style="border: 1px solid black; padding: 0 2px;">5.024</span>                    | 5.1  | <span style="border: 1px solid black; padding: 0 2px;">5.177</span> |                             |                                                                    |
| RP130x521x   | 5.148                                                         | 5.2  | 5.252 | <span style="border: 1px solid black; padding: 0 2px;">5.122</span>                    | 5.2  | <span style="border: 1px solid black; padding: 0 2px;">5.278</span> | 0.24                        | <span style="border: 1px solid black; padding: 0 2px;">0.37</span> |
| RP130x531x   | 5.247                                                         | 5.3  | 5.353 | <span style="border: 1px solid black; padding: 0 2px;">5.221</span>                    | 5.3  | <span style="border: 1px solid black; padding: 0 2px;">5.380</span> |                             |                                                                    |

## APPLICATION INFORMATION

### TYPICAL APPLICATION



RP130x Typical Application

### External Components

| Symbol | Descriptions                                                |
|--------|-------------------------------------------------------------|
| C1, C2 | 0.47 $\mu$ F, Ceramic Capacitor, Murata, GRM155B30J474KE18B |

## TECHNICAL NOTES

### Phase Compensation

In these ICs, phase compensation is made for securing stable operation even if the load current is varied. For this purpose, use a capacitor C2 with 0.47  $\mu$ F or more. If a tantalum capacitor is used, and its ESR (Equivalent Series Resistance) of C2 is large, the loop oscillation may result. Because of this, select C2 carefully considering its frequency characteristics.




### PCB Layout

Make VDD and GND lines sufficient. If their impedance is high, noise pickup or unstable operation may result. Connect a capacitor C1 with a capacitance value as much as 0.47  $\mu$ F or more between VDD and GND pin, and as close as possible to the pins. Set external components, especially the output capacitor C2, as close as possible to the ICs, and make wiring as short as possible.



## TYPICAL CHARACTERISTICS


Typical characteristics are intended to be used as reference data, they are not guaranteed.

### 1) Output Voltage vs. Output Current ( $C_1 = 0.47 \mu\text{F}$ , $C_2 = 0.47 \mu\text{F}$ , $T_a = 25^\circ\text{C}$ )






### 2) Output Voltage vs. Input Voltage ( $C_1 = 0.47 \mu\text{F}$ , $C_2 = 0.47 \mu\text{F}$ , $T_a = 25^\circ\text{C}$ )





**3) Supply Current vs. Input Voltage ( $C1 = 0.47 \mu\text{F}$ ,  $C2 = 0.47 \mu\text{F}$ ,  $T_a = 25^\circ\text{C}$ )**









---

**RP130x**




---

No. EA-173-181227

**4) Output Voltage vs. Temperature ( $I_{OUT} = 1\text{ mA}$ ,  $C1 = 0.47\text{ }\mu\text{F}$ ,  $C2 = 0.47\text{ }\mu\text{F}$ )****5) Supply Current vs. Temperature ( $I_{OUT} = 0\text{ mA}$ ,  $C1 = 0.47\text{ }\mu\text{F}$ ,  $C2 = 0.47\text{ }\mu\text{F}$ )**



**6) Dropout Voltage vs. Output Current ( $C1 = 0.47 \mu F$ ,  $C2 = 0.47 \mu F$ )**




---

## RP130x



---

No. EA-173-181227



### 7) Dropout Voltage vs. Set Output Voltage ( $C_1 = 0.47 \mu\text{F}$ , $C_2 = 0.47 \mu\text{F}$ )




### 8) Ripple Rejection vs. Input Bias Voltage ( $C_1 = \text{none}$ , $C_2 = 0.47 \mu\text{F}$ , Ripple = 0.2 Vp-p, $T_a = 25^\circ\text{C}$ )






### 9) Ripple Rejection vs. Frequency ( $C_1 = \text{none}$ , $C_2 = 0.47 \mu\text{F}$ , Ripple = 0.2 Vp-p, $T_a = 25^\circ\text{C}$ )





**10) Input Transient Response ( $I_{OUT} = 30\text{ mA}$ ,  $t_r = t_f = 5\text{ }\mu\text{s}$ ,  $C_1 = \text{none}$ ,  $C_2 = 0.47\text{ }\mu\text{F}$ ,  $T_a = 25^\circ\text{C}$ )**








---


**RP130x**

---

No. EA-173-181227


**11) Load Transient Response** $(t_r = t_f = 0.5 \mu s, C_1 = 0.47 \mu F, C_2 = 0.47 \mu F, I_{OUT} = 50mA \leftrightarrow 100 mA, T_a = 25^\circ C)$ **RP130x121x****RP130x281x****RP130x501x****12) Load Transient Response** $(t_r = t_f = 0.5 \mu s, C_1 = 0.47 \mu F, C_2 = 0.47 \mu F, I_{OUT} = 1 mA \leftrightarrow 150mA, T_a = 25^\circ C)$ **RP130x121x****RP130x281x**

RP130x501x




13) Turn On Speed with CE pin ( $C1 = 0.47 \mu$ F,  $C2 = 0.47 \mu$ F,  $T_a = 25^\circ$ C)


RP130x121x




RP130x121x








RP130x121x












RP130x281x






14) Turn Off Speed with CE pin (RP130xxx1D) (C1 = 0.47  $\mu$ F, C2 = 0.47  $\mu$ F, Ta = 25°C)





**15) Minimum Operating Voltage ( $C1 = 0.47 \mu F$ ,  $C2 = 0.47 \mu F$ )**



Hatched area is available for 1.2 V output.

## ESR vs. Output Current

When using these ICs, consider the following points:

The relations between  $I_{OUT}$  (Output Current) and ESR of an output capacitor are shown below.




The conditions when the white noise level is under  $40\text{ }\mu\text{V}$  (Avg.) are marked as the hatched area in the graph.

### Measurement conditions

Frequency Band : 10 Hz to 3 MHz

Temperature :  $-40^{\circ}\text{C}$  to  $85^{\circ}\text{C}$

C1, C2 :  $0.47\text{ }\mu\text{F}$



The power dissipation of the package is dependent on PCB material, layout, and environmental conditions. The following measurement conditions are based on JEDEC STD. 51-7.


Measurement Conditions

| Item             | Measurement Conditions                                                                                                                                                                       |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Environment      | Mounting on Board (Wind Velocity = 0 m/s)                                                                                                                                                    |
| Board Material   | Glass Cloth Epoxy Plastic (Four-Layer Board)                                                                                                                                                 |
| Board Dimensions | 76.2 mm × 114.3 mm × 0.8 mm                                                                                                                                                                  |
| Copper Ratio     | Outer Layer (First Layer): Less than 95% of 50 mm Square<br>Inner Layers (Second and Third Layers): Approx. 100% of 50 mm Square<br>Outer Layer (Fourth Layer): Approx. 100% of 50 mm Square |
| Through-holes    | φ 0.2 mm × 11 pcs                                                                                                                                                                            |


Measurement Result (Ta = 25°C, Tjmax = 125°C)

| Item                                     | Measurement Result |
|------------------------------------------|--------------------|
| Power Dissipation                        | 800 mW             |
| Thermal Resistance (θja)                 | θja = 125°C/W      |
| Thermal Characterization Parameter (ψjt) | ψjt = 58°C/W       |

θja: Junction-to-Ambient Thermal Resistance  
ψjt: Junction-to-Top Thermal Characterization Parameter




Power Dissipation vs. Ambient Temperature



Measurement Board Pattern

The above graph shows the power dissipation of the package at Tjmax = 125°C and Tjmax = 150°C. Operating the device in the hatched range might have a negative influence on its lifetime. The total hours of use and the total years of use must be limited as follows:

| Total Hours of Use | Total Years of Use (4 hours/day) |
|--------------------|----------------------------------|
| 13,000 hours       | 9 years                          |



UNIT: mm

DFN(PLP)1010-4 Package Dimensions

\* The tab on the bottom of the package shown by blue circle is a substrate potential (GND). It is recommended that this tab be connected to the ground plane on the board but it is possible to leave the tab floating.

The power dissipation of the package is dependent on PCB material, layout, and environmental conditions. The following conditions are used in this measurement.

Measurement Conditions


| Item             | Standard Land Pattern                             |
|------------------|---------------------------------------------------|
| Environment      | Mounting on Board (Wind Velocity = 0 m/s)         |
| Board Material   | Glass Cloth Epoxy Plastic (Double-Sided Board)    |
| Board Dimensions | 40 mm × 40 mm × 1.6 mm                            |
| Copper Ratio     | Top Side: Approx. 50%<br>Bottom Side: Approx. 50% |
| Through-holes    | φ 0.5 mm × 44 pcs                                 |

Measurement Result


(Ta = 25°C, Tjmax = 125°C)

| Item                     | Standard Land Pattern |
|--------------------------|-----------------------|
| Power Dissipation        | 380 mW                |
| Thermal Resistance (θja) | θja = 263°C/W         |

θja: Junction-to-Ambient Thermal Resistance




Power Dissipation vs. Ambient Temperature



Measurement Board Pattern

The above graph shows the power dissipation of the package at Tjmax = 125°C and Tjmax = 150°C. Operating the device in the hatched range might have a negative influence on its lifetime. The total hours of use and the total years of use must be limited as follows:

| Total Hours of Use | Total Years of Use (4 hours/day) |
|--------------------|----------------------------------|
| 13,000 hours       | 9 years                          |



### SC-82AB Package Dimensions

The power dissipation of the package is dependent on PCB material, layout, and environmental conditions. The following measurement conditions are based on JEDEC STD. 51-7.

Measurement Conditions

| Item             | Measurement Conditions                                                                                                                                                                       |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Environment      | Mounting on Board (Wind Velocity = 0 m/s)                                                                                                                                                    |
| Board Material   | Glass Cloth Epoxy Plastic (Four-Layer Board)                                                                                                                                                 |
| Board Dimensions | 76.2 mm × 114.3 mm × 0.8 mm                                                                                                                                                                  |
| Copper Ratio     | Outer Layer (First Layer): Less than 95% of 50 mm Square<br>Inner Layers (Second and Third Layers): Approx. 100% of 50 mm Square<br>Outer Layer (Fourth Layer): Approx. 100% of 50 mm Square |
| Through-holes    | φ 0.3 mm × 7 pcs                                                                                                                                                                             |


Measurement Result

(Ta = 25°C, Tjmax = 125°C)


| Item                                     | Measurement Result |
|------------------------------------------|--------------------|
| Power Dissipation                        | 660 mW             |
| Thermal Resistance (θja)                 | θja = 150°C/W      |
| Thermal Characterization Parameter (ψjt) | ψjt = 51°C/W       |

θja: Junction-to-Ambient Thermal Resistance

ψjt: Junction-to-Top Thermal Characterization Parameter




Power Dissipation vs. Ambient Temperature



Measurement Board Pattern

The above graph shows the power dissipation of the package at Tjmax = 125°C and Tjmax = 150°C. Operating the device in the hatched range might have a negative influence on its lifetime. The total hours of use and the total years of use must be limited as follows:

| Total Hours of Use | Total Years of Use (4 hours/day) |
|--------------------|----------------------------------|
| 13,000 hours       | 9 years                          |



### SOT-23-5 Package Dimensions



1. The products and the product specifications described in this document are subject to change or discontinuation of production without notice for reasons such as improvement. Therefore, before deciding to use the products, please refer to our sales representatives for the latest information thereon.
2. The materials in this document may not be copied or otherwise reproduced in whole or in part without prior written consent of our company.
3. Please be sure to take any necessary formalities under relevant laws or regulations before exporting or otherwise taking out of your country the products or the technical information described herein.
4. The technical information described in this document shows typical characteristics of and example application circuits for the products. The release of such information is not to be construed as a warranty of or a grant of license under our company's or any third party's intellectual property rights or any other rights.
5. The products listed in this document are intended and designed for use as general electronic components in standard applications (office equipment, telecommunication equipment, measuring instruments, consumer electronic products, amusement equipment etc.). Those customers intending to use a product in an application requiring extreme quality and reliability, for example, in a highly specific application where the failure or misoperation of the product could result in human injury or death (aircraft, spacevehicle, nuclear reactor control system, traffic control system, automotive and transportation equipment, combustion equipment, safety devices, life support system etc.) should first contact us.
6. We are making our continuous effort to improve the quality and reliability of our products, but semiconductor products are likely to fail with certain probability. In order to prevent any injury to persons or damages to property resulting from such failure, customers should be careful enough to incorporate safety measures in their design, such as redundancy feature, fire containment feature and fail-safe feature. We do not assume any liability or responsibility for any loss or damage arising from misuse or inappropriate use of the products.
7. Anti-radiation design is not implemented in the products described in this document.
8. The X-ray exposure can influence functions and characteristics of the products. Confirm the product functions and characteristics in the evaluation stage.
9. WLCSP products should be used in light shielded environments. The light exposure can influence functions and characteristics of the products under operation or storage.
10. There can be variation in the marking when different AOI (Automated Optical Inspection) equipment is used. In the case of recognizing the marking characteristic with AOI, please contact our sales or our distributor before attempting to use AOI.
11. Please contact our sales representatives should you have any questions or comments concerning the products or the technical information.



**Nisshinbo Micro Devices Inc.**

**Official website**

<https://www.nisshinbo-microdevices.co.jp/en/>

**Purchase information**

<https://www.nisshinbo-microdevices.co.jp/en/buy/>