
# HEXFRED®
# Ultrafast Soft Recovery Diode, 167 A



TO-244




## FEATURES

- Very low $Q_{rr}$ and $t_{rr}$
- UL approved file E222165
- Designed and qualified for industrial level
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

RoHS COMPLIANT

## BENEFITS

- Reduced RFI and EMI
- Reduced snubbing

## DESCRIPTION / APPLICATIONS

HEXFRED® diodes are optimized to reduce losses and EMI/RFI in high frequency power conditioning systems. An extensive characterization of the recovery behavior for different values of current, temperature and $dI_F/dt$ simplifies the calculations of losses in the operating conditions. The softness of the recovery eliminates the need for a snubber in most applications. These devices are ideally suited for power converters, motors drives and other applications where switching losses are significant portion of the total losses.

| PRIMARY CHARACTERISTICS | |
|---|---|
| $I_F$ (maximum) | 167 A |
| $V_R$ | 600 V |
| $I_{F(DC)}$ at $T_C$ | 84 A at 100 °C |
| Package | TO-244 |
| Circuit configuration | Two diodes common cathode |

**ABSOLUTE MAXIMUM RATINGS**

| PARAMETER | SYMBOL | TEST CONDITIONS | VALUES | UNITS |
|---|---|---|---|---|
| Cathode to anode voltage | $V_R$ | | 600 | V |
| Continuous forward current | $I_F$ | $T_C$ = 25 °C | 167 | A |
| | | $T_C$ = 100 °C | 84 | |
| Single pulse forward current | $I_{FSM}$ | Limited by junction temperature | 400 | |
| Non-repetitive avalanche energy | $E_{AS}$ | L = 100 µH, duty cycle limited by maximum $T_J$ | 330 | µJ |
| Maximum power dissipation | $P_D$ | $T_C$ = 25 °C | 310 | W |
| | | $T_C$ = 100 °C | 132 | |
| Operating junction and storage temperature range | $T_J$, $T_{Stg}$ | | -55 to +150 | °C |

**ELECTRICAL SPECIFICATIONS PER LEG** ($T_J$ = 25 °C unless otherwise specified)

| PARAMETER | SYMBOL | TEST CONDITIONS | | MIN. | TYP. | MAX. | UNITS |
|---|---|---|---|---|---|---|---|
| Cathode to anode breakdown voltage | $V_{BR}$ | $I_R$ = 100 µA | | 600 | - | - | V |
| Maximum forward voltage | $V_{FM}$ | $I_F$ = 70 A | See fig. 1 | - | 1.37 | 1.89 | |
| | | $I_F$ = 140 A | | - | 1.58 | 2.1 | |
| | | $I_F$ = 70 A, $T_J$ = 125 °C | | - | 1.29 | 1.54 | |
| Maximum reverse leakage current | $I_{RM}$ | $T_J$ = 125 °C, $V_R$ = 480 V | See fig. 2 | - | 1.2 | 4 | mA |
| Junction capacitance | $C_T$ | $V_R$ = 200 V | See fig. 3 | - | 140 | 250 | pF |
| Series inductance | $L_S$ | From top of terminal hole to mounting plane | | - | 7.0 | - | nH |



For technical questions within your region: DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

| DYNAMIC RECOVERY CHARACTERISTICS ($T_J$ = 25 °C unless otherwise specified) | | | | | | | |
|---|---|---|---|---|---|---|---|
| **PARAMETER** | **SYMBOL** | **TEST CONDITIONS** | | **MIN.** | **TYP.** | **MAX.** | **UNITS** |
| Reverse recovery time (fig. 5) | $t_{rr}$ | $I_F$ = 1.0 A, $dI_F/dt$ = 200 A/µs, $V_R$ = 30 V | | - | 33 | - | ns |
| | | $T_J$ = 25 °C | $I_F$ = 70 A<br>$dI_F/dt$ = 200 A/µs<br>$V_R$ = 200 V | - | 80 | 120 | |
| | | $T_J$ = 125 °C | | - | 140 | 220 | |
| Peak recovery current (fig. 6) | $I_{RRM}$ | $T_J$ = 25 °C | | - | 8.5 | 15 | A |
| | | $T_J$ = 125 °C | | - | 14 | 25 | |
| Reverse recovery charge (fig. 7) | $Q_{rr}$ | $T_J$ = 25 °C | | - | 340 | 900 | nC |
| | | $T_J$ = 125 °C | | - | 980 | 2300 | |
| Peak rate of recovery current (fig. 8) | $dI_{(rec)M}/dt$ | $T_J$ = 25 °C | | - | 300 | - | A/µs |
| | | $T_J$ = 125 °C | | - | 220 | - | |

| THERMAL - MECHANICAL SPECIFICATIONS | | | | | | |
|---|---|---|---|---|---|---|
| **PARAMETER** | | **SYMBOL** | **MIN.** | **TYP.** | **MAX.** | **UNITS** |
| Maximum junction and storage temperature range | | $T_J$, $T_{Stg}$ | -55 | - | 150 | °C |
| Thermal resistance, junction to case | per leg | $R_{thJC}$ | - | - | 0.38 | °C/W<br>K/W |
| | per module | | - | - | 0.19 | |
| Typical thermal resistance, case to heatsink | | $R_{thCS}$ | | 0.10 | - | |
| Weight | | | - | 68 | - | g |
| | | | - | 2.4 | - | oz. |
| Mounting torque (1) | | | 30 (3.4) | - | 40 (4.6) | lbf · in<br>(N · m) |
| Mounting torque center hole | | | 12 (1.4) | - | 18 (2.1) | |
| Terminal torque | | | 30 (3.4) | - | 40 (4.6) | |
| Vertical pull | | | - | - | 80 | lbf · in |
| 2" lever pull | | | - | - | 35 | |

**Note**

(1) Mounting surface must be smooth, flat, free or burrs or other protrusions. Apply a thin even film or thermal grease to mounting surface. Gradually tighten each mounting bolt in 5 - 10 lbf · in steps until desired or maximum torque limits are reached





Fig. 1 - Maximum Forward Voltage Drop vs. Instantaneous Forward Current (Per Leg)





Fig. 2 - Typical Reverse Current vs. Reverse Voltage (Per Leg)


For technical questions within your region: DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000





Fig. 3 - Typical Junction Capacitance vs. Reverse Voltage (Per Leg)





Fig. 6 - Typical Recovery Current vs. $dI_F/dt$ (Per Leg)





Fig. 4 - Maximum Allowable Case Temperature vs. DC Forward Current (Per Leg)





Fig. 7 - Typical Stored Charge vs. $dI_F/dt$ (Per Leg)





Fig. 5 - Typical Reverse Recovery Time vs. $dI_F/dt$ (Per Leg)





Fig. 8 - Typical $dI_{(rec)M}/dt$ vs. $dI_F/dt$ (Per Leg)


For technical questions within your region: DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000





Fig. 9 - Maximum Thermal Impedance $Z_{thJC}$ Characteristics






Fig. 10 - Reverse Recovery Parameter Test Circuit




(1) $di_F/dt$ - rate of change of current through zero crossing

(2) $I_{RRM}$ - peak reverse recovery current

(3) $t_{rr}$ - reverse recovery time measured from zero crossing point of negative going $I_F$ to point where a line passing through 0.75 $I_{RRM}$ and 0.50 $I_{RRM}$ extrapolated to zero current.

(4) $Q_{rr}$ - area under curve defined by $t_{rr}$ and $I_{RRM}$

$$Q_{rr} = \frac{t_{rr} \times I_{RRM}}{2}$$

(5) $di_{(rec)M}/dt$ - peak rate of change of current during $t_b$ portion of $t_{rr}$

Fig. 11 - Reverse Recovery Waveform and Definitions


For technical questions within your region: DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000





Fig. 12 - Avalanche Test Circuit and Waveforms

## ORDERING INFORMATION TABLE

Device code

| VS- | HFA | 140 | NJ | 60 | C | PbF |
|---|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 |


| | | |
|---|---|---|
| 1 | - | Vishay Semiconductors product |
| 2 | - | HEXFRED® family |
| 3 | - | Average current rating |
| 4 | - | NJ = TO-244 |
| 5 | - | Voltage rating (600 V) |
| 6 | - | C = two diodes common cathode |
| 7 | - | Lead (Pb)-free |

| LINKS TO RELATED DOCUMENTS | |
|---|---|
| Dimensions | www.vishay.com/doc?95021 |


For technical questions within your region: DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

# TO-244

**DIMENSIONS** in millimeters (inches)






For technical questions within your region: DiodesAmericas@vishay.com, DiodesAsia@vishay.com, DiodesEurope@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

# Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

*© 2022 VISHAY INTERTECHNOLOGY, INC. ALL RIGHTS RESERVED*