

## Duplex Multimode 62.5/125 LSZH Fiber Optic Cable, 1000 ft. Bulk

MODEL NUMBER: N549-01K



### Highlights

- Bulk 62.5/125 Multimode Duplex Fiber Optic Cable
- Low-Smoke, Zero Halogen (LSZH) jacket
- Zip-Cord Style

### Package Includes

Carton of 1,000ft Duplex 62.5/125 Multimode cable

### Features

- Bulk 62.5/125 Multimode Duplex Fiber Optic Cable
- Low-Smoke, Zero Halogen jacket
- Zip-Cord Style
- Cable marked every meter
- Temp Range: -20C to +70C
- Suitable for Indoor Use
- 7lb Reel

## Specifications

| OVERVIEW                |              |
|-------------------------|--------------|
| UPC Code                | 037332142924 |
| Technology              | Multimode    |
| Optical Mode            | OM1          |
| PHYSICAL                |              |
| Cable Jacket Color      | Orange       |
| Connector Color         | Orange       |
| Cable Jacket Material   | LSZH         |
| Cable Jacket Rating     | OFNR         |
| Clad Diameter (microns) | 125          |



|                                      |                               |
|--------------------------------------|-------------------------------|
| Core Diameter (microns)              | 62.5                          |
| Number of Fibers                     | 2                             |
| Cable Length (ft.)                   | 1000                          |
| Cable Length (m)                     | 304.88                        |
| Cable Length (in.)                   | 12000                         |
| Minimum Bend Radius                  | 20MM (Dynamic); 10MM (Static) |
| Shipping Dimensions (hwd / cm)       | 26.01 x 26.01 x 11.94         |
| Shipping Dimensions (hwd / in.)      | 10.24 x 10.24 x 4.70          |
| Shipping Weight (kg)                 | 2.72                          |
| Shipping Weight (lbs.)               | 6.00                          |
| <b>ENVIRONMENTAL</b>                 |                               |
| Operating Temperature Range          | -4 to 140 °F (-20 to 60 °C)   |
| Storage Temperature Range            | -4 to 140 °F (-20 to 60 °C)   |
| Operating Humidity Range             | 5% to 85% RH, Non-Condensing  |
| Storage Humidity Range               | 35% to 65% RH, Non-Condensing |
| <b>COMMUNICATIONS</b>                |                               |
| Attenuation @ 850NM                  | 3.0dB/Km                      |
| <b>CONNECTIONS</b>                   |                               |
| Side A - Connector 1                 | 62.5 BULK                     |
| Side B - Connector 1                 | 62.5 BULK                     |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                               |
| Push/Pull Tabs                       | No                            |
| Breakout                             | No                            |
| Trunk                                | No                            |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                               |
| Certification & Compliance           | RoHS; REACH                   |
| <b>WARRANTY</b>                      |                               |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty     |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

<https://www.tripplite.com/products/product-certification-agencies>