



Specification:

- Electrical Char
 - Insulation Resistance: 500MΩ min. 500V DC for 1 minute
 - Contact Resistance: 30mΩ max.
 - Rating Current: 1.5A max.
 - ① Rating Voltage: 150V AC
 - Dielectric Voltage: 1000 Vrms at 1MA 60 sec. min.
- Physical Char
 - Housing(Option): For Waving Soldering Process.
 - PBT Glass filled (UL 94V-0) Color: Black
 - Soldering Temperature: 235°C for 5 sec.
 - Spring Wire: 0.35mm thickness Phosphor Bronze
 - 6u" Gold on contact area over 50u" Nickel
 - Temperature Range: -40°C to +85°C
 - Durability: 750 mating cycles min.
- Packing: Tray

RoHS compliant
Unit:mm

Scale	Free						Date	Name	Customer-No.
TOLERANCE						Drawn	21.07.2017	Winnie	
① .XX	±0.25								
.XXX	±0.13	③	Update the dimensions	17.06.2019	Segal	Approved	17.06.2019	Amy	ASSMANN WSW-No.
.XXXX	±0.05	②	Update the dimensions	30.08.2018	Segal				A-2004-2-4-LP/S-R
DIM	TOL	①	Update the tolerance & Rating Voltage	12.07.2018	Segal				Drawing-No.
		①	Drawn	21.07.2016	Winnie				ASS 7322 CO
Angle	+0°30'	Id.	Modification	Date	Name				rev03
								Replace	SHEET



Customer-No.		
ASSMANN WSW-No.		
A-2004-2-4-LP/S-R		
Drawing-No.	ASS 7322 CO	rev03
Replace		SHEET