

## AVR Series 120V 700VA 350W Ultra-Compact Line-Interactive UPS with USB port and Muted Alarm

MODEL NUMBER: AVR700UXRM



### Highlights

- 700VA ultra-compact 120V line interactive UPS
- Audible alarm is muted for full-time silent operation
- Corrects brownouts and overvoltages from 83V to 147V
- 4 UPS battery supported outlets, 4 surge-only outlets
- USB port, TEL/DSL protection, Wall mountable, 98% efficient
- 50% longer runtime than Tripp Lite AVR700U
- NEMA 5-15P input plug and 8 NEMA 5-15R outlets

### Package Includes

- AVR700UXRM UPS System
- USB cable
- Instruction manual

### Description

Tripp Lite's AVR700UXRM Ultra-Compact Line Interactive UPS offers complete power protection for desktop PCs, network workstations and a wide variety of professional and consumer electronic devices. Uninterruptible Power Supply / UPS circuits switch to battery backup mode within milliseconds to keep connected equipment running without interruption or data loss during power failures. Automatic Voltage Regulation / AVR power conditioning maintains smooth, continuous operation of connected equipment during brownouts and overvoltages. Surge-only outlets offer convenient protection for printers and other desktop accessories not requiring battery support. AC and dataline surge suppression prevents connected equipment damage. USB communications port supports built-in power management and auto-shutdown features of Windows and Mac OS X or full featured monitoring and data-saving auto-shutdown options using Tripp Lite's free PowerAlert monitoring software.

### Features

- AVR700UXRM ultra-compact 120V line interactive UPS offers complete AC power protection from blackouts, brownouts and transient surges
- 700VA / 350 watt UPS output capacity
- Audible alarm is completely muted from the factory; Alarm operation can be restored using PowerAlert UPS management software
- Uninterruptible Power Supply / UPS operation maintains battery-derived AC output during blackouts to prevent data loss and system downtime for connected equipment
- Built-in USB port enables data-saving unattended shutdown when used with Tripp Lite's PowerAlert software, available via FREE download from [www.tripplite.com/poweralert](http://www.tripplite.com/poweralert)
- HID-compliant USB port also enables integration with built-in power management and auto shutdown features of Windows and Mac OS X
- Automatic Voltage Regulation / AVR corrects extended brownouts and overvoltages from 83 to 147V, without using battery power
- Large internal battery offers 50% longer runtime than Tripp Lite AVR700U



- 11.8 minutes runtime at 50% load (175 watts)
- Up to 42 minutes runtime for a single desktop computer system consuming 60 watts continuous
- 8 built-in NEMA 5-15R outlets, two with extra wide spacing to accommodate transformer plugs
- 4 UPS battery backup outlets, plus 4 additional surge-only outlets
- Right angle NEMA 5-15P input connection with 6ft / 1.8m line cord
- Network grade AC surge protection is available from all outlets
- Built-in data line surge suppression protects a single dialup or DSL line
- Supports Tripp Lite's Watchdog system service to restore operation to locked equipment through soft reboot of application/OS or hard power off/on reboot of connected equipment, ideal for unattended kiosk applications
- 98% line mode efficiency rating uses less energy and BTU emissions
- Built-in grounding lug
- Hot swappable user battery replacement
- Optional PDUB15 bypass PDU enable hot-swappable UPS replacement with no disruption to connected equipment
- Space saving, ultra-compact housing with support for wall-mount, desktop or floor placement

## Specifications

| OVERVIEW                                 |                                     |
|--|-------------------------------------|
| UPC Code                                 | 037332183682                        |
| UPS Type                                 | Line-Interactive                    |
| INPUT                                    |                                     |
| Rated input current (Maximum Load)       | 12A                                 |
| Nominal Input Voltage(s) Supported       | 120V AC                             |
| UPS Input Connection Type                | 5-15P; Right-Angled                 |
| UPS Input Cord Length (ft.)              | 6                                   |
| UPS Input Cord Length (m)                | 1.8                                 |
| Recommended Electrical Service           | 15A 120V                            |
| Input Phase                              | Single-Phase                        |
| OUTPUT                                   |                                     |
| Output Volt Amp Capacity (VA)            | 700                                 |
| Output Watt Capacity (Watts)             | 350                                 |
| Nominal Voltage Details                  | 115v nominal output in battery mode |
| Frequency Compatibility                  | 60 Hz                               |
| Output Voltage Regulation (Line Mode)    | +8%, -21%                           |
| Output Voltage Regulation (Battery Mode) | +/- 5%                              |



|   |  |
|---|--|
| UPS Output Receptacles (Surge Suppression Only) | 4 UPS outlets, 4 surge-only outlets  |
| Hot-Swap PDU options                            | PDUB15 (2U / 8 5-15R outlets)  |
| Output AC Waveform (AC Mode)                    | Sine wave  |
| Output AC Waveform (Battery Mode)               | PWM sine wave  |
| Nominal Output Voltage(s) Supported             | 110V; 115V; 120V   |
| Output Receptacles                              | (8) 5-15R  |
| Individually Controllable Load Banks            | No   |
| <b>BATTERY</b>                                  |  |
| Battery Type                                    | Valve Regulated Lead Acid (VRLA)   |
| Half Load Runtime (min.)                        | 11.8 min. (175w)   |
| Expandable Runtime                              | No   |
| DC System Voltage (VDC)                         | 12   |
| Battery Recharge Rate (Included Batteries)      | 15.8 hours (10% to 90%)  |
| Battery Access                                  | Battery access door  |
| Internal UPS Replacement Battery Cartridge      | &nbsp;<a class="productLink" href="//www.tripplite.com/UPS-Replacement-Battery-Cartridge-Tripp-Lite-APC-Belkin-Best-Powerware-Liebert-other-UPS~RBC51">RBC51</a>&nbsp; |
| Battery Replacement Description                 | Hot-swappable, user replaceable batteries  |
| <b>VOLTAGE REGULATION</b>                       |  |
| Voltage Regulation Description                  | Automatic voltage regulation (AVR) maintains line power operation with an input voltage range of 83 to 147   |
| Overvoltage Correction                          | Input voltages between 128 and 147 are reduced by 12%  |
| Undervoltage Correction                         | Input voltages between 83 and 104 are boosted by 14%   |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b>    |  |
| Switches  | Combination switch controls on/off power status and self-test operation  |
| Audible Alarm                                   | Alarm is factory muted for silent operation; Audible alarm can be restored to indicate power failure and overload conditions using PowerAlert UPS management software  |
| LED Indicators                                  | 2 LEDs indicate power status and overload/check battery status   |
| <b>SURGE / NOISE SUPPRESSION</b>                |  |
| UPS AC Suppression Joule Rating                 | 420  |
| UPS AC Suppression Response Time                | Instantaneous  |
| UPS Dataline Suppression                        | 1 line TEL/DSL (1 in / 1 out)  |
| EMI / RFI AC Noise Suppression                  | Yes  |



| <b>PHYSICAL</b>   |   |
|---|---|
| Primary Form Factor   | Desktop   |
| Installation Form Factors Supported with Included Accessories | Tower; Ultra-compact desktop; Wallmount   |
| Primary UPS Depth (mm)  | 152   |
| Primary UPS Height (mm)                                       | 89  |
| Primary UPS Width (mm)  | 287   |
| Shipping Dimensions (hwd / cm)                                | 11.68 x 34.04 x 21.84   |
| Shipping Dimensions (hwd / in.)                               | 4.60 x 13.40 x 8.60   |
| Shipping Weight (kg)  | 5.35  |
| Shipping Weight (lbs.)  | 11.80   |
| UPS Housing Material  | ABS   |
| UPS Power Module Dimensions (hwd, cm)                         | 8.89 x 28.70 x 15.24  |
| UPS Power Module Dimensions (hwd, in.)                        | 3.5 x 11.3 x 6  |
| UPS Power Module Weight (kg)                                  | 4.99  |
| UPS Power Module Weight (lbs.)                                | 11  |
| <b>ENVIRONMENTAL</b>  |   |
| Operating Temperature Range                                   | +32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius   |
| Storage Temperature Range                                     | +5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius  |
| Relative Humidity   | 0 to 95%, non-condensing  |
| AC Mode BTU / Hr. (Full Load)                                 | 30  |
| AC Mode Efficiency Rating (100% Load)                         | 98%   |
| <b>COMMUNICATIONS</b>   |   |
| PowerAlert Software   | For local monitoring via the UPS's built-in communication ports, download PowerAlert Local software at <a href="http://www.tripplite.com/poweralert">http://www.tripplite.com/poweralert</a>  |
| Communications Cable  | USB interface cable included  |
| WatchDog Compatibility  | Supports Watchdog application, OS and hard-reboot restart options for remote applications   |
| Network UPS Tools Compatibility                               | NUT compatible. See the full list of Tripp Lite NUT compatible UPS systems at <a href="http://www.networkupstools.org/stable-hcl.html?manufacturer=Tripp+Lite">http://www.networkupstools.org/stable-hcl.html?manufacturer=Tripp Lite</a> |
| Communications Interface                                      | USB (HID enabled)   |
| <b>LINE / BATTERY TRANSFER</b>                                |   |
| Transfer Time   | 1-4 milliseconds  |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|   |   |
|---|---|
| Low Voltage Transfer to Battery Power (Setpoint)            | 83  |
| High Voltage Transfer to Battery Power (Setpoint)           | 147   |
| <b>FEATURES &amp; SPECIFICATIONS</b>                        |   |
| Grounding Lug   | Included  |
| Cold Start (Startup in Battery Mode During a Power Failure) | Cold-start operation supported  |
| High Availability UPS Features                              | Hot swappable batteries   |
| Green Energy-Saving Features                                | Greater than 95% efficiency - GREEN UPS   |
| <b>WARRANTY</b>   |   |
| Product Warranty Period (U.S. & Canada)                     | 3-year limited warranty   |
| Product Warranty Period (Latin America)                     | 3-year limited warranty   |
| Product Warranty Period (International)                     | 2-year limited warranty   |
| Product Warranty Period (Mexico)                            | 3-year limited warranty   |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico)  | \$100,000&nbsp;<a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a>&nbsp; |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>