

2-Port Manual VGA/SVGA Video Switch (3x HD15F)

MODEL NUMBER: B112-002-R





Highlights

- 2-port HD15 VGA/SVGA Push-Button Switch
- Rugged Metal Case

System Requirements

- Computer with an HD15 port
- VGA or SVGA monitor with HD15M cable

Package Includes

 B112-002-R Manual VGA/SVGA 2 Position Switch

Description

Tripp Lite's 2-Port Manual VGA/SVGA Switch is the optimal solution for connecting two computers to one monitor or two monitors to one computer. The 2-Port Manual VGA/SVGA Switch features a fully-shielded rugged metal case with front-panel push-button switching. Interior printed circuit board design allows for crystal clear resolutions up to 1600x1280. It does not require any AC power to operate.

Features

- Connects two computers to one monitor or two monitors to one computer
- Fully-shielded rugged metal case with front-panel push button switch
- Does not require external power, software, or complicated set-up procedures

Specifications

OVERVIEW		
UPC Code	037332014269	
Technology	VGA/SVGA	
VIDEO		
Max Supported Video Resolution	1920 x 1080 @60Hz	
INPUT		
Bus Powered	Yes	
Product Length (in.)	4.41	
Product Length (ft.)	0.37	





Power Consumption (Watts) 0.5			
Material of Construction	POWER		
Material of Construction Aluminum Color Silver Shipping Dimensions (hwd / cm) 11.51 x 2.69 x 8.31 Shipping Dimensions (hwd / in.) 4.53 x 1.06 x 3.27 Shipping Weight (kg) 1.60 Shipping Weight (lbs.) 3.53 Unit Dimensions (hwd / in.) 0.94 x 4.4 x 2.7 Unit Weight (lbs.) 0.33 Unit Weight (kg) 0.15 ENVIRONMENTAL Operating Temperature Range 14 to 131 °F (-10 to 55 °C) Storage Temperature Range 5 to 131 °F (-15 to 55 °C) Relative Humidity 5% to 90% RH, Non-Condensing BTUs 1.7 BTU/Hr COMMUNICATIONS EDID Compatible Yes CONNECTIONS Number of Ports 2 Side A - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 HD15 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Port Selection	Power Consumption (Watts)	0.5	
Color Silver Shipping Dimensions (hwd / cm) 11.51 x 2.69 x 8.31 Shipping Dimensions (hwd / in.) 4.53 x 1.06 x 3.27 Shipping Weight (kg) 1.60 Shipping Weight (kb.) 3.53 Unit Dimensions (hwd / in.) 0.94 x 4.4 x 2.7 Unit Packaging Type Box Unit Weight (bs.) 0.33 Unit Weight (kg) 0.15 ENVIRONMENTAL Operating Temperature Range 14 to 131 °F (-10 to 55 °C) Storage Temperature Range 5 to 131 °F (-15 to 55 °C) Relative Humidity 5% to 90% RH, Non-Condensing BTUs 1.7 BTU/Hr COMMUNICATIONS EDID Compatible Yes CONNECTIONS Side A - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 HD15 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS FEATURES & SPECIFICATIONS Port Selection Pushbutton	PHYSICAL		
Shipping Dimensions (hwd / om)	Material of Construction	Aluminum	
Shipping Dimensions (hwd / in.) 4.53 x 1.06 x 3.27 Shipping Weight (lbs.) 3.53 Unit Dimensions (hwd / in.) 0.94 x 4.4 x 2.7 Unit Packaging Type Box Unit Weight (lbs.) 0.33 Unit Weight (kg) 0.15 ENVIRONMENTAL Operating Temperature Range 14 to 131 °F (-10 to 55 °C) Storage Temperature Range 5 to 131 °F (-15 to 55 °C) Relative Humidity 5% to 90% RH, Non-Condensing BTUs 1.7 BTU/Hr COMMUNICATIONS EDID Compatible Yes CONNECTIONS Number of Ports 2 Side A - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 HD15 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Port Selection Pushbutton	Color	Silver	
Shipping Weight (kg) 1.60 Shipping Weight (lbs.) 3.53 Unit Dimensions (hwd / in.) 0.94 x 4.4 x 2.7 Unit Packaging Type Box Unit Weight (kg) 0.33 Unit Weight (kg) 0.15 ENVIRONMENTAL Operating Temperature Range 14 to 131 °F (-10 to 55 °C) Storage Temperature Range 5 to 131 °F (-15 to 55 °C) Relative Humidity 5% to 90% RH, Non-Condensing BTUs 1.7 BTU/Hr COMMUNICATIONS EDID Compatible Yes CONNECTIONS Number of Ports 2 Side A - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 HD15 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS	Shipping Dimensions (hwd / cm)	11.51 x 2.69 x 8.31	
Shipping Weight (lbs.) 3.53 Unit Dimensions (hwd / in.) 0.94 x 4.4 x 2.7 Unit Packaging Type Box Unit Weight (lbs.) 0.33 Unit Weight (kg) 0.15 ENVIRONMENTAL Operating Temperature Range 14 to 131 °F (-10 to 55 °C) Storage Temperature Range 5 to 131 °F (-15 to 55 °C) Relative Humidity 5% to 90% RH, Non-Condensing BTUs 1.7 BTU/Hr COMMUNICATIONS EDID Compatible Yes CONNECTIONS Number of Ports 2 Side A - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 HD15 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS	Shipping Dimensions (hwd / in.)	4.53 x 1.06 x 3.27	
Unit Dimensions (hwd / in.) 0.94 x 4.4 x 2.7 Unit Packaging Type Box Unit Weight (lbs.) 0.33 Unit Weight (kg) 0.15 ENVIRONMENTAL Operating Temperature Range 14 to 131 °F (·10 to 55 °C) Storage Temperature Range 5 to 131 °F (·15 to 55 °C) Relative Humidity 5% to 90% RH, Non-Condensing BTUs 1.7 BTU/Hr COMMUNICATIONS EDID Compatible Yes CONNECTIONS Number of Ports 2 Side A - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 HD15 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Port Selection Pushbutton	Shipping Weight (kg)	1.60	
Unit Packaging Type Box Unit Weight (lbs.) 0.33 Unit Weight (kg) 0.15 ENVIRONMENTAL Operating Temperature Range 14 to 131 °F (-10 to 55 °C) Storage Temperature Range 5 to 131 °F (-15 to 55 °C) Relative Humidity 5% to 90% RH, Non-Condensing BTUs 1.7 BTU/Hr COMMUNICATIONS EDID Compatible Yes CONNECTIONS Number of Ports 2 Side A - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 HD15 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Pushbutton	Shipping Weight (lbs.)	3.53	
Unit Weight (kg) 0.33 Unit Weight (kg) 0.15 ENVIRONMENTAL Operating Temperature Range 14 to 131 °F (-10 to 55 °C) Storage Temperature Range 5 to 131 °F (-15 to 55 °C) Relative Humidity 5% to 90% RH, Non-Condensing BTUs 1.7 BTU/Hr COMMUNICATIONS EDID Compatible Yes CONNECTIONS Number of Ports 2 Side A - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 HD15 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Pushbutton	Unit Dimensions (hwd / in.)	0.94 x 4.4 x 2.7	
ENVIRONMENTAL Operating Temperature Range 14 to 131 °F (-10 to 55 °C) Storage Temperature Range 5 to 131 °F (-15 to 55 °C) Relative Humidity 5% to 90% RH, Non-Condensing BTUs 1.7 BTU/Hr COMMUNICATIONS EDID Compatible Yes CONNECTIONS Number of Ports 2 Side A - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 HD15 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Pushbutton	Unit Packaging Type	Вох	
ENVIRONMENTAL Operating Temperature Range 14 to 131 °F (-10 to 55 °C) Storage Temperature Range 5 to 131 °F (-15 to 55 °C) Relative Humidity 5% to 90% RH, Non-Condensing BTUs 1.7 BTU/Hr COMMUNICATIONS EDID Compatible Yes CONNECTIONS Number of Ports 2 Side A - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 HD15 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Pushbutton	Unit Weight (lbs.)	0.33	
Operating Temperature Range 14 to 131 °F (-10 to 55 °C) Storage Temperature Range 5 to 131 °F (-15 to 55 °C) Relative Humidity 5% to 90% RH, Non-Condensing BTUs 1.7 BTU/Hr COMMUNICATIONS EDID Compatible Yes CONNECTIONS Number of Ports 2 Side A - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 HD15 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Pushbutton	Unit Weight (kg)	0.15	
Operating Temperature Range 14 to 131 °F (-10 to 55 °C) Storage Temperature Range 5 to 131 °F (-15 to 55 °C) Relative Humidity 5% to 90% RH, Non-Condensing BTUs 1.7 BTU/Hr COMMUNICATIONS EDID Compatible Yes CONNECTIONS Number of Ports 2 Side A - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 HD15 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Pushbutton			
Storage Temperature Range 5 to 131 °F (-15 to 55 °C) Relative Humidity 5% to 90% RH, Non-Condensing BTUS 1.7 BTU/Hr COMMUNICATIONS EDID Compatible Yes CONNECTIONS Number of Ports 2 Side A - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 HD15 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Pushbutton			
Relative Humidity 5% to 90% RH, Non-Condensing BTUS 1.7 BTU/Hr COMMUNICATIONS EDID Compatible Yes CONNECTIONS Number of Ports 2 Side A - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 HD15 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Port Selection Pushbutton			
### DETUS 1.7 BTU/Hr ### COMMUNICATIONS ### EDID Compatible Yes ### CONNECTIONS Number of Ports 2 ### Side A - Connector 1 (2) HD15 (FEMALE) ### Side B - Connector 1 HD15 (FEMALE) ### Connector Plating Nickel ### FEATURES & SPECIFICATIONS Port Selection Pushbutton #### Pushbutton #### Port Selection Pushbutton #### Pushbutton ###### Pushbutton #### Pushbutton Pushbutton ###################################			
COMMUNICATIONS EDID Compatible Yes CONNECTIONS Number of Ports 2 Side A - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 HD15 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Port Selection Pushbutton		-	
CONNECTIONS Number of Ports 2 Side A - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 HD15 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Port Selection Pushbutton	BTUs	1.7 BTU/Hr	
CONNECTIONS Number of Ports 2 Side A - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 HD15 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Port Selection Pushbutton	COMMUNICATIONS		
Number of Ports 2 Side A - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 HD15 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Port Selection Pushbutton	EDID Compatible	Yes	
Number of Ports 2 Side A - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 HD15 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Port Selection Pushbutton	CONNECTIONS		
Side A - Connector 1 (2) HD15 (FEMALE) Side B - Connector 1 HD15 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Port Selection Pushbutton	Number of Ports	2	
Side B - Connector 1 HD15 (FEMALE) Connector Plating Nickel FEATURES & SPECIFICATIONS Port Selection Pushbutton			
Connector Plating Nickel FEATURES & SPECIFICATIONS Port Selection Pushbutton			
FEATURES & SPECIFICATIONS Port Selection Pushbutton			
Port Selection Pushbutton			
Driver Pequired I No			
Diliver required 140	Driver Required	No No	
STANDARDS & COMPLIANCE	STANDARDS & COMPLIANCE		
Certification & Compliance CE (Europe); RoHS; REACH; FCC (USA)	Certification & Compliance	CE (Europe); RoHS; REACH; FCC (USA)	



Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies