

# Mini DisplayPort Cable, 4K 60Hz (M/M), White, 10 ft. (3.05 m)

### MODEL NUMBER: P584-010



### Features

- 10-ft. (3.05 m) Mini Displayport to Mini Displayport cable
- Supports Displayport v1.2
- Connect your PC or Mac with Mini Displayport (or Thunderbolt) to a Mini Displayport Monitor or TV
- Supports HDCP Pass-Through
- Compatible with all Mini Displayport computers and peripheralsSupports Ultra High Definition (UHD) 4K x 2K video resolutions up to 3840 x 2160 @ 60Hz, including 1080p

## **Specifications**

OVERVIEW		
	007000474005	
UPC Code	037332174635	
Product Type	Passive	
Technology	DisplayPort	
VIDEO		
Max Supported Video Resolution	3840 x 2160 @ 60Hz	
Max Supported Color Depth	24-bit True Color	
HDR Support	No	
3D Video Supported	Yes	
Chroma Sub Sampling	4:2:0; 4:2:2	
Signal Transmission	Bidirectional	

### Highlights

- 10-ft. (3.05 m) Mini Displayport to Mini Displayport Cable
- Connect your PC or Mac with Mini Displayport (or Thunderbolt) to a Mini Displayport Monitor or TV
- Supports Displayport v1.2
- Supports Ultra High Definition (UHD) 4K x 2K video resolutions up to 3840 x 2160 @ 60Hz, including 1080p

#### Package Includes

• 10-ft. (3.05 m) Mini Displayport to Mini Displayport cable



	te
Cable Jacket ColorWhiteCable Jacket MaterialPVCCable Jacket RatingVW-1Cable Outer Diameter (OD)4.8MMWire Gauge (AWG)32Cable Length (ft.)10Cable Length (m)3.05Ferrite CoreNoMinimum Bend Radius48mmShipping Dimensions (hwd / cm)22.86Shipping Weight (kg)0.05	te
Cable Jacket MaterialPVCCable Jacket RatingVW-1Cable Outer Diameter (OD)4.8MMWire Gauge (AWG)32Cable Length (ft.)10Cable Length (m)3.05Ferrite CoreNoMinimum Bend Radius48mmShipping Dimensions (hwd / cm)22.86Shipping Weight (kg)0.05	2 1 1 1 1 1 1 1 1 1 1 1 1 1
Cable Jacket RatingVW-1Cable Outer Diameter (OD)4.8MMWire Gauge (AWG)32Cable Length (ft.)10Cable Length (m)3.05Ferrite CoreNoMinimum Bend Radius48mmShipping Dimensions (hwd / cm)22.86Shipping Dimensions (hwd / in.)9.00 xShipping Weight (kg)0.05	1 /M //////////////////////////////////
Cable Outer Diameter (OD)4.8MMWire Gauge (AWG)32Cable Length (ft.)10Cable Length (m)3.05Ferrite CoreNoMinimum Bend Radius48mmShipping Dimensions (hwd / cm)22.86Shipping Dimensions (hwd / in.)9.00 xShipping Weight (kg)0.05	/M m 6 x 17.78 x 1.27 x 7.00 x 0.50
Wire Gauge (AWG)32Cable Length (ft.)10Cable Length (m)3.05Ferrite CoreNoMinimum Bend Radius48mmShipping Dimensions (hwd / cm)22.86Shipping Dimensions (hwd / in.)9.00 xShipping Weight (kg)0.05	im i6 x 17.78 x 1.27 i x 7.00 x 0.50
Cable Length (ft.)10Cable Length (m)3.05Ferrite CoreNoMinimum Bend Radius48mmShipping Dimensions (hwd / cm)22.86Shipping Dimensions (hwd / in.)9.00 xShipping Weight (kg)0.05	m 16 x 17.78 x 1.27 0 x 7.00 x 0.50
Cable Length (m)3.05Ferrite CoreNoMinimum Bend Radius48mmShipping Dimensions (hwd / cm)22.86Shipping Dimensions (hwd / in.)9.00 xShipping Weight (kg)0.05	m 16 x 17.78 x 1.27 0 x 7.00 x 0.50
Ferrite CoreNoMinimum Bend Radius48mmShipping Dimensions (hwd / cm)22.86Shipping Dimensions (hwd / in.)9.00 xShipping Weight (kg)0.05	m 16 x 17.78 x 1.27 0 x 7.00 x 0.50
Minimum Bend Radius       48mm         Shipping Dimensions (hwd / cm)       22.86         Shipping Dimensions (hwd / in.)       9.00 x         Shipping Weight (kg)       0.05	6 x 17.78 x 1.27 x 7.00 x 0.50
Shipping Dimensions (hwd / cm)       22.86         Shipping Dimensions (hwd / in.)       9.00 x         Shipping Weight (kg)       0.05	6 x 17.78 x 1.27 x 7.00 x 0.50
Shipping Dimensions (hwd / in.)9.00 xShipping Weight (kg)0.05	x 7.00 x 0.50
Shipping Weight (kg) 0.05	
Shipping Weight (lbs.) 0.12	
0.12	
ENVIRONMENTAL	
Operating Temperature Range 32 to 2	o 113 F (0 to 45 C)
Storage Temperature Range -40 to	to 158 F (-40 to 70 C)
Operating Humidity Range 10% to	to 85% RH, Non-Condensing
Storage Humidity Range 5% to	to 90% RH, Non-Condensing
COMMUNICATIONS	
EDID Compatible Yes	
Consumer Electronics Control (CEC) Supported No	
CONNECTIONS	
Side A - Connector 1 MINI E	I DISPLAYPORT (MALE)
Side B - Connector 1 MINI E	I DISPLAYPORT (MALE)
Connector Plating Gold	3
Contact Plating Gold	
Connector Style Straig	ight
Latching or Gripping Connector No	
FEATURES & SPECIFICATIONS	
Displayport Specification 1.2	



HDCP Specification	2.2	
EMI/RFI Line Noise Protection	No	
MST Support	Yes	
IP68 Rated	No	
Antibacterial	No	
Armored Cable	No	
Ethernet Support	No	
STANDARDS & COMPLIANCE		
Certification & Compliance	RoHS; REACH; WEEE	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies