

# Component Video with Stereo Audio over Cat5/Cat6 Extender Kit, In-Line Transmitter and Receiver, Up to 700 ft. (213 m)

MODEL NUMBER: B136-101





# **Highlights**

- Comes with both local and remote units
- Extends a 1080i (60Hz)
   Component Video and Stereo
   Audio signal up to 300-ft. (91.44
   m) when using 24Awg, Solid
   Wire UTP cable (Tripp Lite
   N202-Series); or, up to 400-ft.
   (121.92 m) when using Zero-Skew UTP cable (Tripp Lite
   P524-01K)
- No External Power required

# Package Includes

- B136-101 Component Video + Stereo Audio Extender Kit (2pc)
- Owner's Manual

#### Description

Tripp Lite's B136-101 Component Video + Stereo Audio extender kit comes with both local and remote units, allowing you to place a TV, Projector, etc, up to 700-ft. (213.36 m) away from the source. A 1080i (60Hz) Component Video and Stereo Audio signal can be extended up to 300-ft. (91.44 m) when using 24Awg, Solid Wire UTP cable (Tripp Lite N202-Series); or, up to 400-ft. (121.92 m) when using Zero-Skew UTP cable (Tripp Lite P524-01K). A 480p (60Hz) Component Video and Stereo Audio signal can be extended up to 500-ft. (152.4 m) when using 24Awg, Solid Wire UTP cable (Tripp Lite N202-Series); or, up to 700-ft. (213.36 m) when using Zero-Skew UTP cable (Tripp Lite P524-01K). Built-in RCA connectors plug directly into the source and display, without the need for additional cables....no power required. Please note: Left and Right channel audio are combined on the transmitter end for one complete sound.

# **Features**

- · Comes with both local and remote units
- Built-in RCA connectors plug directly into the source and display, without the need for additional cables
- Extends a 1080i (60Hz) Component Video and Stereo Audio signal up to 300-ft. (91.44 m) when using 24Awg, Solid Wire UTP cable (Tripp Lite N202-Series); or, up to 400-ft. (121.92 m) when using Zero-Skew UTP cable (Tripp Lite P524-01K)
- No external power required

# **Specifications**

OVERVIEW		
UPC Code	037332155467	
Product Type	Extender Kit	
Technology	Component; Stereo Audio; Cat5/5e; Cat6	



VIDEO		
Max Supported Video Resolution	1920x1080 (1080i @ 60Hz)	
Max 720P Range (ft)	400	
Max 1280 x 720 (720p) Range (ft)	328	
Transmitter Video Input	Component (RCA)	
Transmitter - Number of Video Outputs	1	
Receiver/Transceiver Video Output	Component (RCA)	
Receiver - Number of Video Outputs	1	
Recommended Cabling	P524-01K	
HDR Support	No	
3D Video Supported	Yes	
Maximum Signal Range (ft)	700	
Maximum Signal Range (m)	213	
AUDIO		
Audio Input	RCA (x2) Stereo	
Audio Output	RCA (x2) Stereo	
Audio Specification	Stereo Audio	
INPUT		
Bus Powered	No	
POWER		
Power Over Cable (PoC) Support	No	
PHYSICAL		
Color	Black	
Number of Displays	1	
Form Factor/Mounting Options	Pigtail	
Receiver Unit Dimensions (hwd / in.)	2.42 x 1.95 x 1.0	
Receiver Unit Weight (lbs.)	0.1	
Shipping Dimensions (hwd / cm)	5.08 x 12.19 x 13.46	
Shipping Dimensions (hwd / in.)	2.00 x 4.80 x 5.30	
Shipping Weight (kg)	0.18	
Shipping Weight (lbs.)	0.40	



Transmitter Unit Dimensions (hwd / in.)	2.42 x 1.95 x 1.0	
Transmitter Unit Weight (lbs.)	0.1	
Unit Packaging Type	Вох	
Housing	Plastic	
ENVIRONMENTAL		
Operating Temperature Range	32 to 104°F (0 to 40°C)	
Storage Temperature Range	14 to 158 F (-10 to 70 C)	
Relative Humidity	0% to 85%, Non-Condensing	
COMMUNICATIONS		
Max 1024 x 768 Range (ft)	400	
Max 480P Range (ft)	700	
Max 1440 x 900 Range (ft)	400	
Max 1080i Range (ft)	400	
Max 480i Range (ft)	700	
Max 640 x 480 Range (ft)	700	
Max 800 x 600 Range (ft)	450	
Max 1600 x 1200 Range (ft)	350	
EDID Compatible	No	
IR Remote Extension Support	No	
RS-232 Serial Extension Support	No	
Consumer Electronics Control (CEC) Supported	No	
USB Extension Support	No	
CONNECTIONS		
Number of Ports	1	
Side A - Connector 1	(5) RCA (MALE)	
Side A - Connector 2	RJ45 (FEMALE)	
Side B - Connector 1	(5) RCA (MALE)	
Side B - Connector 2	RJ45 (FEMALE)	
Connector Plating	Nickel	
FEATURES & SPECIFICATIONS		
Driver Required	No	
10/100 Ethernet Extension Support	No	



**Tripp Lite**1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

Built-In Equalizer	No	
STANDARDS & COMPLIANCE		
CTANDARDO & COMI EIAROE		
Certification & Compliance	CE (Europe); RoHS; REACH; FCC (USA)	
WARRANTY		
Product Warranty Period (Worldwide)	1-year limited warranty	

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>