

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

# Isobar 2-Outlet Low-Profile Professional Audio/Video Power Conditioning Center, 10 ft. and 18 in. Cords, 5100 Joules

MODEL NUMBER: AV2FP









Premium protection for A/V home theater components, including HDTVs and stereo receivers, against dangerous power surges, spikes and line noise. Recommended for professional-grade home theater installations.

### Description

Premium protection for your expensive home theater equipment, the AV2FP Isobar® 2-Outlet Low-Profile Professional Audio/Video Power Conditioning Center features a network-grade surge protection rating of 5100 joules to defend your sensitive electronics against even the strongest surges and spikes. In fact, Tripp Lite will repair or replace any connected equipment damaged by surges up to \$100,000 for life (valid in the U.S., Canada and Puerto Rico only).

The AV2FP features two NEMA 5-15R outlets, one for your flat-panel HDTV and one for an accessory, such as an audio receiver or Blu-ray<sup>™</sup> player. This unit's unique protection system prevents disruptive line noise from causing A/V distortion, computer lock-ups, data errors and similar problems. Large toroidal chokes, ferrite rod-core inductors, HF/VHF capacitors and multiple layers of metal oxide varistors remove EMI/RFI interference and prevent system crashes, reboots and performance problems. Coaxial and RJ45 jacks also protect your incoming cable, satellite and Ethernet signals.

Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the AV2FP protects all three, covering two protection modes: full normal mode (H-N) and common mode (N-G/H-G). An integrated 12A circuit breaker protects all outlets and shuts down connected equipment in the event of an overload. An on/off switch provides one-touch control over both outlets. Diagnostic LEDs confirm power, protection and ground status at a glance. Detachable 10-foot and 18-inch AC power cords include right-angle NEMA 5-15P plugs, allowing furniture to be placed flush against the wall.

#### **Features**

**Network-Grade 5100-Joule Surge Protection for Your Home Theater Electronics**Protects your A/V components against even the strongest surges and spikesFull normal mode (H-N) and common mode (N-G/H-G) line surge suppression2 NEMA 5-15R surge-protected outlets for HDTV and accessoryBidirectional coaxial and RJ45 jacks protect cable, satellite and Ethernet signals

**Premium Safety Features**On/off switch provides one-touch control over connected equipmentAutomatic shutoff permanently cuts power to outlets if protection circuit is incapacitated, preventing equipment damage and indicating replacement is requiredDiagnostic LEDs confirm power, protection and ground status at a glanceAudible alarm alerts you to damaged internal protection circuitryConforms to current UL 1449 and 962A safety standards

Fits Effortlessly Into Your SetupDetachable 10 ft. (3.1 m) and 18 in. AC power cords provide flexibility in

#### **Highlights**

- 2 NEMA 5-15R surge-protected outlets for HDTV and accessory
- Network-grade 5100-joule surge protection rating
- Durable metal housing mounts out of sight behind HDTV
- 12A resettable circuit breaker prevents dangerous overloads
- Detachable 10 ft. and 18 in. power cords with right-angle plugs

#### **Package Includes**

- AV2FP Isobar 2-Outlet Low-Profile Professional Audio/Video Power Conditioning Center
- Detachable power cord with C-13 connector, 10 ft.
- Detachable power cord with C-13 connector, 18 in.
- Built-in mounting brackets
- Owner's manual



placementSpace-saving right-angle NEMA 5-15P plugs allows furniture and equipment to move flush against the wallBuilt-in mounting brackets allow for secure installation on wall behind HDTVMetal housing designed for long life

**Backed by Tripp Lite's Ultimate Lifetime Insurance**\$100,000 Ultimate Lifetime Insurance covers any connected components damaged by power surge (U.S., Canada and Puerto Rico only)

## **Specifications**

OVERVIEW		
UPC Code	037332125071	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	120V (110-125V)	
Input Cord Gauge Type	14 gauge; SJT	
Input Cord Gauge (AWG)	14	
Voltage Compatibility (VAC)	120	
Maximum Surge Amps	255000	
Input Plug Type	NEMA 5-15P	
Input Cord Details	SJT	
Input Cord Length (ft.)	10	
Right-Angle Plug	Yes	
Input Cord Length (m)	3.05	
Integrated Cord Clip	No	
ОИТРИТ		
Frequency Compatibility	50 / 60 Hz	
Output (Watts)	1440	
Output Receptacles	(2) 5-15R	
Circuit Breaker (amps)	12	
Overload Protection	12-amp circuit breaker	
Right-Angle Outlets	No	
USER INTERFACE, ALERTS & CONTROLS		
Diagnostic LED(s)	Yes	
Switches	Circuit breaker	
Audible Alarm	Audible alarm	



Diagnostic LED Details	3 (protection, grounding, power)	
SURGE / NOISE SUPPRESSION		
AC Suppression Joule Rating	5100	
AC Suppression Response Time	NM = instantaneous CM = < 1 ns	
Safe Thermal Fusing	yes	
UL1449 Let Through Rating	330V - UL verified	
EMI / RFI Filtering	Yes	
Automatic Shut-Off	Yes	
DATALINE SURGE SUPPRESSION		
Cable (Coax) Protection	Yes	
Network (Ethernet) Protection	Yes	
Telephone/DSL Protection	No	
PHYSICAL		
Material of Construction	Metal	
Power Cord Color	Black	
Housing Color	Black	
Included Mounting Accessories	Built-in mounting brackets	
Mounting Holes or Slots	No	
Slot or Hole Mount Measurement (Center to Center)	220.49 mm	
Outlets Measurement (Center to Center)	45mm	
Receptacle Color	Black	
Shipping Dimensions (hwd / cm)	24.89 x 6.10 x 25.40	
Shipping Dimensions (hwd / in.)	9.80 x 2.40 x 10.00	
Shipping Weight (kg)	1.45	
Shipping Weight (lbs.)	3.20	
Unit Dimensions (hwd / in.)	1.50 x 4.50 x 9.25	
Unit Weight (lbs.)	1.65	
Unit Weight (kg)	0.75	
COMMUNICATIONS		
Network Compatibility	100 Mbps (Fast Ethernet)	
FEATURES & SPECIFICATIONS		



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Antimicrobial	No	
Rotatable Outlets	No	
STANDARDS & COMPLIANCE		
Certification & Compliance	RoHS; UL 1449; UL 962A; UL 1778; CAN/CSA-C22.2 No. 107.3 (Canada)	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$100,000 <a class="insuranceLink" href="//www.tripplite.com/support/insurance-policy">Ultimate Lifetime Insurance</a>	

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>