

1U Rack-Mount Console with 19-in. LCD

MODEL NUMBER: **B021-000-19**



Description

Tripp Lite's B021-000-19 1U Rackmount Console features an integrated 19" LCD display, full 88-key keyboard and touch pad, all in a 1U rackmountable housing. The included KVM cable kit allows for connection to a PS/2 computer or KVM, and a PS/2 to USB adapter is included, which can be used to connect to a USB computer or KVM. The unit features a USB 2.0 pass-through port for connection of a USB peripheral, such as a flash drive, CAC card reader, etc.. Your peripheral device connects to the USB type A port on the front of the unit, and your computer connects to the USB type A port on the back of the unit using a Tripp Lite UR020-Series type A M/M cable. Constructed of heavy-duty steel housing. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Features

- Features 19-inch LCD TFT active-matrix, color panel
- Space saving 1U 19-inch, rackmount drawer design
- Features a USB 2.0 pass-through port for connection of a USB peripheral, such as a flash drive, CAC card reader, etc.
- Supports resolutions of up to 1366 X 768
- Included PS/2 to USB adapter allows for connection to a USB computer or KVM
- Sleep mode when the monitor cover is closed
- Input 120/240 VAC
- Constructed of heavy-duty steel housing
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Highlights

- Control an entire network in just 1U of rack space; includes keyboard, 19" LCD screen and touch pad
- Features a USB 2.0 pass-through port for connection of a USB peripheral, such as a flash drive, CAC card reader, etc.
- Connects to a PS/2 or USB server or KVM switch
- Supports resolutions up to 1366 X 768
- Rackmountable in 19" system rack (1U), from 27" to 42" deep
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

System Requirements

- Computer or KVM with a VGA monitor port and USB or PS/2 keyboard/mouse ports

Package Includes

- 1U Rackmount Console w/ 19" LCD
- 1- KVM Cable Kit (HD15M to HD15M + 2 PS2 Male)
- 1-PS/2 to USB Adapter
- 1- C13 to 5-15P Power Cord
- 1- User Manual
- Mounting Hardware

Specifications

| OVERVIEW | |
|------------|----------------|
| UPC Code | 037332152657 |
| Technology | PS/2; VGA/SVGA |



| VIDEO | |
|--|---|
| Max Supported Video Resolution | 1366 x 768 @ 60Hz |
| INPUT | |
| Voltage Compatibility (VAC) | 100; 110; 120; 127; 200; 208; 220; 230; 240 |
| Input Frequency | 50/60Hz |
| Input Current | 120V (1.2A) / 230V (0.7A) |
| Power Input Receptacle | IEC-320-C14 |
| POWER | |
| Power Consumption (Watts) | 30 |
| Power Consumption Detail | (Line Mode) 30W / (Standby Mode) 5W |
| USER INTERFACE, ALERTS & CONTROLS | |
| LED Indicators | Green (CAPS LOCK, SCROLL LOCK, NUM LOCK) |
| PHYSICAL | |
| Material of Construction | Steel (Steel, ElectroGalvanized, Cold Rolled, Coil) |
| Color | Black |
| Rackmountable | Yes |
| Shipping Dimensions (hwd / cm) | 15.24 x 60.20 x 82.55 |
| Shipping Dimensions (hwd / in.) | 6.00 x 23.70 x 32.50 |
| Shipping Weight (kg) | 17.55 |
| Shipping Weight (lbs.) | 38.70 |
| Unit Dimensions (hwd / in.) | 1.7 x 17.7 x 28.4 |
| Unit Packaging Type | Box |
| Unit Weight (lbs.) | 31 |
| Unit Weight (kg) | 14.06 |
| ENVIRONMENTAL | |
| Operating Temperature Range | 32 to 104 F (0 to 40 C) |
| Storage Temperature Range | -4 to 140 F (-20 to 60 C) |
| Relative Humidity | 20% to 90% RH, Non-Condensing |
| BTUs | (Line Mode) 102 BTU/Hr / (Standby Mode) 17.1 BTU/Hr |
| COMMUNICATIONS | |
| IP Remote Access | No |



| CONNECTIONS | |
|---------------------------------------|--|
| Number of Ports | 1 |
| PC/Server Connections | VGA; USB; PS/2 |
| Side A - Connector 1 | USB A (FEMALE) |
| Side A - Connector 2 | HD15 (FEMALE) |
| Side B - Connector 1 | USB A (FEMALE) |
| Computer Keyboard and Mouse Interface | PS/2; USB |
| Computer Monitor Interface | VGA |
| FEATURES & SPECIFICATIONS | |
| Number of Users | 1 |
| NIAP-Certified Secure | No |
| USB Specification | USB 2.0 (up to 480 Mbps) |
| Driver Required | No |
| Cat5 KVM Switch | No |
| BUILT-IN CONSOLE | |
| Console Screen Size (inches) | 19 |
| Console Screen Aspect Ratio | 16:9 |
| STANDARDS & COMPLIANCE | |
| Certification & Compliance | UL 60950-1; CAN/CSA C22.2; FCC Part 15 Class A (USA); CE (Europe); CAN/CSA-C22.2 No. 60950-1 (Canada); RoHS; REACH |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 1-year limited warranty |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>