

# Gigabit Multimode Fiber to Ethernet Media Converter, 10/100/1000 to 1000BaseLX SC, 2km, 1310nm

MODEL NUMBER: N785-001-SC



### Highlights

- Converts UTP Gigabit Ethernet to Fiber Optic
- Cost-effective solution for extending network distance up to 2 km
- Automatic MDI/MDI-X configuration
- Half or Full Duplex Operation
- Auto-Senses 10 / 100 / 1000
- Supports Multimode 50/125 cable up to 2km or 62.5/125 cable up to 400M

### Package Includes

- N785-001-SC 10/100/1000 to 1000BaseLX Gigabit Multimode Media Converter
- External Power Supply with NEMA 1-15P Plug ( Input: 110-265V, 50/60Hz, 0.2A; Output: 5V, 2A )
- Owners Manual

An economical way to extend the distance up to 2 Km (1.2 Miles) of remote Gigabit network nodes by converting Cat5/6 UTP Ethernet to Fiber Optic while still maintaining the existing infrastructure.

### Description

Tripp Lite's N785-001-SC 10/100/1000 Gigabit Multimode Media Converter is an economical way to extend the distance ( up to 2Km ) of network nodes by converting Cat5/6 UTP cables to Fiber Optic. With advanced features such as selectable half or full duplex operation on the fiber port, 1300 nm wavelength, automatic MDI/MDI-X configuration and link fault pass-through, the N785-001-SC supplies superior signal quality and gives you ultimate network control. The N785-001-SC is compatible with both 62.5/125 and 50/125 multimode fiber cable.

### Features

- Connect 10/100/1000 UTP Ethernet to 1000BaseLX Fiber Ethernet
- Auto MDI/MDI-X
- UTP port auto-senses network speed
- Fiber lengths up to 2Km
- 6 LED Function lights
- Uses 62.5/125 or 50/125 Multimode cable
- 3.75"L x 2.75"W x 1"H
- Wavelength: 1300nm
- RoHS Compliant
- Supports Multimode 50/125 cable up to 2km or 62.5/125 cable up to 400M

## Specifications

OVERVIEW	
UPC Code	037332153777



Product Type	Fiber to Ethernet
Technology	Cat5/5e; Cat6; Multimode
Mode Type	Multimode
<b>DISPLAY</b>	
Accessories (Included)	External Power Supply (Input: 100-240V, 50/60Hz, 0.5A; Output: 5V/2A)
<b>NETWORK</b>	
Network Ports	RJ45 (FEMALE); SC (FEMALE)
<b>POWER</b>	
AC Adapter	Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 1.2A
External Power Supply Input Specs (V / Hz / A)	100-240V, 50/60Hz, 1.2A
External Power Supply Output Specs (V / A)	5V, 2A
External Power Supply Cord Length (ft.)	4.53
External Power Supply Cord Length (m.)	1.38
DC Barrel Plug	OD: 5.5 x 2.5 x 11mm, Positive Pin, Negative Sleeve
External Power Supply Plug(s)	NEMA 1-15P North America
<b>USER INTERFACE, ALERTS &amp; CONTROLS</b>	
LED Indicators	PWR (Power LED), L/A (Fiber port connection indicator), SD (Fiber signal indicator), SPD (Network speed), TP-L/A (Copper port connection indicator), FDX/COL (Full Duplex/Half Duplex)
<b>PHYSICAL</b>	
Color	Black
Power Cord Color	Black
Shipping Dimensions (hwd / cm)	23.50 x 5.51 x 12.50
Shipping Dimensions (hwd / in.)	9.25 x 2.17 x 4.92
Shipping Weight (kg)	0.43
Shipping Weight (lbs.)	0.94
Unit Dimensions (hwd / in.)	1.00 x 3.70 x 2.8
Unit Packaging Type	Box
Unit Weight (lbs.)	1.00
Unit Weight (kg)	0.45
Housing	Metal



<b>ENVIRONMENTAL</b>	
Operating Temperature Range	32 to 140 F (0 to 60 C)
Storage Temperature Range	-4 to 158 F (-20 to 70 C)
Relative Humidity	5 to 90% RH, Non-Condensing
<b>COMMUNICATIONS</b>	
Network Compatibility	10 Mbps; 100 Mbps (Fast Ethernet); 1 Gbps (Gigabit)
Wavelength	1310nm
Network Speed Details	10 Mbps; 100 Mbps; 1000 Mbps
Transmission Distance	2 km
IEEE Standards Supported	802.3; 802.3u; 802.3ab; 802.3z
Wavelength Division Multiplexing (WDM)	Yes
<b>CONNECTIONS</b>	
Side A - Connector 1	RJ45 (FEMALE)
Side B - Connector 1	SC DUPLEX (FEMALE)
<b>FEATURES &amp; SPECIFICATIONS</b>	
Data Transfer Rate	1 Gbps; 10 Mbps; 100 Mbps
Auto MDIX Support	Yes
DIN Mountable	No
Mounting Accessory Included	No
Working Mode	Full/Half Duplex
Optical Port	SC
<b>STANDARDS &amp; COMPLIANCE</b>	
Certifications	CE, FCC, RoHS
External Power Supply Certifications	CE; FCC; cUL; WEEE
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	2-year limited warranty

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>