

## 6-Port USB 3.0 SuperSpeed Charging Hub - 2x USB 3.0, 4x USB 2.0, 1 charging port

MODEL NUMBER: U360-412



Charge an iPad or tablet via a USB hub.

### Description

Tripp Lite's U360-412 USB 3.0 Charging Hub plugs into a computer's USB 3.0 port and provides two USB 3.0 SuperSpeed peripheral ports, four USB 2.0 High-Speed peripheral ports, and one charging port for charging tablets such as an iPad. Two of the USB 2.0 ports have convenient top plugging, for thumb drive access. Dedicated 2AMP charging port supplies the extra amperage needed to charge tablets, which most USB hubs do not include. Plug-and-Play... no software or drivers required. Automatically switches to the highest speed supported by the peripheral. Windows (compatible with Windows 10) and Mac compatible.

### Features

- USB 3.0 ports support 5Gbps transfer speeds when plugged into a USB 3.0 computer and peripheral
- USB 2.0 ports support High-Speed 480Mbps speeds
- Charging port provides 5V, 2A for tablet ( iPad ) full battery charging
- USB 3.0 ports support up to 900mA per port
- USB 2.0 ports support up to 500mA per port
- The included external power supply provides 4A of power, to be shared between the hub ports (up to 2A for iPad charging port, up to 900mA per USB 3.0 port, up to 500mA per USB 2.0 port)
- Top mount ports for Thumb Drive connections  
Plug-and-Play
- No software or drivers required
- Windows (compatible with Windows 10) and Mac compatible
- Overcurrent protection
- LED power indicator light

## Specifications

### OVERVIEW

### Highlights

- USB 3.0 Hub with two USB 3.0 SuperSpeed ports and four USB 2.0 High-Speed ports
- One dedicated port for Tablet charging ( 5V, 2A )
- USB 3.0 ports support up to 900mA per port
- USB 2.0 ports support up to 500mA per port
- Plug-and-Play - no software or drivers required

### System Requirements

- USB 3.0 or 2.0 computer
- USB 3.0 or 2.0 peripherals

### Package Includes

- USB 7-port Hub
- USB 3.0 A-B cable, 3ft
- External Power Supply with NEMA 1-15P Plug (Input: 100-240V, 50/60Hz, 0.9A; Output: 5V, 4A)



UPC Code	037332173560
Product Type	Hub
AC Adapter	Input: 100-240V, 50/60Hz, 0.9A; Output: 5V, 4A
Host Connector	USB A (MALE)
<b>VIDEO</b>	
Number of Monitors Supported	0
Extended Mode	No
Mirror Mode	No
<b>DATA</b>	
Data Ports	(6) USB A (FEMALE)
Data Ports Details	(2) USB-A - USB 3.2 Gen 1 (5 Gbps); (4) USB-A - USB 2.0
<b>INPUT</b>	
Voltage Compatibility (VAC)	100; 110; 120; 125; 127; 200; 208; 220; 230; 240
External Power Supply Plug(s)	NEMA 1-15P North America
<b>POWER</b>	
External Power Supply Input Specs (V / Hz / A)	100-240V / 50/60Hz / 0.6A
External Power Supply Output Specs (V / A)	5V / 4A
External Power Supply Cord Length (ft.)	5
External Power Supply Cord Length (m.)	1.5
DC Barrel Plug	OD: 3.5 x 1.35 x 10mm, Positive Pin, Negative Sleeve
External Power Supply Certifications	FCC; UL; cUL; RoHS
<b>USER INTERFACE, ALERTS &amp; CONTROLS</b>	
LED Indicators	Green - Power
<b>CHARGING</b>	
Charging Ports Details	Dedicated charging port
Charging Ports	USB-A: 2A
Charging Ports / Amps	(1) 2A
<b>PHYSICAL</b>	
Color	Black



Material of Construction	ABS
Shipping Dimensions (hwd / cm)	7.62 x 11.68 x 13.97
Shipping Dimensions (hwd / in.)	3.00 x 4.60 x 5.50
Shipping Weight (kg)	0.41
Shipping Weight (lbs.)	0.90
Unit Dimensions (hwd / in.)	1 x 4 x 2.25
Unit Packaging Type	Box
Unit Weight (lbs.)	0.18
Unit Weight (kg)	0.08
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	-4 to 158 °F (-20 to 70 °C)
Storage Temperature Range	-4 to 185 °F (-20 to 85 °C)
Relative Humidity	20% to 80% RH, Non-Condensing
BTUs	5.5 BTU/Hr
Power Consumption (Watts)	1.6
Power Provided to Connected Device(s)	5V 0.5A (2.5W) Output (USB-A 2.0), 5V 0.9A (4.5W) Output (USB-A 3.0), 5V 2A (10W) Output (USB 2A Charger)
<b>CONNECTIONS</b>	
Ports	7
Side A - Connector 1	USB 3.0 A (MALE)
Side B - Connector 1	(2) USB 3.0 A (FEMALE)
Side B - Connector 2	(5) USB A (FEMALE)
Connector Plating	Nickel
<b>FEATURES &amp; SPECIFICATIONS</b>	
USB Specification	USB 2.0 (up to 480 Mbps); USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)
Driver Required	No
<b>STANDARDS &amp; COMPLIANCE</b>	
Certifications	CE, FCC, RoHS, REACH
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	3-year limited warranty



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>