

Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

# Smart 108 - 8-Port Cat5 KVM Switch for Rack Environments

### MODEL NUMBER: 0SU22081









#### Description

Save Space and Money

#### From SOHO to Enterprise

#### Features

- 8 Ports
- BIOS level access
- Multilayer security
- Multi-platform PS/2 and USB support
- Extends distance between servers and switch up to 30 meters/100 feet over Cat5e cabling
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

## Highlights

- 8 Ports
- BIOS level access
- Multilayer security
- Multi-platform PS/2 and USB support
- Extends distance between servers and switch up to 30 meters/100 feet over Cat5e cabling
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

#### **System Requirements**

#### **Operating System**

 DOS, Windows, LINUX, UNIX, MAC and all other major operating systems

#### Console

- VGA Monitor
- PS/2 Keyboard and Mouse

#### Resolution

• Supports video resolutions up to 1600 x 1200 @ 75Hz

#### Package Includes

- Smart 108
- RS232 Cable
- Power Cord
- Rackmount Hardware
- Owner's Manual

# **Specifications**

| OVERVIEW |              |
|----------|--------------|
| UPC Code | 654518209488 |
| Console  | No           |
| PHYSICAL |              |



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

| [                                      |                            |
|--|----------------------------|
| Color                                  | Black                      |
| Shipping Dimensions (hwd / cm)         | 11.43 x 16.51 x 26.67      |
| Shipping Dimensions (hwd / in.)        | 4.50 x 6.50 x 10.50        |
| Shipping Weight (kg)                   | 1.41                       |
| Shipping Weight (lbs.)                 | 3.10                       |
| Unit Dimensions (hwd / in.)            | 1.6 x 8.5 x 4.8            |
| Unit Dimensions (hwd / cm)             | 4.15 x 21.5 x 12.2         |
| Unit Weight (Ibs.)                     | 2.2                        |
| Unit Weight (kg)                       | 1.00                       |
| ENVIRONMENTAL                          |                            |
| Storage Temperature Range              | -40 to 70 C / -40 to 158 F |
| Relative Humidity                      | 80% Non-Condensing         |
| Operating Temperature                  | 0 to 40 C / 32 to 104 F    |
| COMMUNICATIONS                         |                            |
| Port Control                           | Push Buttons, Hotkeys, OSD |
| IP Remote Access                       | Yes                        |
| CONNECTIONS                            |                            |
| Number of Ports                        | 8                          |
| PC/Server Connections                  | VGA; USB; PS/2             |
| FEATURES & SPECIFICATIONS              |                            |
| Number of Users                        | 1                          |
| NIAP-Certified Secure                  | No                         |
| Cat5 KVM Switch                        | Yes                        |
| WARRANTY                               |                            |
| Product Warranty Period<br>(Worldwide) | 3-year limited warranty    |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies