

**Tripp Lite** 

1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234

## Smart 232 32-Port Multi-User Cat5 KVM Switch for Rack Environments

MODEL NUMBER: 0SU22091









#### Description

Multi-user access and control of many computers/servers

Straightforward set up

Space saving devices that eliminate cable clutter

From server rooms to data centers

#### **Features**

- 32 Ports with 2 simultaneous KVM Users
- BIOS level access
- USB keyboard and mouse console
- Multi-platform PS/2 and USB support
- Extends distance between servers and switch up to 30 meters/100 feet
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule Purchases

# **Specifications**

## **Highlights**

- 32 Ports with 2 simultaneous **KVM Users**
- BIOS level access
- USB keyboard and mouse console
- Multi-platform PS/2 and USB support
- Extends distance between servers and switch up to 30 meters/100 feet
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule Purchases

## **System Requirements**

Operating System

• Windows, Novell, Linux, **SUN Solaris** 

#### Resolution

• Supports video resolutions up to 1600 x 1200 @ 85Hz

## Package Includes

- Smart 232
- Power Cord
- RS232 Cable
- · Rackmount Hardware
- Owner's Manual



| OVERVIEW                               |                            |
|--|----------------------------|
| UPC Code                               | 654518209921               |
| PHYSICAL                               |                            |
| Color                                  | Black                      |
| Shipping Dimensions (hwd / cm)         | 13.97 x 33.27 x 50.29      |
| Shipping Dimensions (hwd / in.)        | 5.50 x 13.10 x 19.80       |
| Shipping Weight (kg)                   | 3.67                       |
| Shipping Weight (lbs.)                 | 8.10                       |
| Unit Dimensions (hwd / in.)            | 1.7 x 17 x 10.6            |
| Unit Dimensions (hwd / cm)             | 4.4 x 43.1 x 27            |
| Unit Weight (lbs.)                     | 5.1                        |
| Unit Weight (kg)                       | 2.31                       |
| ENVIRONMENTAL                          |                            |
| Storage Temperature Range              | -40 to 70 C / -40 to 158 F |
| Relative Humidity                      | 80% Non-Condensing         |
| Operating Temperature                  | 0 to 40 C / 32 to 104 F    |
| COMMUNICATIONS                         |                            |
| Port Control                           | Hotkeys, OSD               |
| IP Remote Access                       | Yes                        |
| CONNECTIONS                            |                            |
| Number of Ports                        | 32                         |
| Computer/Server Ports                  | 32                         |
| PC/Server Connections                  | VGA; USB; PS/2             |
| FEATURES & SPECIFICATIONS              |                            |
| Number of Users                        | 2                          |
| NIAP-Certified Secure                  | No                         |
| Cat5 KVM Switch                        | Yes                        |
| WARRANTY                               |                            |
| Product Warranty Period<br>(Worldwide) | 3-year limited warranty    |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>