2M RANGE UHF RFID ON METAL



ART915X050503OP-IC

 $\begin{array}{c|c} 5.0 \text{ x } 5.0 \text{ x } 3.0 \text{ mm} \\ \hline \text{Pb} & \text{RoHS/RoHS II Compliant} \\ & \text{MSL} = 2 \end{array}$

FEATURES

- Long 2.0m read range
- Compatible with any material, including metal
- Passive tag requires no battery or power supply
- Suitable for applications in harsh conditions
- Wide operating temperature $-40 \sim +85$
- Compliant with ISO 18000-6C/EPC Class1 Gen2
- $902 \sim 928$ MHz operation
- Utilizing Alien H3 RFID chipset
- Compact 5.0 x 5.0 mm footprint
- 3.0 mm height ideal for low profile requirements

APPLICATIONS

- Local asset tracking for industrial, heavy equipment, and data center applications
- Medical equipment
- Aviation equipment and tools
- Military devices and vehicles
- Oil and gas industry
- Trains and other transportation assets

STANDARD SPECIFICATIONS

Parameters	Min.	Тур.	Max.	Units	Note
Range of Receiving Frequency		866 - 868 902 - 928		MHz	
Frequency of Lowest Return Loss		915±5		MHz	(Based on 150 x 150 mm GND Plane)
Polarization		Linear			
IC Protocol	ISO 18000-6C/EPC Class1 Gen2				
Memory	96 EPC			Bits	
	512 User			Bits	
	64 TID			Bits	
IC Type	Alien H3				
Reading Range		2.0		m	On metal, 4W EIRP
		1.0		m	In metal, 4W EIRP
Operating Temperature	-40		+85	°C	
Application Temperature	-40		+150	°C	
IP rate		IP68	•		



1501 Hidden Creek Lane Spicewood TX 78751 Phone: 949-546-8000 | Fax: 949-546-8001 For terms and conditions of sales visit: www.abracon.com **REVISED:**

02/26/2019

ABRACON IS ISO9001-2015 CERTIFIED

2M RANGE UHF RFID ON METAL




ART915X050503OP-IC


5.0 x 5.0 x 3.0 mm




OUTLINE DRAWING | UNIT: mm

TOLERANCES ARE ± 0.2 MM, UNLESS OTHERWISE SPECIFIED









L	W	H	
5 TYP	5 TYP	3 TYP	

PACKAGING

1000 PCS/REEL, 10 REELS/CARTON







1501 Hidden Creek Lane Spicewood TX 78751 Phone: 949-546-8000 | Fax: 949-546-8001 For terms and conditions of sales visit: www.abracon.com **REVISED:**

02/26/2019

ABRACON IS ISO9001-2015 CERTIFIED

2M RANGE UHF RFID ON METAL



ART915X050503OP-IC

5.0 x 5.0 x 3.0 mm
RoHS/RoHS II Compliant
MSI = 2

NOTE

- 1. The parts are manufactured in accordance with this specification. If other conditions and specifications which are required for this specification, please contact ABRACON for more information.
- 2. ABRACON will supply the parts in accordance with this specification unless we receive a written request to modify prior to an order placement.
- 3. In no case shall ABRACON be liable for any product failure from in appropriate handling or operation of the item beyond the scope of this specification.
- 4. When changing your production process, please notify ABRACON immediately.
- 5. ABRACON's products are COTS Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. ABRACON's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from ABRACON LLC is required. Please contact ABRACON LLC for more information.
- 6. All specifications and marking will be subject to change without notice.



1501 Hidden Creek Lane Spicewood TX 78751 Phone: 949-546-8000 | Fax: 949-546-8001 For terms and conditions of sales visit: www.abracon.com **REVISED:**

02/26/2019