



PART NUMBER	DESCRIPTION
L-0700CC0900-0090XC	COVER
L-0700SA0900-0090XF	FRAME







A (6 : 1)



RoHS Compliant

THIRD ANGLE PROJECTION

DO NOT SCALE DRAWING

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ORBEL CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ORBEL CORPORATION IS PROHIBITED.

DIMENSIONS ARE IN INCHES [MILLIMETERS]
TOLERANCES:
FRACTIONAL ±
ANGULAR: MACH ± 3 Degrees
TWO PLACE DECIMAL ± .015 [.381]
THREE PLACE DECIMAL ± .010 [.254]

MATERIAL:
.010" [.254] NICKEL SILVER, 1/2 HARD

FINISH:

WEIGHT: 0.024oz. [0.677g]

	NAME	DATE
DRAWN	TNC	2/12/2015
CHECKED		
ENG APPR.		
MFG APPR.		
Q.A.		

COMMENTS:

ORBEL
ENGINEERED SOLUTIONS


SIZE	DWG NO.	REV.
A	L-0700SA0900-0090XF	01

SCALE: 2:1 | CAGE CODE: 57DU2 | SHEET 1 OF 1

HOW TO ORDER BOARD LEVEL SHIELDING

The chart below is an easy-to-use reference on how Orbel BLS part numbers are created and used to order standard and custom board level shielding. Custom configurations that fall outside of our standard shield styles are also available.

Sample Part Number (Snap-Shield Bullzeye™): B-0750TB1125-0250XF - TPS



Board Shield Style

G = EZ-Shield **Guardian**™
M = Snap-Shield **Micro**™
B = Snap-Shield **Bullzeye**™
L = Snap-Shield **LaZerLock**™
S = Snap-Shield **SmartFORM**™
T = Snap-Shield **TRU-View**™
V = **Vault**-Shield™
H = Snap-Shield **HEMI**™

Frame Width

Mounting Style

TA = Through-Hole (0.250" spacing)
TB = Through-Hole (0.500" spacing)
TC = Through-Hole (1.000" spacing)
SA = Surface-Mount w/Alignment Pins
SB = Surface-Mount w/Castellations
SC = Surface-Mount w/No Pins

Frame Length

Material Options

No Code = Nickel Silver (standard)
TPS = Tin-Plated Steel
TPB = Tin-Plated Brass
TPC = Tin-Plated Copper

Shield Code

F = Shield Frame
C = Shield Cover
A = Assembled
P = Unassembled Pair


Material Thickness

X = 0.010" (Standard)
Y = 0.015"
Z = 0.008"


Frame Height

STANDARD FEATURES


PIN OPTIONS




Alignment Pin




Through-Hole Pin



Through-Hole Pin with Standoff




Castellation Edge




Straight Edge, No Pin


CORNER OPTIONS



Tight Corner




Louvered Corner



Welded Corner

ADDITIONAL OPTIONS



Trace Notch



Pick Target



Ventilation Holes



Logo or Part Number Marking

PERFORMANCE SPECS

Material Options

- Nickel Silver
- TPS: Tin-Plated Steel
- TPB: Tin-Plated Brass
- TPC: Tin-Plated Copper

Co-Planarity

- Smaller Shields: 0.004"
- Larger Shields: 0.008"

Material Thicknesses

- 0.010" (Standard)
- 0.008"
- 0.012"
- 0.015"

RoHS-Compliant

- Yes

Shielding Effectiveness

- Up to 60dB

Other material options include beryllium copper, phosphorus bronze, and stainless steel. Additional plating finishes available upon request.

All technical data presented herein is accurate to the best of our knowledge based on Orbel's most up-to-date testing information and material specs. This information is not presented as a warranty or guarantee and is not intended to be all-inclusive as to conditions of use.