

Specification Sheet

Part Number: CTM310C2



KR/CTM series are designed to provide stability to wire bundles. These mounts can accommodate miniature, intermediate, or standard cross-section cable ties.

Each mount is secured with a single screw.

Cable Tie Anchor Mount, .86" x .61", .2" Hole Dia, .31" Max Tie Width, PA66, White, 100/pkg

Article Number 151-30605

Type CTM3

Color White (WH)

Quantity Per bag

Product Description Designed specifically for holding heavier cable bundles these mounting bases can be used in many industries from agriculture to truck manufacture. They offer a very secure fixing and can be used with a wide variety of heavy duty cable ties up to 8.3 mm width.

Short Description Cable Tie Anchor Mount, .86" x .61", .2" Hole Dia, .31" Max Tie Width, PA66, White, 100/pkg

Global Part Name CTM3-PA66-WH

| | |
|--|--------------------------|
| Length L (Imperial) | 0.86 |
| Length L (Metric) | 21.8 |
| Fixation Method | Screw Mounting and Rivet |
| Width W (Imperial) | 0.61 |
| Width W (Metric) | 15.5 |
| Cable Ties | T18 - T120 |
| Height H (Imperial) | .37 |
| Height H (Metric) | 9.40 |
| Cable Tie Width Max (Imperial) | 0.31 |
| Cable Tie Width Max (Metric) | 7.9 |
| Mounting Hole Diameter D (Imperial) | 0.2 |
| Mounting Hole Diameter D (Metric) | 5.1 mm |
| Mounting Hole Diameter D Max (Metric) | 5.1 |
| Material | Polyamide 6.6 (PA66) |

| | |
|--------------------------------------|--|
| Material Shortcut | PA66 |
| Flammability | UL 94 V-2 |
| Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Certification/Specification | UL ANSI/UL 1565 UL ANSI/UL 62275 UL ANSI/UL 746B |
| UL Recognized (US) | Yes |
| UL Recognized (US and Canada) | Yes |
| Package Quantity (Imperial) | 100 |
| Package Quantity (Metric) | 100 |
| Customs Number | 3926909988 |