# Specification Sheet

Part Number: GT.50X6MP2V2



UL 94 V-2 flame rated material allows use in air handling spaces. Features quick release for repetitive access to cable and wire.

Can be opened and closed numerous times without failure.

Adjustable so one size can accommodate multiple bundle diameters.

Grip Tie, UL94V0-2 Flame Rated, .5" x 6.0", PA6/PP, Maroon, 10/pkg

| | |
|---|---|
| **Article Number** | 854-44352 |
| **Type** | GT.50X6 |
| **Color** | Red Brown (RDBN) |
| **Quantity Per** | bag |
| **Product Description** | HellermannTyton offers UL 94 V-2 flame rated Grip Ties for use in air handling spaces. Grip Ties are UL Listed in accordance with the National Electric Code regulations. Grip Ties are low-profile, one-piece fastening devices. Constructed of a hook and loop design, laminated back to back, the Grip Tie features quick release for repetitive access to cable and wire. Grip Ties are available in a variety of colors and are versatile enough for applications ranging from network installations to bundling power cords. |
| **Short Description** | Grip Tie, UL94V0-2 Flame Rated, .5" x 6.0", PA6/PP, Maroon, 10/pkg |

| | |
|---|---|
| **Global Part Name** | GT.50X6 |
| **Minimum Tensile Strength (Imperial)** | 40.0 |
| **Minimum Tensile Strength (Metric)** | 177.93 |
| **Length L (Imperial)** | 6.0 |
| **Length L (Metric)** | 152.4 |
| **Width W (Imperial)** | 0.5 |
| **Width W (Metric)** | 12.7 |
| **Bundle Diameter Max (Imperial)** | 1.0 |
| **Bundle Diameter Max (Metric)** | 25.4 |
| **Material** | Polyamide 6 (PA6) Polypropylene (PP) |
| **Material Shortcut** | PA6 PP |
| **UL Recognized (US)** | Yes |
| **UL Recognized (US and Canada)** | Yes |

| | |
|---|---|
| **Package Quantity (Imperial)** | 10 |
| **Package Quantity (Metric)** | 10 |
| **Customs Number** | 3926909988 |

© 2022 HellermannTyton. All Rights Reserved.