

Specification Sheet

Part Number: 596-00613

Made with UV-stable inks and materials for durability and weather resistance.

Reflective properties to meet applicable NEC code requirements for reflective identification.

Supplied with an aggressive adhesive to ensure long life.

CAUTION: SOLAR ELECTRIC SYSTEM CONNECTED

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Solar Label, Reflective, CAUTION SOLAR ELECTRIC SYSTEM CONNECTED, 6.5" x 1.0", VL, Yellow, 50/roll

Article Number 596-00613

Type CSESC

Color Yellow (YE)

Quantity Per roll

Product Description

HellermannTyton Pre-Printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code (NEC) and the International Fire Code (IFC) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

| Short Description | Solar Label, Reflective, CAUTION SOLAR ELECTRIC SYSTEM CONNECTED, 6.5" x 1.0", VL, Yellow, 50/roll |
|------------------------|--|
| Global Part Name | CSESC-505/281-YE |
| Technical Description | Pre-Printed Solar Label, Reflective, "SOLAR ELECTRIC SYSTEM CONNECTED", 6.5" X 1.0", Yellow |
| Local Order Number 2 | Cross Reference = 10 per pack: 596-00672; Spanish version 50 per roll: 596-00821 |
| Width W (Imperial) | 6.5 |
| Width W (Metric) | 165.1 |
| Thickness T (Imperial) | 0.0025 |
| Thickness T (Metric) | 64.0 |
| Height H (Imperial) | 1.0 |
| Height H (Metric) | 25.4 |
| | |
| Material | Type 505/281, UV-stabilized reflective vinyl with clear polyester laminate (505/281) |
| Material Shortcut | 505/281 |

Acrylic

Adhesive

Halogen Free No **Adhesive Operating Temperature** -40°F to +302°F (-40°C to +150°C) **Operating Temperature** -40°F to +174°F (-40°C to +79°C) Reach Compliant (Article 33) Yes **ROHS Compliant** Yes Certification/Specification IFC 2012 ANSI Standard Z535.4 NEC2014 UL 969 NEC2011 Warranty (US) Yes **UL Recognized (US)** Yes **Package Quantity (Imperial)** 50 **Package Quantity (Metric)** 50 **Customs Number** 3919905060 Labels per Column 1

Labels per Row

1