




Scotchlok™ Terminals

MVU18-156DM, MVU14-156DM,
MVU10-156DM

Male Snap Plug, Vinyl Insulated, Butted Seam



Data Sheet

| Product Number | Wire Range (AWG) | Mating Snap Diameter S | L | Barrel Length | Barrel I.D. | Maximum Insulation Diameter |
|----------------|------------------|------------------------|------|---------------|-------------|-----------------------------|
| MVU18-156DM | 22-18 | 0.156 | 0.85 | 0.19 | 0.070 | 0.145 |
| MVU14-156DM | 16-14 | 0.156 | 0.85 | 0.19 | 0.090 | 0.170 |
| MVU10-156DM | 12-10 | 0.156 | 0.94 | 0.22 | 0.155 | 0.250 |



UNDERWRITERS
LABORATORIES
STANDARD NO. UL 486A
3M FILE NO. E23438



CANADIAN STANDARDS
ASSOCIATION
STANDARD NO. 22.2
NO. 0, 65
3M FILE NO. LR22190

Installation Information

⚠ WARNING

Turn power off before installing or removing terminal. All electrical work should be done according to appropriate electrical codes.

UL Listed and CSA Certified for use on stranded copper (AWG) wire only.

Strip away the end 3/8 inch of wire insulation.

Make the crimp in the proper station of a recommended 3M crimp tool: TH-440, TH-450 (scissor style), or TR-490 (ratchet style) hand tools.

Specifications

| | |
|-------------------------|--|
| Wire Size: | See Table Above |
| Barrel Seam: | Butted |
| Maximum Voltage Rating: | 600 V Building Wire 1000 V Signs or Fixtures (Luminaires) |
| Maximum Operating Temp: | 221°F (105°C) |
| Maximum Current: | Same as Wire |
| Insulator Material: | Vinyl |
| Terminal Material: | Brass |
| Plating: | Tin |



● Barrel Crimp (Electrical)

Engineering Specification

Crimp-Type Snap Plug Connectors shall, electrically and mechanically, connect permanently to a prestripped end of a stranded copper wire; and have a round tongue portion for mating to a Snap Receptacle in a separable, reusable manner.

The connector line shall offer tongue variations (0.156" and 0.180" diameter) and barrel variations in wire (AWG) size (22-18, 16-14, 12-10) and construction (vinyl insulated, nylon insulated with insulation grip). The separable connectors shall have regulatory agency coverage (UL Listed, CSA Certification).

The vinyl insulated 0.156" Male Snap Plug shall be tinned 0.030" thick copper, with a tongue tapered from 0.156" diameter and a butted seam barrel covered by a molded vinyl funnel entry sleeve, color coded and sized for a specified (AWG) wire range (22-18, 16-14, 12-10).

Insulated separable connectors shall be UL Listed and CSA Certified for 600 V building wire: 1000 V signs or lighting fixtures (luminaires) and temperature rated 221 °F (105 °C) maximum.

The separable connector formed by the paired Male Snap Plug and Female Snap Receptacle may require a suitable strain relief to prevent accidental separation.

3M and Scotchlok are trademarks of 3M.



is a trademark of Underwriters Laboratories.



is a trademark of Canadian Standards Association.

IMPORTANT NOTICE

Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use.

Warranty; Limited Remedy; Limited Liability. This product will be free from defects in material and manufacture as of the date of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.**

3M

Electrical Products Division

6801 River Place Blvd.
Austin, TX 78726-9000
<http://www.3M.com/elpd>

Litho in USA.
© 3M 2002 78-8126-0393-0-A