



Screw Terminal Blocks

1000/ 3

terminal block, 3 pole, insulating material: PA 6, cross-section rating: 6.0 mm², pin spacing: 12.00 mm, fixing: screw, voltage rating: 500 V, current rating: 41.0 A



Order Info

reference number (ref. no.)	125203
PU	400
EAN	4028012100873

Type

type	terminal block
number of poles	3 pole
clamping units per pole	1
colour	natural
cross-section rating	6.0 mm ²
connection type	screw

Technical Data

voltage rating	500 V
current rating	41.0 A
insulating material	PA 6
contact material	brass
core cross-section min.	0.5 mm ²
core cross-section max.	10.0 mm ²
flammability rating	V-2
min. Umgebungstemperatur	-40 °C
max. Ambient Temperature Operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	7.5-8.0 mm
Assembly Contact Screw	0.8x4.0 / ⚙ 0.8 Nm
pin spacing	12.00 mm
fixing	screw

Approvals

acc. to EN 60998	Download PDF
acc. to UL	Download PDF
acc. to CSA	Download PDF

Accessories

1000 BZ/ 3	191403
ABK 406/ 3	193303
ZEL 110	196420