



REPRESENTATIVE IMAGE

Product: [11700A](#)

DataTuff® Cat 5e, 4 Bonded-Pr #24 Sol BC, PO Ins, PVC Jkt, PVC Jkt, MSHA CMR

[Request Sample](#)

Product Description

Industrial Ethernet Cat 5e, 4 Bonded-Pair 24AWG (Solid) Bare Copper, PO Insulation, PVC Inner Jacket, PVC Outer Jacket, MSHA CMR

Technical Specifications

Product Overview

| | |
|------------------------|--|
| Suitable Applications: | outdoor, mining, exposure to abrasion, harsh environment, IIoT, factory or process automation, IP cameras and devices, data communication, etc. |
| Patent: | This product has one or more applicable patents. More information on patents can be found at https://www.belden.com/resources/patents . |

Construction Details

Conductor

| Size | Stranding | Material | Number of Pairs |
|--------|-----------|------------------|-----------------|
| 24 AWG | Solid | BC - Bare Copper | 4 |

Insulation

| Material | Nom. Insulation Diameter | Color Code |
|-----------------|--------------------------|--|
| PO - Polyolefin | 0.035 in (0.89 mm) | White/Blue Stripe & Blue, White/Orange Stripe & Orange, White/Green Stripe & Green, White/Brown Stripe & Brown |

| | |
|--------------|-----|
| Bonded-Pair: | Yes |
|--------------|-----|

Inner Jacket

| Material | Nom. Diameter | Ripcord |
|--------------------------|--------------------|---------|
| PVC - Polyvinyl Chloride | 0.202 in (5.13 mm) | Yes |

Outer Jacket

| Material | Nom. Diameter | Ripcord |
|--------------------------|--------------------|---------|
| PVC - Polyvinyl Chloride | 0.285 in (7.24 mm) | Yes |

| | |
|-----------------------------------|--------------------|
| Overall Cable Diameter (Nominal): | 0.285 in (7.24 mm) |
|-----------------------------------|--------------------|

Electrical Characteristics

Electricals

| Max. Conductor DCR | Max. Capacitance Unbalance |
|--------------------|----------------------------|
| 93.8 Ohm/km | 66 pF/ft |

Delay

| Max. Delay | Max. Delay Skew | Nom. Velocity of Prop. |
|-------------|-----------------|------------------------|
| 510 ns/100m | 25 ns/100m | 70% |

High Frequency

| Frequency [MHz] | Max. Insertion Loss (Attenuation) | Min. NEXT [dB] | Min. PSNEXT [dB] | Min. ACR [dB] | Min. PSACR [dB] | Min. ACRF (ELFEXT) [dB] | Min. PSACRF (PSELFEXT) [dB] | Min. RL (Return Loss) [dB] | Max./Min. Input Impedance (unFitted) | Max./Min. Fitted Impedance |
|-----------------|-----------------------------------|----------------|------------------|---------------|-----------------|-------------------------|-----------------------------|----------------------------|--------------------------------------|----------------------------|
| 1 | 2.0 dB/100m | 65.3 | 65.3 | 63.3 | 63.3 | 63.8 | 60.8 | 20 | 100 ± 12 Ohm | 105 ± 10 Ohm |
| 4 | 4.0 dB/100m | 56.3 | 56.3 | 52.3 | 52.3 | 51.7 | 48.7 | 23 | 100 ± 12 Ohm | 100 ± 10 Ohm |
| 8 | 5.7 dB/100m | 51.8 | 51.8 | 46.1 | 46.1 | 45.7 | 42.7 | 24.5 | 100 ± 12 Ohm | 100 ± 10 Ohm |
| 10 | 6.4 dB/100m | 50.3 | 50.3 | 43.9 | 43.9 | 43.8 | 40.8 | 25 | 100 ± 12 Ohm | 100 ± 10 Ohm |

| | | | | | | | | | | |
|-------|--------------|------|------|------|------|------|------|------|--------------|--------------|
| 16 | 8.1 dB/100m | 47.3 | 47.3 | 39.1 | 39.1 | 39.7 | 36.7 | 25 | 100 ± 12 Ohm | 100 ± 10 Ohm |
| 20 | 9.2 dB/100m | 45.8 | 45.8 | 35.2 | 35.2 | 37.7 | 34.7 | 25 | 100 ± 12 Ohm | 100 ± 10 Ohm |
| 25 | 10.3 dB/100m | 44.3 | 44.3 | 34.1 | 34.1 | 35.8 | 32.8 | 24.3 | 100 ± 15 Ohm | 100 ± 10 Ohm |
| 31.25 | 11.6 dB/100m | 42.9 | 42.9 | 31.3 | 31.3 | 33.9 | 30.9 | 23.6 | 100 ± 15 Ohm | 100 ± 10 Ohm |
| 62.5 | 16.8 dB/100m | 38.4 | 38.4 | 21.6 | 21.6 | 27.8 | 24.8 | 21.5 | 100 ± 15 Ohm | 100 ± 10 Ohm |
| 100 | 21.7 dB/100m | 35.3 | 35.3 | 17.1 | 17.1 | 23.8 | 20.8 | 20.1 | 100 ± 15 Ohm | |
| 155 | 27.7 dB/100m | 32.5 | 32.5 | 4.7 | 4.7 | 19.9 | 16.9 | 19 | 100 ± 18 Ohm | |
| 200 | 32 dB/100m | 30.8 | 30.8 | 3 | 3 | 17.7 | 14.7 | 19 | 100 ± 20 Ohm | |
| 250 | 36.4 dB/100m | 29.3 | 29.3 | 0 | 0 | 15.8 | 12.8 | 18 | 100 ± 20 Ohm | |
| 300 | 40.5 dB/100m | 28.2 | 28.2 | 0 | 0 | 14.2 | 11.2 | 18 | 100 ± 20 Ohm | |
| 310 | 41.3 dB/100m | 27.9 | 27.9 | | | 13.9 | 10.9 | 18 | 100 ± 20 Ohm | |
| 350 | 44.3 dB/100m | 27.2 | 27.2 | | | 12.9 | 9.9 | 17 | 100 ± 22 Ohm | |

Voltage

| UL Voltage Rating |
|----------------------------------|
| 300 V (CMR), 300 V (CMX-Outdoor) |

Mechanical Characteristics

Temperature

| UL Temperature | Operating | Installation | Storage |
|----------------|----------------|----------------|----------------|
| 60°C | -40°C To +75°C | -25°C To +75°C | -40°C To +85°C |

Bend Radius

Stationary Min.

0.29 in (7.4 mm)

| | |
|--------------------|----------------|
| Max. Pull Tension: | 40 lbs (18 kg) |
| Bulk Cable Weight: | 35 lbs/1000ft |

Standards and Compliance

| | |
|---------------------------------------|---|
| Environmental Suitability: | Indoor/Outdoor, Indoor, Outdoor, Sunlight Resistance, Oil Resistance |
| Flammability / Reaction to Fire: | UL 1666 Riser, FT4, FT4, IEC 60332-1-2 |
| CPR Compliance: | CPR Euroclass: Eca |
| NEC / UL Compliance: | Article 800, CMR;CMX-Outdoor |
| CEC / C(UL) Compliance: | CMR |
| IEEE Compliance: | IEEE 802.3bt Type 1, Type 2, Type 3 |
| Data Category: | Category 5e |
| TIA/EIA Compliance: | ANSI/TIA-568.2-D Category 5e |
| Third Party Performance Verification: | Category 5e |
| European Directive Compliance: | EU Directive 2015/863/EU (RoHS 2 amendment), REACH, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE), REACH: 2020-01-16 |
| APAC Compliance: | China RoHS II (GB/T 26572-2011) |
| Other Standard Compliance(s): | P-07-KA060005-MSHA, Ethernet/IP™ Compliant |

Product Notes

| | |
|--------|--|
| Notes: | US Patent #'s 5, 606, 151; 5, 734, 126. EtherNet/IP is a trademark of ControlNet International, Ltd. under license by Open DeviceNet Vendor Association, Inc. Operating temperatures are subject to length de-rating. Cable passes -40C Cold Bend per UL 1581. Outer Shield Separator Material: Polyester. |
|--------|--|

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.388 Revision Date: 12-15-2021 |
|----------------------|--|

Variants

| Item # | Color | Putup Type | Length | UPC |
|----------------|-------|------------|----------|--------------|
| 11700A 0101000 | Black | Reel | 1,000 ft | 612825107705 |
| 11700A 0103000 | Black | Reel | 3,000 ft | 612825107712 |
| 11700A 0061000 | Blue | Reel | 1,000 ft | 612825107682 |
| 11700A 0081000 | Gray | Reel | 1,000 ft | 612825107699 |
| 11700A 0021000 | Red | Reel | 1,000 ft | 612825107675 |
| 11700A 1NH1000 | Teal | Reel | 1,000 ft | 612825107729 |

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.