HellermannTyton

Specification Sheet

Part Number: TSR2I-25-1


Tamper resistant covers with hidden latch provide security while allowing quick entry for cable maintenance.

PVC construction is lightweight, durable and more affordable than metallic raceway systems.

Flexible hinge is designed to reduce stress cracking and discoloration from repeated opening and closing.

Systems and fittings are available in white, office white and ivory to coordinate with a variety of décor.

Fittings incorporate a minimum 1" bend radius to meet TIA/EIA 568-B and 569-A standards.



Elbow Cover, 1-1/4", 1" Bend Radius, PVC, Ivory, 1/bag

Article Number	250-02256

Type TSR2-25-1

Color Ivory (IV)

Quantity Per bag

Product Description

HellermannTyton surface raceway systems are the ideal solution for routing communication and power cables. No need to break into existing walls - raceway systems are designed to route cable along wall surfaces. Made of a PVC material, components are durable and affordable; and the one-piece construction and adhesive tape backing make positioning and mounting easy. HellermannTyton offers a low voltage TSR system and a power rated TSRP system that are available in three different diameters to accommodate different cable and wire bundle and conduit sizes. Both systems include a complete line of fittings and junction boxes that allow for clean and professional installations. TSR surface raceway systems can be used to route a variety of communication cable, including high speed UTP and fiber optic cable.

Short Description Elbow Cover, 1-1/4", 1" Bend Radius, PVC, Ivory, 1/bag

Global Part Name TSR2-25-1-PVC-BGE

Material Polyvinylchloride (PVC)

Material Shortcut PVC

Flammability UL 94 V-0

Halogen Free No

Operating Temperature +122°F (+50°C)

Reach Compliant (Article 33) No

ROHS Compliant Yes

Customs Number	3925	900000				
© 2022 HellermannTyton. All Right	ts Reserved. Contact Us	RoHS/WEEE Cor	mpliance	Disclaimer	Terms and Conditi	ions

10

Package Quantity (Metric)