

## Specification Sheet

Part Number: TAG53L-788



White polyester has a smooth surface, allowing for the highest resolution and print contrast.

The acrylic-based adhesive bonds to a wide variety of substrates and resists abrasion.

LaserTags are sheet fed for easy loading and fast printing.

Laser Tag Label, 8.5" x 11", 1 Per Sheet, PET, White, 250/pkg

**Article Number** 594-53788

**Type** TAG53L

**Color** White (WH)

**Quantity Per** pack

**Product Description** HellermannTyton white polyester labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's 788 material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, general purpose marking.

**Short Description** Laser Tag Label, 8.5" x 11", 1 Per Sheet, PET, White, 250/pkg

<b>Global Part Name</b>	TAG53L-788-WH
<b>Width W (Imperial)</b>	8.5
<b>Width W (Metric)</b>	215.9
<b>Bundle Diameter Min (Imperial)</b>	0.24
<b>Bundle Diameter Min (Metric)</b>	6.10
<b>Thickness T (Metric)</b>	64.0
<b>Height H (Imperial)</b>	10.81
<b>Height H (Metric)</b>	274.60
<b>Material</b>	Type 788, Polyethylene Terephthalate (788)
<b>Material Shortcut</b>	788
<b>Adhesive</b>	Acrylic
<b>Halogen Free</b>	No
<b>Adhesive Operating Temperature</b>	-40°F to +199°F (-40°C to +93°C)
<b>Operating Temperature</b>	-40°F to +199°F (-40°C to +93°C)

**Reach Compliant (Article 33)** Yes

**ROHS Compliant** Yes

**Package Quantity (Imperial)** 250

**Package Quantity (Metric)** 250

**Customs Number** 3919905060

**Labels per Column** 1

**Labels per Row** 1

© 2022 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)