## **HellermannTyton**

## **Specification Sheet**

AWARNING

**INVERTER OUTPUT** 

**CONNECTION. DO** 

NOT RELOCATE THIS OVERCURRENT DEVICE.

Part Number: 596-00846

Pre-Printed Vinyl Solar Labels are made with UV-stable inks and materials for durability and weather resistance. Supplied with an aggressive adhesive to ensure long life.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Pre-printed labels offer significant time and cost savings over high priced plastic engraved phenolic placards and lead time purchased markers.

**Article Number** 596-00846 IOCOD14 Туре Color Orange (OG) **Quantity Per** roll **Product Description** HellermannTyton pre-printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description	Solar Label, WARNING INVERTER OUTPUTOVERCURRENT DEVICE, 2.0" x 1.25", VL, Orange, 50/roll
Global Part Name	IOCOD14-443/281-OG
Technical Description	Pre-Printed Solar Label," WARNING - INVERTER OUTPUT CONNECTION", 2.0" X 1.25", Orange
Length L (Imperial)	1.25
Length L (Metric)	31.75
Width W (Imperial)	2.0
Width W (Metric)	50.8
Thickness T (Imperial)	0.0025
Thickness T (Metric)	64.0
Height H (Imperial)	1.25
Height H (Metric)	31.75

MaterialType 443/281, UV-stabilized flexible white vinyl with clear polyester<br/>laminate (443/281)Material Shortcut443/281

Adhesive	Acrylic
Halogen Free	No
Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Operating Temperature	-40°F to +174°F (-40°C to +79°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	UL 969 NEC2014
Warranty (US)	Yes
UL Recognized (US)	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50
Customs Number	3919102055
Labels per Column	1
Labels per Row	1