HellermannTyton

Specification Sheet

Part Number: MCRI-ENT

Raceway and fittings are manufactured from a UL94 V0 rated material to ensure compliance with codes.

All fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B and 569-A standard.

Raceway and fittings are UL Listed to 600 volts to meet new UL5A and CSA 22.2 No. 62-93 standards.



InfoStream Multi-Channel Raceway Entrance End Fitting, PVC, Ivory, 1/pkg

Article Number 250-00045

Type MCR-ENT

Color Ivory (IV)

Quantity Per bag

Product Description For use as a ceiling drop, conduit transition from end or base of

raceway, or low voltage entrance from end or base of raceway. Includes dual 0.75", 1.0", 1.25", 1.75", 2.0" and 2.5" knockouts.

Short Description InfoStream Multi-Channel Raceway Entrance End Fitting, PVC, Ivory,

1/pkg

Global Part Name MCR-ENT-PVC-BGE

Material Polyvinylchloride (PVC) **Material Shortcut PVC Flammability** UL 94 V-0 **Halogen Free** No **Operating Temperature** +122°F (+50°C) Reach Compliant (Article 33) No **ROHS Compliant** Yes **UL Listed (US and Canada)** Yes **UL Listed (US)** Yes Package Quantity (Imperial) 1

Package Quantity (Metric)

Customs Number 3925900000

1