HellermannTyton

Specification Sheet

Part Number: MCRI-B8

Raceway and fittings are manufactured from a UL94 V0 rated material to ensure compliance with codes.

All fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B and 569-A standard.

Raceway and fittings are UL Listed to 600 volts to meet new UL5A and CSA 22.2 No. 62-93 standards

Base is supplied with prepunched mounting slots every 8".

Raceway base includes adhesive ddouble sided tape for aid in mounting. Raceway must still be properly fastened to the wall per instructions.



InfoStream Multi-Channel Raceway Base With Center Divider, 8 ft Long, PVC, Ivory, 48 ft/pkg

Article Number	250-00032
Туре	MCR-B8
Color	Ivory (IV)
Quantity Per	box

Product Description	The InfoStream® multi-channel surface raceway system is designed
	to organize, protect and route multiple types of cable and wire along
	interior walls. Dividers snap inside raceway to create up to four
	channels to separate and route communication and power cables.
	Manufactured from lightweight PVC material, InfoStream multi-

up to 600 volts.

Short Description InfoStream Multi-Channel Raceway Base With Center Divider, 8 ft

Long, PVC, Ivory, 48 ft/pkg

channel raceway components are UL5A listed and CSA 22.2 rated for

Global Part Name MCR-B8-PVC-BGE

Length L (Imperial) 8.0

Length L (Metric) 2.44

Width W (Imperial) 4.5

Width W (Metric) 114.3

Height H (Imperial) 2.05

Height H (Metric) 52.07

Material Polyvinylchloride (PVC)

Material Shortcut PVC

Flammability UL 94 V-0

No

Operating Temperature +122°F (+50°C)

Reach Compliant (Article 33) No

Halogen Free

ROHS Compliant Yes

UL Listed (US and Canada) Yes

UL Listed (US) Yes

Package Quantity (Imperial) 48

Package Quantity (Metric) 14.63

Customs Number 3925900000

© 2022 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions