

Specification Sheet

Part Number: 556-00460

600 dpi print head for high resolution printing.

Ethernet ready for easy network connectivity.

Print speeds up to 7.87 in / second for fast label production. LCD user interface for easy printer adjustments.

Adjustable gap sensor so that the printer can detect a wide variety of label types.

Floating print head to automatically adjust to varying media thickness such as printable heat shrink tubing.

Optional cutter faceplate for automatic cutting and kitting of printed labels.

Wireless network ready for full production control.

LCD touch screen for easy reference of network status, date, time, print head temperature and ribbon usage.



TTM460 Thermal Transfer Printer, 600 dpi, Gray 1/pkg

Article Number 556-00460

Type TTM460

Color Gray (GY)

Quantity Per EA

| | |
|------------------------------|---|
| Product Description | HellermannTyton's TTM430 and TTM460 Series thermal transfer printers are designed for medium- to high-volume users of thermal transfer labels and ShrinkTrak. Their user-friendly design features a streamlined menu for simple navigation, while the built-in caddy allows even the largest label rolls to fit inside. The optional cutter can cut through the thickest material. The TTM430's 300 dpi print head delivers excellent results and the TTM460's 600 dpi print head provides the highest quality printing available. These printers handle all sizes of HellermannTyton's ShrinkTrak markers and can print on even the smallest labels. |
| Short Description | TTM460 Thermal Transfer Printer, 600 dpi, Gray 1/pkg |
| Global Part Name | TTM460-PL-GY |
| Technical Description | Thermal Transfer Printer, 600 DPI, Gray |
| Length L (Imperial) | 16.0 |
| Length L (Metric) | 406.4 |
| Width W (Imperial) | 9.44 |
| Width W (Metric) | 240 |
| Height H (Imperial) | 12.28 |
| Height H (Metric) | 312 |
| Depth D (Imperial) | 17.12 |
| Depth D (Metric) | 435 |

| | |
|-------------------------------------|---------------------------------|
| Material | Plastic (PL) |
| Material Shortcut | PL |
| Operating Temperature | +40°F to +104°F (+4°C to +40°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 1 |
| Package Quantity (Metric) | 1 |
| Customs Number | 8443321050 |