

External Battery Pack for UPS System - NAFTA assembled version of BP48V60RT-3U

MODEL NUMBER: **BP48V60-3UNAFTA**



Highlights

- Extends runtime of select compatible Tripp Lite UPS Systems with 48VDC external battery connector
- Provides daisy-chain capability
- Simple installation; 3U rackmount, tower and stack adaptable

Package Includes

- BP48V60-3UNAFTA external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

Description

BP48V60-3UNAFTA rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in stacking, upright tower and rackmount applications using only 3 rack spaces (3U). Includes heavy gauge cabling with high current DC connector for simple installation. Additional output connector allows multiple BP48V60-3UNAFTA battery packs to be daisy-chained to the UPS for even longer extended run operation.

COMPATIBLE UPS SYSTEMS - SM2200RMNAFTA, SM3000RMNAFTA, and other Tripp Lite UPS systems that specify the use of this battery pack.

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 3 rack spaces (3U)
- Includes heavy gauge cabling with high current DC connectors for simple installation
- Additional output connector allows multiple BP48V60RT3U battery packs to be daisy-chained to the UPS for even longer extended run operation

Specifications

OVERVIEW	
UPC Code	037332137746
BATTERY	
Expandable Battery Runtime	Blue 2-point battery connector
DC System Voltage (VDC)	48
UPS Connection	Blue 2-point battery connector



Typical Battery Lifespan	4-6 years typical (North America)
PHYSICAL	
Material of Construction	Steel
Form Factors Supported	3U rack/tower
Shipping Dimensions (hwd / cm)	28.58 x 58.42 x 80.01
Shipping Dimensions (hwd / in.)	11.25 x 23.00 x 31.50
Shipping Weight (kg)	92.00
Shipping Weight (lbs.)	202.83
Unit Dimensions (hwd / in.)	5.25 x 17.5 x 25
Unit Dimensions (hwd / cm)	13.3 x 44.4 x 63.5
Unit Weight (lbs.)	163.1
Unit Weight (kg)	73.98
ENVIRONMENTAL	
Operating Temperature	32-104 degrees F / 0-40 degrees C
WARRANTY	
Product Warranty Period (U.S. & Canada)	2-year limited warranty
Product Warranty Period (International)	1-year limited warranty
Product Warranty Period (Mexico)	1-year limited warranty
Product Warranty Period (Puerto Rico)	1-year limited warranty
Optional Coverage	3 year, 5 year, next day and on-site warranty coverage available

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>