



- Specification:
- Electrical Char
 Insulation Resistance: 500MΩ min. 500V DC for 1 minute
 Contact Resistance: 30mΩ max.
 Rating Current: 1.5A max.
 Rating Voltage: 150V AC
 Dielectric Voltage: 1000 Vrms at 1MA 60 sec. min.
 - Physical Char
 Housing: PBT Glass filled (UL 94V-0) Color: Black
 Soldering Temperature: 235°C for 5 sec.
 Spring Wire: 0.35mm thickness Phosphor Bronze
 6u" Gold on contact area,
 gold flash on solder area, all over 50u" Nickel
 Temperature Range: -40°C to +85°C
 Durability: 750 mating cycles min.
 - Packing: Tray

RoHS compliant
Unit:mm

Scale	Free
TOLERANCE	
.XX	±0.20
.XXX	±0.13
.XXXX	±0.05
DIM	TOL
Angle	+0°30'

Id.	Drawn	Modification	Date	Name
①	Drawn		28.10.2015	Amy

Date	Name
28.10.2015	Amy
28.10.2015	Amy

Customer-No.	Drawing-No.	Replace
ASSMANN WSW-No.	A-2004-1-4-R	
	ASS 7037 CO	rev00
		SHEET



1	2	3	4	5	6	7	A
1	2	3	4	5	6	7	A
1	2	3	4	5	6	7	B
1	2	3	4	5	6	7	C
1	2	3	4	5	6	7	D
1	2	3	4	5	6	7	E
1	2	3	4	5	6	7	F
1	2	3	4	5	6	7	G
1	2	3	4	5	6	7	H