

Specification Sheet

Part Number: 121-83355

Kabelrap tie offers a smooth strap providing secure assembly without damaging cables or hoses.

Product Image

Curved head design provides full circumferential compression which offers vibration resistance.

Article Number 121-83355

Type KR8/33

Color Natural (NA)

Quantity Per pcs.

Product Description The patented Kabelrap cable tie design offers a smooth strap which is locked into place with a glass fiber reinforced pin. The curved head design provides full circumferential compression around the bundle or harness. Once applied with the required KR6/8 manual tool, the tie offers a secure and vibration resistant assembly.

Short Description Kabelrap Tie, 13.3" Long, 176lb Tensile Strength, PA66HS, Natural, 50/pkg

Global Part Name KR8/33-PA66HS-NA

Minimum Tensile Strength (Imperial) 176.0

Minimum Tensile Strength (Metric)	785.0
Length L (Imperial)	13.3
Length L (Metric)	337.0
Fixation Method	Cable Tie
Identification Plate Position	none
Releasable Closure	No
Tie Closure	fibreglass pin
Variant	No Serration
Width W (Imperial)	0.32
Width W (Metric)	8.0
Bundle Diameter Min (Imperial)	0.32
Bundle Diameter Min (Metric)	8.0
Bundle Diameter Max (Imperial)	3.4
Bundle Diameter Max (Metric)	86.0
Thickness T (Imperial)	0.091
Thickness T (Metric)	2.3
Cable Tie Head Length (Imperial)	0.31

Cable Tie Head Width (Imperial)	0.46
Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL 94 V-2
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50
Customs Number	3926909988