

## Specification Sheet

Part Number: 156-01796

Delivers high extraction force for reliable performance, yet it's easy to install.

Reusable fastener can be removed from threaded or nonthreaded holes using a 5/16" hex driver.

Heat stabilized material provides excellent resistance to high temperatures.



Blind Hole Mount Outside Serrated Tie 1/4" Thread/Non-Thread Hole, 8", 50lb, PA66HS, Black, 500/bag

<b>Article Number</b>	156-01796
<b>Type</b>	T50ROSBHMB
<b>Color</b>	Black (BK)
<b>Quantity Per</b>	bag

<b>Product Description</b>	HellermannTyton Blind Hole Mount Cable Ties for threaded and nonthreaded holes offer an easy-to-use method for bundling and affixing cables. The 2-piece design includes a heat stabilized cable tie and formula-matched, 1/4" mount that features a low insertion force and aggressively resists pull off. Performs equally well in threaded or nonthreaded blind holes. Mount can slide along cable tie to adjust orientation if needed. Fastener can be removed from hole using a hex driver. This ensures fastener can be reused.
----------------------------	---

<b>Short Description</b>	Blind Hole Mount Outside Serrated Tie 1/4" Thread/Non-Thread Hole, 8", 50lb, PA66HS, Black, 500/bag
<b>Global Part Name</b>	T50ROSBHMB-PA66HS-BK
<b>Minimum Tensile Strength (Imperial)</b>	50.0
<b>Minimum Tensile Strength (Metric)</b>	225.0
<b>Length L (Imperial)</b>	8.0
<b>Length L (Metric)</b>	203.2
<b>Identification Plate Position</b>	none
<b>Width W (Imperial)</b>	0.31
<b>Width W (Metric)</b>	7.8
<b>Bundle Diameter Min (Imperial)</b>	0.10
<b>Bundle Diameter Min (Metric)</b>	2.5
<b>Bundle Diameter Max (Imperial)</b>	1.97
<b>Bundle Diameter Max (Metric)</b>	50.0
<b>Height H (Imperial)</b>	0.736
<b>Height H (Metric)</b>	18.7

<b>Diameter D (Imperial)</b>	0.25
<b>Diameter D (Metric)</b>	6.35
<b>Mounting Hole Diameter D (Imperial)</b>	0.25
<b>Mounting Hole Diameter D (Metric)</b>	6.35 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.246
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.254
<b>Mounting Hole Diameter D Max (Metric)</b>	6.45

**Material** Polyamide 6.6 heat stabilized (PA66HS)

**Material Shortcut** PA66HS

**Material Cable Tie** Polyamide 6.6 heat stabilized (PA66HS)

**Flammability** UL 94 V-2

**Operating Temperature** -40°F to +257°F (-40°C to +125°C)

**Reach Compliant (Article 33)** Yes

**ROHS Compliant** Yes

**Package Quantity (Imperial)** 500

**Package Quantity (Metric)** 500

**Customs Number** 3926909988