

Specification Sheet

Part Number: 596-00824

Pre-Printed Vinyl Solar Labels are made with UV-stable inks and materials for durability and weather resistance.

Supplied with an aggressive adhesive to ensure long life.

Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

Pre-printed labels offer significant time and cost savings over high priced plastic engraved phenolic placards and lead time purchased markers.



FUENTE SENCILLA DE 120 VOLTIOS NO CONECTAR RAMAS DE CIRCUITOS MULTIPOLARES.

Solar Label, Spanish, WARNING 120-VOLT SUPPLY, 3.75" x 2.0", VL, Orange/White, 50/roll

Article Number 596-00824

Type 120VOLTSP

Color Orange (OG)

Quantity Per roll

Product Description

HellermannTyton pre-printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description	Solar Label, Spanish, WARNING 120-VOLT SUPPLY, 3.75" x 2.0", VL, Orange/White, 50/roll
Global Part Name	120VOLTSP-443/281-OG
Technical Description	Pre-Printed Solar Label, Spanish Version, "WARNING - 120-VOLT SUPPLY", 3.75" X 2", Orange/White
Local Order Number 2	English Version: 596-00591
Length L (Imperial)	3.75
Length L (Metric)	95.25
Width W (Imperial)	3.75
Width W (Metric)	95.25
Thickness T (Imperial)	0.0025
Thickness T (Metric)	64.0
Height H (Imperial)	2.0
Height H (Metric)	50.8

Material Type 443/281, UV-stabilized flexible white vinyl with clear polyester laminate (443/281)

Material Shortcut 443/281 Adhesive Acrylic **Halogen Free** No **Adhesive Operating Temperature** -40°F to +174°F (-40°C to +79°C) **Operating Temperature** -40°F to +174°F (-40°C to +79°C) Reach Compliant (Article 33) Yes **ROHS Compliant** Yes **Certification/Specification** UL 969 NEC2017 NEC2014 **UL Recognized (US)** Yes **Package Quantity (Imperial)** 50 Package Quantity (Metric) 50 **Customs Number** 3919102055 1 Labels per Column

Labels per Row

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions