HellermannTyton

Specification Sheet

Part Number: MCRI-C8



Raceway and fittings are manufactured from a UL94 V0 rated material to insure compliance with codes

All fittings have been designed to maintain the required 1" minimum bend radius to meet TIA/EIA-568-B and 569-A standard

Raceway and fittings are UL Listed to 600 volts to meet new UL5A and CSA 22.2 No. 62-93 standards

Patented hinged cover speeds installation time by allowing installer to partially mount cover prior to laying cables

InfoStream Multi-Channel Raceway Cover, 8 ft Long, PVC, Ivory, 48 ft/pkg

Article Number	250-00037
Туре	MCR-C8
Color	Ivory (IV)
Quantity Per	box
Product Description	The InfoStream® multi-channel surface raceway system is designed to organize, protect and route multiple types of cable and wire along interior walls. Dividers snap inside raceway to create up to four channels to separate and route communication and power cables. Manufactured from lightweight PVC material, InfoStream multi- channel raceway components are UL5A listed and CSA 22.2 rated for up to 600 volts.

Short Description	InfoStream Multi-Channel Raceway Cover, 8 ft Long, PVC, Ivory, 48 ft/pkg
Global Part Name	MCR-C8-PVC-BGE
Length L (Imperial)	8.0
Length L (Metric)	2.44
Width W (Imperial)	4.5
Width W (Metric)	114.3
Height H (Imperial)	2.05
Height H (Metric)	52.07
Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	UL 94 V-0
Halogen Free	No
Operating Temperature	+122°F (+50°C)
Reach Compliant (Article 33)	No

ROHS Compliant	Yes
UL Listed (US and Canada)	Yes
UL Listed (US)	Yes
Package Quantity (Imperial)	48
Package Quantity (Metric)	14.63
Customs Number	3925900000

© 2022 HellermannTyton. All Rights Reserved. Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions